

**INTERNATIONAL OBLIGATIONS (ECONOMIC AND ANCILLARY
MEASURES) (IRAN) (AMENDMENT) ORDER, 2010**


Arrangement of Paragraphs

Paragraph

1. Citation.....	2
2. Amends paragraph 2 of the principal Order.....	2
3. Amends paragraph 4 of the principal Order.....	3
4. Repeals and replaces the First and Second Schedules to the principal Order.....	3

FIRST SCHEDULE	4
-----------------------	----------

SECOND SCHEDULE	98
------------------------	-----------

N.J No 135 of 2010
Extraordinary Gazette dated 06/12/10
Signature. 

**INTERNATIONAL OBLIGATIONS (ECONOMIC AND ANCILLARY
MEASURES) ACT
(CHAPTER 16)**

**INTERNATIONAL OBLIGATIONS (ECONOMIC AND ANCILLARY
MEASURES) (IRAN) (AMENDMENT) ORDER, 2010**

The Governor-General, in exercise of the powers conferred by section 3 of the International Obligations (Economic and Ancillary Measures) Act, makes the following Order —

1. Citation.

This Order, which amends the International Obligations (Economic and Ancillary Measures) (Iran) Order,¹ may be cited as the International Obligations (Economic and Ancillary Measures) (Iran) (Amendment) Order, 2010.

2. Amends paragraph 2 of the principal Order.

Paragraph 2 of the principal Order is amended —

- (a) in subparagraph (a) —
- (i) in sub-subparagraph (i), by deleting the words “INFCIRC/254/Rev.8/Part 1 in document S/2006/814” and substituting therefor the words, “document INFCIRC/254/Rev.9/Part 1”;
 - (ii) in sub-subparagraph (ii), by deleting the words “INFCIRC/254/Rev.8/Part 1 in document S/2006/814” and substituting therefor the words “document INFCIRC/254/Rev.9/Part 1”;
 - (iii) in sub-subparagraph (iii), by deleting the words “S/2006/815” and substituting therefor the words “S/2010/263”;
 - (iv) in sub-subparagraph (v), by deleting the words “of document S/2006/814”;
 - (v) in sub-subparagraph (vi), by deleting the words “S/2006/814 or S/2006/815” and substituting therefor the words, “INFCIRC/254/Rev.9/Part 1, INFCIRC/254/Rev.7/Part 2 and S/2010/263”;

¹S. I. No. 105 of 2008.

(vi) by inserting, immediately after sub-subparagraph (vii), the following as a new sub-subparagraph (viii) —

“(viii) battle tanks, armoured combat vehicles, large calibre artillery systems, combat aircraft, attack helicopters, warships, missiles or missile systems as defined for the purpose of the United Nations Register of Conventional Arms, or related materiel, including spare parts, or items as determined by the Committee;”;

(b) in subparagraph (e), by deleting the word “and”, immediately after the words “First Schedule;”;

(c) in subparagraph (f), by deleting the full-stop and substituting therefor a semi-colon;

(d) by inserting, immediately after subparagraph (f), the following as a new subparagraph (g) —

“(g) provide bunkering services such as provision of fuel or supplies, or other servicing of vessels, to Iranian-owned or-contracted vessels, including chartered vessels, if there is reasonable grounds to believe that the vessels are carrying items specified in the First Schedule, unless provision of such services is necessary for humanitarian purposes, or until such time as the cargo has been inspected, seized and disposed of, if necessary.”.

3. Amends paragraph 4 of the principal Order.

Paragraph 4 of the principal Order is amended, in subparagraph (a), by deleting the figures (3i), and substituting therefor the figure (i).

4. Repeals and replaces the First and Second Schedules to the principal Order.

The First and Second Schedules to the principal Order are repealed and replaced by the following —

Information Circular

INFCIRC/254/Rev.9/Part 1^a

Date: 7 November 2007

General Distribution

Original: English

Communication Received from the Permanent Mission of Brazil regarding Certain Member States' Guidelines for the Export of Nuclear Material, Equipment and Technology

1. The Agency has received a Note Verbale from the Permanent Mission of Brazil, dated 22 March 2007, in which it requests that the Agency circulate to all Member States a letter of 12 December 2006 from the Chairman of the Nuclear Suppliers Group, Ambassador José Artur Denot Medeiros, to the Director General, on behalf of the Governments of Argentina, Australia, Austria, Belarus, Belgium, Brazil, Bulgaria, Canada, China, Croatia, Cyprus, Czech Republic, Denmark, Estonia, Finland, France, Germany, Greece, Hungary, Ireland, Italy, Japan, Kazakhstan, Republic of Korea, Latvia, Lithuania, Luxemburg, Malta, Netherlands, New Zealand, Norway, Poland, Portugal, Romania, Russian Federation, Slovakia, Slovenia, South Africa, Spain, Sweden, Switzerland, Turkey, Ukraine, the United Kingdom of Great Britain and Northern Ireland and the United States of America, providing further information on those Governments' Guidelines for Nuclear Transfers^b:
2. In the light of the wish expressed in the above-mentioned Note Verbale, the text of the Note Verbale, as well as the letter and attachment thereto, are hereby reproduced for the information of all Member States.

^a INFCIRC/254/Part 2, as amended, contains Guidelines for Transfers of Nuclear-Related Dual-Use Equipment, Materials, Software and Related Technology

^b The European Commission participates as an observer.


IAEA/NR. 69 /2007

The Permanent Mission of Brazil to the IAEA and to the PrepCom/CTBTO presents its compliments to the IAEA and has the honour to forward a letter, dated December 12, 2006 by Ambassador José Artur Denot Medeiros, current Chairman of the NSG, regarding the agreed amendments to INFCIRC 254/ Part 1 (the NSG Part 1 Guidelines), to be conveyed to the Director General of the International Atomic Energy Agency, Dr. Mohamed ELBARADEI.

2. The Permanent Mission has the honour to request that the abovementioned amendments to INFCIRC 254/Part 1 be circulated among the the Member States of the IAEA.

The Permanent Mission of Brazil to the IAEA and to the PrepCom/CTBTO avails itself of this opportunity to renew to the IAEA the assurances of its highest consideration.

Vienna, 22 March 2007



CHAIRMAN OF THE NUCLEAR SUPPLIERS GROUP

Ministry of External Relations of Brazil
Esplanada dos Ministérios – Bloco H – Anexo I – Sala 728
Brasília – DF – Brazil. CEP 70170-900

Tel: +55 61 34118660 Fax: +55 61 34119478
E-mail: denot@mre.gov.br

Brasília, December 12, 2006.

On behalf of the Governments of Argentina, Australia, Austria, Belarus, Belgium, Brazil, Bulgaria, Canada, China, Croatia, Cyprus, Czech Republic, Denmark, Estonia, Finland, France, Germany, Greece, Hungary, Ireland, Italy, Japan, Kazakhstan, Republic of Korea, Latvia, Lithuania, Luxemburg, Malta, Netherlands, New Zealand, Norway, Poland, Portugal, Romania, Russian Federation, Slovakia, Slovenia, South Africa, Spain, Sweden, Switzerland, Turkey, Ukraine, United Kingdom, and United States¹, I have the honour to refer to all previous relevant communications from these Governments concerning their decisions to act in accordance with the Guidelines for Nuclear Transfers currently published as document INFCIRC/254/Rev.8/Part1, including its Annexes.

These Governments have decided to amend the Part 1 Guidelines, in order to more clearly define the standard of implementation that all Participating Governments of the Nuclear Suppliers Group (NSG) regard as essential for the fulfillment of the Guidelines, as follows:

- A new General Note 3 was added to Annex A, in order to call upon all NSG Participating Governments to implement the necessary domestic controls to properly control stable isotope separation equipment and technology.
- A new Introductory Note to Section 5 of Annex B was added to the Guidelines in order to allow Participating Governments flexibility in how controls on plants, equipment and technology for the separation of stable isotopes are implemented on a national basis, to add further “control” weight by its position in Annex B, and finally, to provide overall guidance with regard to gradations of concern depending on the isotope separation process.
- In order to expand the scope of control to include separation techniques for “special fissionable material” and in order to harmonize the NSG Trigger List with that of the Zangger Committee, a new amendment was added to Section 2.5 of Annex A and Section 5 of Annex B.

¹ The European Commission participates as an observer.



- So as to close a loophole in the existing controls for special shut-off and control valves for use in main or auxiliary system of gas centrifuge enrichment plants, a new Section 5.2.3 of Annex B was introduced to the NSG Trigger List to include valves especially designed or prepared for gas centrifuge enrichment plants (UF₆-resistant bellows sealed valves). All subsequent Sections were accordingly renumbered.

In the interest of clarity, the complete text of the modified Guidelines and its Annexes is reproduced in the attachment, as well as a "Comparison Table of Changes to the Guidelines for Nuclear Transfers (INFCIRC/254/Rev.8/Part 1)."

These Governments have decided to act in accordance with the Guidelines so revised and to implement them in accordance with their respective national legislation.


In reaching this decision, these Governments are fully aware of the need to contribute to economic development while avoiding contributing in any way to a proliferation of nuclear weapons or other nuclear explosive devices or the diversion to acts of nuclear terrorism, and of the need to separate the issue of non-proliferation or non-diversion assurances from that of commercial competition.

Insofar as trade within the European Union is concerned, the Governments that are Member States of the European Union will implement this decision in the light of its commitments as a Member State of the Union.

I would be grateful if you would bring this Note and its attachment to the attention of all Member States of the IAEA.

On behalf of the above Governments I wish to avail myself of this opportunity to renew to you the assurances of the Governments' highest consideration.

Yours sincerely,



José Artur Denot Medeiros
Chairman of the Nuclear Suppliers Group

H.E. Dr. Mohamed ELBARADEI
Director General
International Atomic Energy Agency
Vienna

GUIDELINES FOR NUCLEAR TRANSFERS

1. The following fundamental principles for safeguards and export controls should apply to nuclear transfers for peaceful purposes to any non-nuclear-weapon State and, in the case of controls on retransfer, to transfers to any State. In this connection, suppliers have defined an export trigger list.

Prohibition on nuclear explosives

2. Suppliers should authorize transfer of items or related technology identified in the trigger list only upon formal governmental assurances from recipients explicitly excluding uses which would result in any nuclear explosive device.

Physical protection

3. (a) All nuclear materials and facilities identified by the agreed trigger list should be placed under effective physical protection to prevent unauthorized use and handling. The levels of physical protection to be ensured in relation to the type of materials, equipment and facilities, have been agreed by the suppliers, taking account of international recommendations.

(b) The implementation of measures of physical protection in the recipient country is the responsibility of the Government of that country. However, in order to implement the terms agreed upon amongst suppliers, the levels of physical protection on which these measures have to be based should be the subject of an agreement between supplier and recipient.

(c) In each case special arrangements should be made for a clear definition of responsibilities for the transport of trigger list items.

Safeguards

4. (a) Suppliers should transfer trigger list items or related technology to a non-nuclear weapon State only when the receiving State has brought into force an agreement with the IAEA requiring the application of safeguards on all source and special fissionable material in its current and future peaceful activities. Suppliers should authorize such transfers only upon formal governmental assurances from the recipient that:
 - if the above-mentioned agreement should be terminated the recipient will bring into force an agreement with the IAEA based on existing IAEA model safeguards agreements requiring the application of safeguards on all trigger list items or related technology transferred by the supplier or processed, or produced or used in connection with such transfers; and
 - if the IAEA decides that the application of IAEA safeguards is no longer possible, the supplier and recipient should elaborate appropriate verification measures. If the recipient does not accept these measures, it should allow at the request of the supplier the restitution of transferred and derived trigger list items.

- (b) Transfers covered by paragraph 4 (a) to a non-nuclear-weapon State without such a safeguards agreement should be authorized only in exceptional cases when they are deemed essential for the safe operation of existing facilities and if safeguards are applied to those facilities. Suppliers should inform and, if appropriate, consult in the event that they intend to authorize or to deny such transfers.
 - (c) The policy referred to in paragraph 4 (a) and 4 (b) does not apply to agreements or contracts drawn up on or prior to April 3, 1992. In case of countries that have adhered or will adhere to INFCIRC/254/Rev. 1/Part 1 later than April 3, 1992, the policy only applies to agreements (to be) drawn up after their date of adherence.
 - (d) Under agreements to which the policy referred to in paragraph 4 (a) does not apply (see paragraphs 4 (b) and (c)) suppliers should transfer trigger list items or related technology only when covered by IAEA safeguards with duration and coverage provisions in conformity with IAEA doc. GOV/1621. However, suppliers undertake to strive for the earliest possible implementation of the policy referred to in paragraph 4 (a) under such agreements.
 - (e) Suppliers reserve the right to apply additional conditions of supply as a matter of national policy.
5. Suppliers will jointly reconsider their common safeguards requirements, whenever appropriate.

Special controls on sensitive exports

6. Suppliers should exercise restraint in the transfer of sensitive facilities, technology and material usable for nuclear weapons or other nuclear explosive devices. If enrichment or reprocessing facilities, equipment or technology are to be transferred, suppliers should encourage recipients to accept, as an alternative to national plants, supplier involvement and/or other appropriate multinational participation in resulting facilities. Suppliers should also promote international (including IAEA) activities concerned with multinational regional fuel cycle centres.

Special controls on export of enrichment facilities, equipment and technology

7. For a transfer of an enrichment facility, or technology therefor, the recipient nation should agree that neither the transferred facility, nor any facility based on such technology, will be designed or operated for the production of greater than 20% enriched uranium without the consent of the supplier nation, of which the IAEA should be advised.

Controls on supplied or derived material usable for nuclear weapons or other nuclear explosive devices

8. Suppliers should, in order to advance the objectives of these guidelines and to provide opportunities further to reduce the risks of proliferation, include, whenever appropriate and practicable, in agreements on supply of nuclear materials or of facilities which produce material usable for nuclear weapons or other nuclear explosive devices, provisions calling for mutual agreement between the supplier and the recipient on

arrangements for reprocessing, storage, alteration, use, transfer or retransfer of any material usable for nuclear weapons or other nuclear explosive devices involved.

Controls on retransfer

9. (a) Suppliers should transfer trigger list items or related technology only upon the recipient's assurance that in the case of:

(1) retransfer of such items or related technology,

or

(2) transfer of trigger list items derived from facilities originally transferred by the supplier, or with the help of equipment or technology originally transferred by the supplier;

the recipient of the retransfer or transfer will have provided the same assurances as those required by the supplier for the original transfer.

(b) In addition the supplier's consent should be required for:

(1) any retransfer of trigger list items or related technology and any transfer referred to under paragraph 9(a) (2) from any State which does not require full scope safeguards, in accordance with paragraph 4(a) of these Guidelines, as a condition of supply;

(2) any retransfer of enrichment, reprocessing or heavy water production facilities, equipment or related technology, and for any transfer of facilities or equipment of the same type derived from items originally transferred by the supplier;

(3) any retransfer of heavy water or material usable for nuclear weapons or other nuclear explosive devices.

(c) To ensure the consent right as defined under paragraph 9(b), government to government assurances will be required for any relevant original transfer.

(d) Suppliers should consider restraint in the transfer of items and related technology identified in the trigger list if there is a risk of retransfers contrary to the assurances given under paragraph 9(a) and (c) as a result of a failure by the recipient to develop and maintain appropriate, effective national export and transshipment controls, as identified by UNSC Resolution 1540.

Non-proliferation Principle

10. Notwithstanding other provisions of these Guidelines, suppliers should authorize transfer of items or related technology identified in the trigger list only when they are satisfied that the transfers would not contribute to the proliferation of nuclear weapons or other nuclear explosive devices or be diverted to acts of nuclear terrorism.

Implementation

11. Suppliers should have in place legal measures to ensure the effective implementation of the Guidelines, including export licensing regulations, enforcement measures, and penalties for violations.

SUPPORTING ACTIVITIES

Physical security

12. Suppliers should promote international co-operation in the areas of physical security through the exchange of physical security information, protection of nuclear materials in transit, and recovery of stolen nuclear materials and equipment. Suppliers should promote broadest adherence to the respective international instruments, inter alia, to the Convention on the Physical Protection of Nuclear Material, as well as implementation of INFCIRC/225, as amended from time to time. Suppliers recognize the importance of these activities and other relevant IAEA activities in preventing the proliferation of nuclear weapons and countering the threat of nuclear terrorism.

Support for effective IAEA safeguards

13. Suppliers should make special efforts in support of effective implementation of IAEA safeguards. Suppliers should also support the Agency's efforts to assist Member States in the improvement of their national systems of accounting and control of nuclear material and to increase the technical effectiveness of safeguards.

Similarly, they should make every effort to support the IAEA in increasing further the adequacy of safeguards in the light of technical developments and the rapidly growing number of nuclear facilities, and to support appropriate initiatives aimed at improving the effectiveness of IAEA safeguards.

Trigger list plant design features

14. Suppliers should encourage the designers and makers of trigger list facilities to construct them in such a way as to facilitate the application of safeguards and to enhance physical protection, taking also into consideration the risk of terrorist attacks. Suppliers should promote protection of information on the design of trigger list installations, and stress to recipients the necessity of doing so. Suppliers also recognize the importance of including safety and non-proliferation features in designing and construction of trigger list facilities.

Export Controls

15. Suppliers should, where appropriate, stress to recipients the need to subject transferred trigger list items and related technology and trigger list items derived from facilities originally transferred by the supplier or with the help of equipment or technology originally transferred by the supplier to export controls as outlined in UNSC Resolution 1540. Suppliers are encouraged to offer assistance to recipients to fulfil their respective obligations under UNSC Resolution 1540 where appropriate and feasible.

Consultations

16. (a) Suppliers should maintain contact and consult through regular channels on matters connected with the implementation of these Guidelines.
- (b) Suppliers should consult, as each deems appropriate, with other governments concerned on specific sensitive cases, to ensure that any transfer does not contribute to risks of conflict or instability.
- (c) Without prejudice to sub-paragraphs (d) to (f) below:
- In the event that one or more suppliers believe that there has been a violation of supplier/recipient understanding resulting from these Guidelines, particularly in the case of an explosion of a nuclear device, or illegal termination or violation of IAEA safeguards by a recipient, suppliers should consult promptly through diplomatic channels in order to determine and assess the reality and extent of the alleged violation. Suppliers are also encouraged to consult where nuclear material or nuclear fuel cycles activity undeclared to the IAEA or a nuclear explosive activity is revealed.
 - Pending the early outcome of such consultations, suppliers will not act in a manner that could prejudice any measure that may be adopted by other suppliers concerning their current contacts with that recipient. Each supplier should also consider suspending transfers of Trigger List items while consultations under 16(c) are ongoing, pending supplier agreement on an appropriate response.
 - Upon the findings of such consultations, the suppliers, bearing in mind Article XII of the IAEA Statute, should agree on an appropriate response and possible action, which could include the termination of nuclear transfers to that recipient.
- (d) If a recipient is reported by the IAEA to be in breach of its obligation to comply with its safeguards agreement, suppliers should consider the suspension of the transfer of Trigger List items to that State whilst it is under investigation by the IAEA. For the purposes of this paragraph, “breach” refers only to serious breaches of proliferation concern;
- (e) Suppliers support the suspension of transfers of Trigger List items to States that violate their nuclear non-proliferation and safeguards obligations, recognising that the responsibility and authority for such decisions rests with national governments or the United Nations Security Council. In particular, this is applicable in situations where the IAEA Board of Governors takes any of the following actions:
- finds, under Article XII.C of the Statute, that there has been non-compliance in the recipient, or requires a recipient to take specific actions to bring itself into compliance with its safeguards obligations;
 - Decides that the Agency is not able to verify that there has been no diversion of nuclear material required to be safeguarded, including situations where actions taken by a recipient have made the IAEA unable to carry out its safeguards mission in that State.

An extraordinary Plenary meeting will take place within one month of the Board of Governors' action, at which suppliers will review the situation, compare national policies and decide on an appropriate response.

(f) The provisions of subparagraph (e) above do not apply to transfers under paragraph 4 (b) of the Guidelines.

17. Unanimous consent is required for any changes in these Guidelines, including any which might result from the reconsideration mentioned in paragraph 5.

ANNEX A
TRIGGER LIST REFERRED TO IN GUIDELINES

GENERAL NOTES

1. The object of these controls should not be defeated by the transfer of component parts. Each government will take such actions as it can to achieve this aim and will continue to seek a workable definition for component parts, which could be used by all suppliers.
2. With reference to Paragraph 9(b)(2) of the Guidelines, *same type* should be understood as when the design, construction or operating processes are based on the same or similar physical or chemical processes as those identified in the Trigger List.
3. Suppliers recognize the close relationship for certain isotope separation processes between plants, equipment and technology for uranium enrichment and that for the separation of stable isotopes for research, medical and other non-nuclear industrial purposes. In that regard, suppliers should carefully review their legal measures, including export licensing regulations and information/technology classification and security practices, for stable isotope separation activities to ensure the implementation of appropriate protection measures as warranted. Suppliers recognize that, in particular cases, appropriate protection measures for stable isotope separation activities will be essentially the same as those for uranium enrichment. (See Introductory Note in Section 5 of the Trigger List.) In accordance with Paragraph 16(a) of the Guidelines, suppliers shall consult with other suppliers as appropriate, in order to promote uniform policies and procedures in the transfer and protection of stable isotope separation plants, equipment and technology.

TECHNOLOGY CONTROLS

The transfer of "technology" directly associated with any item in the List will be subject to as great a degree of scrutiny and control as will the item itself, to the extent permitted by national legislation.

Controls on "technology" transfer do not apply to information "in the public domain" or to "basic scientific research".

In addition to controls on "technology" transfer for nuclear non-proliferation reasons, suppliers should promote protection of this technology for the design, construction, and operation of trigger list facilities in consideration of the risk of terrorist attacks, and should stress to recipients the necessity of doing so.

DEFINITIONS

"Technology" means specific information required for the "development", "production", or "use" of any item contained in the List. This information may take the form of "technical data", or "technical assistance".

"Basic scientific research" - Experimental or theoretical work undertaken principally to acquire new knowledge of the fundamental principles of phenomena and observable facts, not primarily directed towards a specific practical aim or objective.

"development" - is related to all phases before "production" such as:

- design
- design research
- design analysis
- design concepts
- assembly and testing of prototypes
- pilot production schemes
- design data
- process of transforming design data into a product
- configuration design
- integration design
- layouts

"in the public domain" - "In the public domain," as it applies herein, means technology that has been made available without restrictions upon its further dissemination. (Copyright restrictions do not remove technology from being in the public domain.)

"production" - means all production phases such as:

- construction
- production engineering
- manufacture
- integration
- assembly (mounting)
- inspection
- testing
- quality assurance

"technical assistance" - "Technical assistance" may take forms such as: instruction, skills, training, working knowledge, consulting services.

Note: "Technical assistance" may involve transfer of "technical data".

"technical data" - "Technical data" may take forms such as blueprints, plans, diagrams, models, formulae, engineering designs and specifications, manuals and instructions written or recorded on other media or devices such as disk, tape, read-only memories.

"use" - Operation, installation (including on-site installation), maintenance (checking), repair, overhaul and refurbishing.

MATERIAL AND EQUIPMENT

1. Source and special fissionable material

As defined in Article XX of the Statute of the International Atomic Energy Agency:

1.1. "Source material"

The term "source material" means uranium containing the mixture of isotopes occurring in nature; uranium depleted in the isotope 235; thorium; any of the foregoing in the form of metal, alloy, chemical compound, or concentrate; any other material containing one or more of the foregoing in such concentration as the Board of Governors shall from time to time determine; and such other material as the Board of Governors shall from time to time determine.

1.2. "Special fissionable material"

- i) The term "special fissionable material" means plutonium-239; uranium-233; uranium enriched in the isotopes 235 or 233; any material containing one or more of the foregoing; and such other fissionable material as the Board of Governors shall from time to time determine; but the term "special fissionable material" does not include source material.
- ii) The term "uranium enriched in the isotopes 235 or 233" means uranium containing the isotopes 235 or 233 or both in an amount such that the abundance ratio of the sum of these isotopes to the isotope 238 is greater than the ratio of the isotope 235 to the isotope 238 occurring in nature.

However, for the purposes of the Guidelines, items specified in subparagraph (a) below, and exports of source or special fissionable material to a given recipient country, within a period of 12 months, below the limits specified in subparagraph (b) below, shall not be included:

- (a) Plutonium with an isotopic concentration of plutonium-238 exceeding 80%.

Special fissionable material when used in gram quantities or less as a sensing component in instruments; and

Source material which the Government is satisfied is to be used only in non-nuclear activities, such as the production of alloys or ceramics;

- (b) Special fissionable material 50 effective grams;
 Natural uranium 500 kilograms;
 Depleted uranium 1000 kilograms; and
 Thorium 1000 kilograms.

2. Equipment and Non-nuclear Materials

The designation of items of equipment and non-nuclear materials adopted by the Government is as follows (quantities below the levels indicated in the Annex B being regarded as insignificant for practical purposes):

- 2.1. Nuclear reactors and especially designed or prepared equipment and components therefor (see Annex B, section 1.);**
- 2.2. Non-nuclear materials for reactors (see Annex B, section 2.);**
- 2.3. Plants for the reprocessing of irradiated fuel elements, and equipment especially designed or prepared therefor (see Annex B, section 3.);**
- 2.4. Plants for the fabrication of nuclear reactor fuel elements, and equipment especially designed or prepared therefor (see Annex B, section 4.);**
- 2.5. Plants for the separation of isotopes of natural uranium, depleted uranium or special fissionable material and equipment, other than analytical instruments, especially designed or prepared therefor (see Annex B, section 5.);**
- 2.6. Plants for the production or concentration of heavy water, deuterium and deuterium compounds and equipment especially designed or prepared therefor (see Annex B, section 6.);**
- 2.7. Plants for the conversion of uranium and plutonium for use in the fabrication of fuel elements and the separation of uranium isotopes as defined in sections 4 and 5 respectively, and equipment especially designed or prepared therefor (See Annex B, section 7.).**

ANNEX B
CLARIFICATION OF ITEMS ON THE TRIGGER LIST
(as designated in Section 2 of MATERIAL AND EQUIPMENT of Annex A)

1. Nuclear reactors and especially designed or prepared equipment and components therefor

1.1. Complete nuclear reactors

Nuclear reactors capable of operation so as to maintain a controlled self-sustaining fission chain reaction, excluding zero energy reactors, the latter being defined as reactors with a designed maximum rate of production of plutonium not exceeding 100 grams per year.

EXPLANATORY NOTE

A "nuclear reactor" basically includes the items within or attached directly to the reactor vessel, the equipment which controls the level of power in the core, and the components which normally contain or come in direct contact with or control the primary coolant of the reactor core.

It is not intended to exclude reactors which could reasonably be capable of modification to produce significantly more than 100 grams of plutonium per year. Reactors designed for sustained operation at significant power levels, regardless of their capacity for plutonium production are not considered as "zero energy reactors".

EXPORTS

The export of the whole set of major items within this boundary will take place only in accordance with the procedures of the Guidelines. Those individual items within this functionally defined boundary which will be exported only in accordance with the procedures of the Guidelines are listed in paragraphs 1.2. to 1.10. The Government reserves to itself the right to apply the procedures of the Guidelines to other items within the functionally defined boundary.

1.2. Nuclear reactor vessels

Metal vessels, or major shop-fabricated parts therefor, especially designed or prepared to contain the core of a nuclear reactor as defined in paragraph 1.1. above, as well as relevant reactor internals as defined in paragraph 1.8. below.

EXPLANATORY NOTE

The reactor vessel head is covered by item 1.2. as a major shop-fabricated part of a reactor vessel.

1.3. Nuclear reactor fuel charging and discharging machines

Manipulative equipment especially designed or prepared for inserting or removing fuel in a nuclear reactor as defined in paragraph 1.1. above.

EXPLANATORY NOTE

The items noted above are capable of on-load operation or at employing technically sophisticated positioning or alignment features to allow complex off-load fueling operations such as those in which direct viewing of or access to the fuel is not normally available.

1.4. Nuclear reactor control rods and equipment

Especially designed or prepared rods, support or suspension structures therefor, rod drive mechanisms or rod guide tubes to control the fission process in a nuclear reactor as defined in paragraph 1.1. above.

1.5. Nuclear reactor pressure tubes

Tubes which are especially designed or prepared to contain fuel elements and the primary coolant in a reactor as defined in paragraph 1.1. above at an operating pressure in excess of 50 atmospheres.

1.6. Zirconium tubes

Zirconium metal and alloys in the form of tubes or assemblies of tubes, and in quantities exceeding 500 kg for any one recipient country in any period of 12 months, especially designed or prepared for use in a reactor as defined in paragraph 1.1. above, and in which the relation of hafnium to zirconium is less than 1:500 parts by weight.

1.7. Primary coolant pumps

Pumps especially designed or prepared for circulating the primary coolant for nuclear reactors as defined in paragraph 1.1. above.

EXPLANATORY NOTE

Especially designed or prepared pumps may include elaborate sealed or multi-sealed systems to prevent leakage of primary coolant, canned-driven pumps, and pumps with inertial mass systems. This definition encompasses pumps certified to Section III, Division I, Subsection NB (Class 1 components) of the American Society of Mechanical Engineers (ASME) Code, or equivalent standards.

1.8. Nuclear reactor internals

"Nuclear reactor internals" especially designed or prepared for use in a nuclear reactor as defined in paragraph 1.1 above, including support columns for the core, fuel channels, thermal shields, baffles, core grid plates, and diffuser plates.

EXPLANATORY NOTE

"Nuclear reactor internals" are major structures within a reactor vessel which have one or more functions such as supporting the core, maintaining fuel alignment, directing primary coolant flow, providing radiation shields for the reactor vessel, and guiding in-core instrumentation.

1.9. Heat exchangers

Heat exchangers (steam generators) especially designed or prepared for use in the primary coolant circuit of a nuclear reactor as defined in paragraph 1.1 above.

EXPLANATORY NOTE

Steam generators are especially designed or prepared to transfer the heat generated in the reactor (primary side) to the feed water (secondary side) for steam generation. In the case of a liquid metal fast breeder reactor for which an intermediate liquid metal coolant loop is also present, the heat exchangers for transferring heat from the primary side to the intermediate coolant circuit are understood to be within the scope of control in addition to the steam generator. The scope of control for this entry does not include heat exchangers for the emergency cooling system or the decay heat cooling system.

1.10. Neutron detection and measuring instruments

Especially designed or prepared neutron detection and measuring instruments for determining neutron flux levels within the core of a reactor as defined in paragraph 1.1. above.

EXPLANATORY NOTE

The scope of this entry encompasses in-core and ex-core instrumentation which measure flux levels in a large range, typically from 10^4 neutrons per cm^2 per second to 10^{10} neutrons per cm^2 per second or more. Ex-core refers to those instruments outside the core of a reactor as defined in paragraph 1.1. above, but located within the biological shielding.

2. Non-nuclear materials for reactors

2.1. Deuterium and heavy water

Deuterium, heavy water (deuterium oxide) and any other deuterium compound in which the ratio of deuterium to hydrogen atoms exceeds 1:5000 for use in a nuclear reactor as defined in paragraph 1.1. above in quantities exceeding 200 kg of deuterium atoms for any one recipient country in any period of 12 months.

2.2. Nuclear grade graphite

Graphite having a purity level better than 5 parts per million boron equivalent and with a density greater than 1.50 g/cm³ for use in a nuclear reactor as defined in paragraph 1.1 above, in quantities exceeding 30 metric tons for any one recipient country in any period of 12 months.

EXPLANATORY NOTE

For the purpose of export control, the Government will determine whether or not the exports of graphite meeting the above specifications are for nuclear reactor use.

Boron equivalent (BE) may be determined experimentally or is calculated as the sum of BE_Z for impurities (excluding BE_{carbon} since carbon is not considered an impurity) including boron, where:

BE_Z (ppm) = CF x concentration of element Z (in ppm);

CF is the conversion factor: ($\sigma_z \times A_B$) divided by ($\sigma_B \times A_z$);

σ_B and σ_z are the thermal neutron capture cross sections (in barns) for naturally occurring boron and

element Z respectively; and A_B and A_z are the atomic masses of naturally occurring boron and element Z respectively.

3. Plants for the reprocessing of irradiated fuel elements, and equipment especially designed or prepared therefor

INTRODUCTORY NOTE

Reprocessing irradiated nuclear fuel separates plutonium and uranium from intensely radioactive fission products and other transuranic elements. Different technical processes can accomplish this separation. However, over the years Purex has become the most commonly used and accepted process. Purex involves the dissolution of irradiated nuclear fuel in nitric acid, followed by separation of the uranium, plutonium, and fission products by solvent extraction using a mixture of tributyl phosphate in an organic diluent.

Purex facilities have process functions similar to each other, including: irradiated fuel element chopping, fuel dissolution, solvent extraction, and process liquor storage. There may also be equipment for thermal denitration of uranium nitrate, conversion of plutonium nitrate to oxide or metal, and treatment of fission product waste liquor to a form suitable for long term storage or disposal. However, the specific type and configuration of the equipment performing these functions may differ between Purex facilities for several reasons, including the type and quantity of irradiated nuclear fuel to be reprocessed and the intended disposition of the recovered materials, and the safety and maintenance philosophy incorporated into the design of the facility.

A "plant for the reprocessing of irradiated fuel elements", includes the equipment and components which normally come in direct contact with and directly control the irradiated fuel and the major nuclear material and fission product processing streams.

These processes, including the complete systems for plutonium conversion and plutonium metal production, may be identified by the measures taken to avoid criticality (e.g. by geometry), radiation exposure (e.g. by shielding), and toxicity hazards (e.g. by containment).

EXPORTS

The export of the whole set of major items within this boundary will take place only in accordance with the procedures of the Guidelines.

The Government reserves to itself the right to apply the procedures of the Guidelines to other items within the functionally defined boundary as listed below.

Items of equipment that are considered to fall within the meaning of the phrase "and equipment especially designed or prepared" for the reprocessing of irradiated fuel elements include:

3.1. Irradiated fuel element chopping machines

INTRODUCTORY NOTE

This equipment breaches the cladding of the fuel to expose the irradiated nuclear material to dissolution. Especially designed metal cutting shears are the most commonly employed, although advanced equipment, such as lasers, may be used.

Remotely operated equipment especially designed or prepared for use in a reprocessing plant as identified above and intended to cut, chop or shear irradiated nuclear fuel assemblies, bundles or rods.

3.2. Dissolvers

INTRODUCTORY NOTE

Dissolvers normally receive the chopped-up spent fuel. In these critically safe vessels, the irradiated nuclear material is dissolved in nitric acid and the remaining hulls removed from the process stream.

Critically safe tanks (e.g. small diameter, annular or slab tanks) especially designed or prepared for use in a reprocessing plant as identified above, intended for dissolution of irradiated nuclear fuel and which are capable of withstanding hot, highly corrosive liquid, and which can be remotely loaded and maintained.

3.3. Solvent extractors and solvent extraction equipment

INTRODUCTORY NOTE

Solvent extractors both receive the solution of irradiated fuel from the dissolvers and the organic solution which separates the uranium, plutonium, and fission products. Solvent extraction equipment is normally designed to meet strict operating parameters, such as long operating lifetimes with no maintenance requirements or adaptability to easy replacement, simplicity of operation and control, and flexibility for variations in process conditions.

Especially designed or prepared solvent extractors such as packed or pulse columns, mixer settlers or centrifugal contactors for use in a plant for the reprocessing of irradiated fuel. Solvent extractors must be resistant to the corrosive effect of nitric acid. Solvent extractors are normally fabricated to extremely high standards (including special welding and inspection and quality assurance and quality control techniques) out of low carbon stainless steels, titanium, zirconium, or other high quality materials.

3.4. Chemical holding or storage vessels

INTRODUCTORY NOTE

Three main process liquor streams result from the solvent extraction step. Holding or storage vessels are used in the further processing of all three streams, as follows:

- (a) The pure uranium nitrate solution is concentrated by evaporation and passed to a denitration process where it is converted to uranium oxide. This oxide is re-used in the nuclear fuel cycle.
- (b) The intensely radioactive fission products solution is normally concentrated by evaporation and stored as a liquor concentrate. This concentrate may be subsequently evaporated and converted to a form suitable for storage or disposal.
- (c) The pure plutonium nitrate solution is concentrated and stored pending its transfer to further process steps. In particular, holding or storage vessels for plutonium solutions are designed to avoid criticality problems resulting from changes in concentration and form of this stream.

Especially designed or prepared holding or storage vessels for use in a plant for the reprocessing of irradiated fuel. The holding or storage vessels must be resistant to the corrosive effect of nitric acid. The holding or storage vessels are normally fabricated of materials such as low carbon stainless steels, titanium or zirconium, or other high quality materials. Holding or storage vessels may be designed for remote operation and maintenance and may have the following features for control of nuclear criticality:

- (1) walls or internal structures with a boron equivalent of at least two per cent, or
- (2) a maximum diameter of 175 mm (7 in) for cylindrical vessels, or
- (3) a maximum width of 75 mm (3 in) for either a slab or annular vessel.

4. Plants for the fabrication of nuclear reactor fuel elements, and equipment especially designed or prepared therefor

INTRODUCTORY NOTE

Nuclear fuel elements are manufactured from one or more of the source or special fissionable materials mentioned in MATERIAL AND EQUIPMENT of this annex. For oxide fuels, the most common type of fuel, equipment for pressing pellets, sintering, grinding and grading will be present. Mixed oxide fuels are handled in glove boxes (or equivalent containment) until they are sealed in the cladding. In all cases, the fuel is hermetically sealed inside a suitable cladding which is designed to be the primary envelope encasing the fuel so as to provide suitable performance and safety during reactor operation. Also, in all cases, precise control of processes, procedures and equipment to extremely high standards is necessary in order to ensure predictable and safe fuel performance.

EXPLANATORY NOTE

Items of equipment that are considered to fall within the meaning of the phrase "and equipment especially designed or prepared" for the fabrication of fuel elements include equipment which:

- (a) normally comes in direct contact with, or directly processes, or controls, the production flow of nuclear material;
- (b) seals the nuclear material within the cladding;
- (c) checks the integrity of the cladding or the seal; or
- (d) checks the finish treatment of the sealed fuel.

Such equipment or systems of equipment may include, for example:

- 1) fully automatic pellet inspection stations especially designed or prepared for checking final dimensions and surface defects of the fuel pellets;
- 2) automatic welding machines especially designed or prepared for welding end caps onto the fuel pins (or rods);
- 3) automatic test and inspection stations especially designed or prepared for checking the integrity of completed fuel pins (or rods).

Item 3 typically includes equipment for: a) x-ray examination of pin (or rod) end cap welds, b) helium leak detection from pressurized pins (or rods), and c) gamma-ray scanning of the pins (or rods) to check for correct loading of the fuel pellets inside.

5. Plants for the separation of isotopes of natural uranium, depleted uranium or special fissionable material and equipment, other than analytical instruments, especially designed or prepared therefor

INTRODUCTORY NOTE

Plants, equipment and technology for the separation of uranium isotopes have, in many instances, a close relationship to plants, equipment and technology for the separation of stable isotopes. In particular cases, the controls under Section 5 also apply to plants and equipment that are intended for the separation of stable isotopes. These controls of plants and equipment for the separation of stable isotopes are complimentary to controls on plants and equipment especially designed or prepared for the processing, use or production of special fissionable material covered by the Trigger List. These complementary Section 5 controls for stable isotope uses do not apply to the electromagnetic isotope separation process, which is addressed under Part 2 of the Guidelines.

Processes for which the controls in Section 5 equally apply whether the intended use is uranium isotope separation or stable isotope separation are: gas centrifuge, gaseous diffusion, the plasma separation process, and aerodynamic processes.

For some processes, the relationship to uranium isotope separation depends on the element (stable isotope) being separated. These processes are: laser-based processes (e.g. molecular laser isotope separation and atomic vapor laser isotope separation), chemical exchange, and ion exchange. Suppliers must therefore evaluate these processes on a case-by-case basis to apply Section 5 controls for stable isotope uses accordingly.

Items of equipment that are considered to fall within the meaning of the phrase "equipment, other than analytical instruments, especially designed or prepared" for the separation of isotopes of uranium include:

5.1. Gas centrifuges and assemblies and components especially designed or prepared for use in gas centrifuges

INTRODUCTORY NOTE

The gas centrifuge normally consists of a thin-walled cylinder(s) of between 75 mm (3 in) and 400 mm (16 in) diameter contained in a vacuum environment and spun at high peripheral speed of the order of 300 m/s or more with its central axis vertical. In order to achieve high speed the materials of construction for the rotating components have to be of a high strength to density ratio and the rotor assembly, and hence its individual components, have to be manufactured to very close tolerances in order to minimize the unbalance. In contrast to other centrifuges, the gas centrifuge for uranium enrichment is characterized by having within the rotor chamber a rotating disc-shaped baffle(s) and a stationary tube arrangement for feeding and extracting the UF₆ gas and featuring at least 3 separate channels, of which 2 are connected to scoops extending from the rotor axis towards the periphery of the rotor chamber. Also contained within the vacuum environment are a number of critical items which do not rotate and which although they are especially designed are not difficult to fabricate

nor are they fabricated out of unique materials. A centrifuge facility however requires a large number of these components, so that quantities can provide an important indication of end use.

5.1.1. Rotating components

(a) Complete rotor assemblies:

Thin-walled cylinders, or a number of interconnected thin-walled cylinders, manufactured from one or more of the high strength to density ratio materials described in the EXPLANATORY NOTE to this Section. If interconnected, the cylinders are joined together by flexible bellows or rings as described in section 5.1.1.(c) following. The rotor is fitted with an internal baffle(s) and end caps, as described in section 5.1.1.(d) and (e) following, if in final form. However the complete assembly may be delivered only partly assembled.

(b) Rotor tubes:

Especially designed or prepared thin-walled cylinders with thickness of 12 mm (0.5 in) or less, a diameter of between 75 mm (3 in) and 400 mm (16 in), and manufactured from one or more of the high strength to density ratio materials described in the EXPLANATORY NOTE to this Section.

(c) Rings or Bellows:

Components especially designed or prepared to give localized support to the rotor tube or to join together a number of rotor tubes. The bellows is a short cylinder of wall thickness 3 mm (0.12 in) or less, a diameter of between 75 mm (3 in) and 400 mm (16 in), having a convolute, and manufactured from one of the high strength to density ratio materials described in the EXPLANATORY NOTE to this Section.

(d) Baffles:

Disc-shaped components of between 75 mm (3 in) and 400 mm (16 in) diameter especially designed or prepared to be mounted inside the centrifuge rotor tube, in order to isolate the take-off chamber from the main separation chamber and, in some cases, to assist the UF₆ gas circulation within the main separation chamber of the rotor tube, and manufactured from one of the high strength to density ratio materials described in the EXPLANATORY NOTE to this Section.

(e) Top caps/Bottom caps:

Disc-shaped components of between 75 mm (3 in) and 400 mm (16 in) diameter especially designed or prepared to fit to the ends of the rotor tube, and so contain the UF₆ within the rotor tube, and in some cases to support, retain or contain as an integrated part an element of the upper bearing (top cap) or to carry the rotating

elements of the motor and lower bearing (bottom cap), and manufactured from one of the high strength to density ratio materials described in the EXPLANATORY NOTE to this Section.

EXPLANATORY NOTE

The materials used for centrifuge rotating components are:

- (a) Maraging steel capable of an ultimate tensile strength of $2.05 \times 10^9 \text{ N/m}^2$ (300,000 psi) or more;
- (b) Aluminium alloys capable of an ultimate tensile strength of $0.46 \times 10^9 \text{ N/m}^2$ (67,000 psi) or more;
- (c) Filamentary materials suitable for use in composite structures and having a specific modulus of $3.18 \times 10^6 \text{ m}$ or greater and a specific ultimate tensile strength of $7.62 \times 10^4 \text{ m}$ or greater ('Specific Modulus' is the Young's Modulus in N/m^2 divided by the specific weight in N/m^3 ; 'Specific Ultimate Tensile Strength' is the ultimate tensile strength in N/m^2 divided by the specific weight in N/m^3).

5.1.2. Static components

- (a) Magnetic suspension bearings:

Especially designed or prepared bearing assemblies consisting of an annular magnet suspended within a housing containing a damping medium. The housing will be manufactured from a UF_6 -resistant material (see EXPLANATORY NOTE to Section 5.2.). The magnet couples with a pole piece or a second magnet fitted to the top cap described in Section 5.1.1.(e). The magnet may be ring-shaped with a relation between outer and inner diameter smaller or equal to 1.6:1. The magnet may be in a form having an initial permeability of 0.15 H/m (120,000 in CGS units) or more, or a remanence of 98.5% or more, or an energy product of greater than 80 kJ/m^3 (10^7 gauss-oersteds). In addition to the usual material properties, it is a prerequisite that the deviation of the magnetic axes from the geometrical axes is limited to very small tolerances (lower than 0.1 mm or 0.004 in) or that homogeneity of the material of the magnet is specially called for.

- (b) Bearings/Dampers:

Especially designed or prepared bearings comprising a pivot/cup assembly mounted on a damper. The pivot is normally a hardened steel shaft with a hemisphere at one end with a means of attachment to the bottom cap described in section 5.1.1.(e) at the other. The shaft may however have a hydrodynamic bearing attached. The cup is pellet-shaped with a hemispherical indentation in one surface. These components are often supplied separately to the damper.

- (c) Molecular pumps:

Especially designed or prepared cylinders having internally machined or extruded helical grooves and internally machined bores. Typical dimensions are as follows: 75 mm (3 in) to 400 mm (16 in) internal diameter, 10 mm (0.4 in) or more wall thickness, with the length equal to or greater than the diameter. The grooves are typically rectangular in cross-section and 2 mm (0.08 in) or more in depth.

(d) Motor stators:

Especially designed or prepared ring-shaped stators for high speed multiphase AC hysteresis (or reluctance) motors for synchronous operation within a vacuum in the frequency range of 600 – 2000 Hz and a power range of 50 - 1000 VA. The stators consist of multi-phase windings on a laminated low loss iron core comprised of thin layers typically 2.0 mm (0.08 in) thick or less.

(e) Centrifuge housing/recipient:

Components especially designed or prepared to contain the rotor tube assembly of a gas centrifuge. The housing consists of a rigid cylinder of wall thickness up to 30 mm (1.2 in) with precision machined ends to locate the bearings and with one or more flanges for mounting. The machined ends are parallel to each other and perpendicular to the cylinder's longitudinal axis to within 0.05 degrees or less. The housing may also be a honeycomb type structure to accommodate several rotor tubes. The housings are made of or protected by materials resistant to corrosion by UF_6 .

(f) Scoops:

Especially designed or prepared tubes of up to 12 mm (0.5 in) internal diameter for the extraction of UF_6 gas from within the rotor tube by a Pitot tube action (that is, with an aperture facing into the circumferential gas flow within the rotor tube, for example by bending the end of a radially disposed tube) and capable of being fixed to the central gas extraction system. The tubes are made of or protected by materials resistant to corrosion by UF_6 .

5.2. Especially designed or prepared auxiliary systems, equipment and components for gas centrifuge enrichment plants

INTRODUCTORY NOTE

The auxiliary systems, equipment and components for a gas centrifuge enrichment plant are the systems of plant needed to feed UF₆ to the centrifuges, to link the individual centrifuges to each other to form cascades (or stages) to allow for progressively higher enrichments and to extract the 'product' and 'tails' UF₆ from the centrifuges, together with the equipment required to drive the centrifuges or to control the plant.

Normally UF₆ is evaporated from the solid using heated autoclaves and is distributed in gaseous form to the centrifuges by way of cascade header pipework. The 'product' and 'tails' UF₆ gaseous streams flowing from the centrifuges are also passed by way of cascade header pipework to cold traps (operating at about 203 K (-70°C)) where they are condensed prior to onward transfer into suitable containers for transportation or storage. Because an enrichment plant consists of many thousands of centrifuges arranged in cascades there are many kilometers of cascade header pipework, incorporating thousands of welds with a substantial amount of repetition of layout. The equipment, components and piping systems are fabricated to very high vacuum and cleanliness standards.

5.2.1. Feed systems/product and tails withdrawal systems

Especially designed or prepared process systems including:

Feed autoclaves (or stations), used for passing UF₆ to the centrifuge cascades at up to 100 kPa (15 psi) and at a rate of 1 kg/h or more;

Desublimers (or cold traps) used to remove UF₆ from the cascades at up to 3 kPa (0.5 psi) pressure. The desublimers are capable of being chilled to 203 K (-70°C) and heated to 343 K (70°C);

'Product' and 'Tails' stations used for trapping UF₆ into containers.

This plant, equipment and pipework is wholly made of or lined with UF₆-resistant materials (see EXPLANATORY NOTE to this section) and is fabricated to very high vacuum and cleanliness standards.

5.2.2. Machine header piping systems

Especially designed or prepared piping systems and header systems for handling UF₆ within the centrifuge cascades. The piping network is normally of the 'triple' header system with each centrifuge connected to each of the headers. There is thus a substantial amount of repetition in its form. It is wholly made of UF₆-resistant materials (see EXPLANATORY NOTE to this section) and is fabricated to very high vacuum and cleanliness standards.

5.2.3 Special shut-off and control valves

Especially designed or prepared bellows-sealed valves, manual or automated, shut-off or control, made of or protected by materials resistant to corrosion by UF₆, with a diameter of 10 to 160 mm, for use in main or auxiliary systems of gas centrifuge enrichment plants.

5.2.4. UF₆ mass spectrometers/ion sources

Especially designed or prepared magnetic or quadrupole mass spectrometers capable of taking 'on-line' samples of feed, product or tails, from UF₆ gas streams and having all of the following characteristics:

1. Unit resolution for atomic mass unit greater than 320;
2. Ion sources constructed of or lined with nichrome or monel or nickel plated;
3. Electron bombardment ionization sources;
4. Having a collector system suitable for isotopic analysis.

5.2.5. Frequency changers

Frequency changers (also known as converters or invertors) especially designed or prepared to supply motor stators as defined under 5.1.2.(d), or parts, components and sub-assemblies of such frequency changers having all of the following characteristics:

1. A multiphase output of 600 to 2000 Hz;
2. High stability (with frequency control better than 0.1%);
3. Low harmonic distortion (less than 2%); and
4. An efficiency of greater than 80%.

EXPLANATORY NOTE

The items listed above either come into direct contact with the UF₆ process gas or directly control the centrifuges and the passage of the gas from centrifuge to centrifuge and cascade to cascade.

Materials resistant to corrosion by UF₆ include stainless steel, aluminium, aluminium alloys, nickel or alloys containing 60% or more nickel.

5.3. Especially designed or prepared assemblies and components for use in gaseous diffusion enrichment

INTRODUCTORY NOTE

In the gaseous diffusion method of uranium isotope separation, the main technological assembly is a special porous gaseous diffusion barrier, heat exchanger for cooling the gas (which is heated by the process of compression), seal valves and control valves, and pipelines. Inasmuch as gaseous diffusion technology uses uranium hexafluoride (UF₆), all equipment, pipeline and instrumentation surfaces (that come in contact with the gas) must be made of materials that remain stable in contact with UF₆. A gaseous diffusion facility requires a number of these assemblies, so that quantities can provide an important indication of end use.

5.3.1. Gaseous diffusion barriers

- (a) Especially designed or prepared thin, porous filters, with a pore size of 100 - 1,000 Å (angstroms), a thickness of 5 mm (0.2 in) or less, and for tubular forms, a diameter of 25 mm (1 in) or less, made of metallic, polymer or ceramic materials resistant to corrosion by UF₆, and
- (b) especially prepared compounds or powders for the manufacture of such filters. Such compounds and powders include nickel or alloys containing 60% or more nickel, aluminium oxide, or UF₆-resistant fully fluorinated hydrocarbon polymers having a purity of 99.9% or more, a particle size less than 10 microns, and a high degree of particle size uniformity, which are especially prepared for the manufacture of gaseous diffusion barriers.

5.3.2. Diffuser housings

Especially designed or prepared hermetically sealed cylindrical vessels greater than 300 mm (12 in) in diameter and greater than 900 mm (35 in) in length, or rectangular vessels of comparable dimensions, which have an inlet connection and two outlet connections all of which are greater than 50 mm (2 in) in diameter, for containing the gaseous diffusion barrier, made of or lined with UF₆-resistant materials and designed for horizontal or vertical installation.

5.3.3. Compressors and gas blowers

Especially designed or prepared axial, centrifugal, or positive displacement compressors, or gas blowers with a suction volume capacity of 1 m³/min or more of UF₆, and with a discharge pressure of up to several hundred kPa (100 psi), designed for long-term operation in the UF₆ environment with or without an electrical motor of appropriate power, as well as separate assemblies of such compressors and gas blowers. These compressors and gas blowers have a pressure ratio between 2:1 and 6:1 and are made of, or lined with, materials resistant to UF₆.

5.3.4. Rotary shaft seals

Especially designed or prepared vacuum seals, with seal feed and seal exhaust connections, for sealing the shaft connecting the compressor or the gas blower rotor with the driver motor so as to ensure a reliable seal against in-leaking of air into the inner chamber of the compressor or gas blower which is filled with UF₆. Such seals are normally designed for a buffer gas in-leakage rate of less than 1000 cm³/min (60 in³/min).

5.3.5. Heat exchangers for cooling UF₆

Especially designed or prepared heat exchangers made of or lined with UF₆-resistant materials (except stainless steel) or with copper or any combination of those metals, and intended for a leakage pressure change rate of less than 10 Pa (0.0015 psi) per hour under a pressure difference of 100 kPa (15 psi).

5.4. Especially designed or prepared auxiliary systems, equipment and components for use in gaseous diffusion enrichment

INTRODUCTORY NOTE

The auxiliary systems, equipment and components for gaseous diffusion enrichment plants are the systems of plant needed to feed UF₆ to the gaseous diffusion assembly, to link the individual assemblies to each other to form cascades (or stages) to allow for progressively higher enrichments and to extract the "product" and "tails" UF₆ from the diffusion cascades. Because of the high inertial properties of diffusion cascades, any interruption in their operation, and especially their shut-down, leads to serious consequences. Therefore, a strict and constant maintenance of vacuum in all technological systems, automatic protection from accidents, and precise automated regulation of the gas flow is of importance in a gaseous diffusion plant. All this leads to a need to equip the plant with a large number of special measuring, regulating and controlling systems.

Normally UF₆ is evaporated from cylinders placed within autoclaves and is distributed in gaseous form to the entry point by way of cascade header pipework. The "product" and "tails" UF₆ gaseous streams flowing from exit points are passed by way of cascade header pipework to either cold traps or to compression stations where the UF₆ gas is liquefied prior to onward transfer into suitable containers for transportation or storage. Because a gaseous diffusion enrichment plant consists of a large number of gaseous diffusion assemblies arranged in cascades, there are many kilometers of cascade header pipework, incorporating thousands of welds with substantial amounts of repetition of layout. The equipment, components and piping systems are fabricated to very high vacuum and cleanliness standards.

5.4.1. Feed systems/product and tails withdrawal systems

Especially designed or prepared process systems, capable of operating at pressures of 300 kPa (45 psi) or less, including:

Feed autoclaves (or systems), used for passing UF₆ to the gaseous diffusion cascades;

Desublimers (or cold traps) used to remove UF₆ from diffusion cascades;

Liquefaction stations where UF₆ gas from the cascade is compressed and cooled to form liquid UF₆;

"Product" or "tails" stations used for transferring UF₆ into containers.

5.4.2. Header piping systems

Especially designed or prepared piping systems and header systems for handling UF₆ within the gaseous diffusion cascades. This piping network is normally of the "double" header system with each cell connected to each of the headers.

5.4.3. Vacuum systems

- (a) Especially designed or prepared large vacuum manifolds, vacuum headers and vacuum pumps having a suction capacity of 5 m³/min (175 ft³/min) or more.
- (b) Vacuum pumps especially designed for service in UF₆-bearing atmospheres made of, or lined with, aluminium, nickel, or alloys bearing more than 60% nickel. These pumps may be either rotary or positive, may have displacement and fluorocarbon seals, and may have special working fluids present.

5.4.4. Special shut-off and control valves

Especially designed or prepared manual or automated shut-off and control bellows valves made of UF₆-resistant materials with a diameter of 40 to 1500 mm (1.5 to 59 in) for installation in main and auxiliary systems of gaseous diffusion enrichment plants.

5.4.5. UF₆ mass spectrometers/ion sources

Especially designed or prepared magnetic or quadrupole mass spectrometers capable of taking "on-line" samples of feed, product or tails, from UF₆ gas streams and having all of the following characteristics:

1. Unit resolution for atomic mass unit greater than 320;
2. Ion sources constructed of or lined with nichrome or monel or nickel plated;
3. Electron bombardment ionization sources;
4. Collector system suitable for isotopic analysis.

EXPLANATORY NOTE

The items listed above either come into direct contact with the UF₆ process gas or directly control the flow within the cascade. All surfaces which come into contact with the process gas are wholly made of, or lined with, UF₆-resistant materials. For the purposes of the sections relating to gaseous diffusion items the materials resistant to corrosion by UF₆ include stainless steel, aluminium, aluminium alloys, aluminium oxide, nickel or alloys containing 60% or more nickel and UF₆-resistant fully fluorinated hydrocarbon polymers.

5.5. Especially designed or prepared systems, equipment and components for use in aerodynamic enrichment plants

INTRODUCTORY NOTE

In aerodynamic enrichment processes, a mixture of gaseous UF₆ and light gas (hydrogen or helium) is compressed and then passed through separating elements wherein isotopic separation is accomplished by the generation of high centrifugal forces over a curved-wall geometry. Two processes of this type have been successfully developed: the separation nozzle process and the vortex tube process. For both processes the main components of a separation stage include cylindrical vessels housing the special separation elements (nozzles or vortex tubes), gas compressors and heat exchangers to remove the heat of compression. An aerodynamic plant requires a number of these stages, so that quantities can provide an important indication of end use. Since aerodynamic processes use UF₆, all equipment, pipeline and instrumentation surfaces (that come in contact with the gas) must be made of materials that remain stable in contact with UF₆.

EXPLANATORY NOTE

The items listed in this section either come into direct contact with the UF₆ process gas or directly control the flow within the cascade. All surfaces which come into contact with the process gas are wholly made of or protected by UF₆-resistant materials. For the purposes of the section relating to aerodynamic enrichment items, the materials resistant to corrosion by UF₆ include copper, stainless steel, aluminium, aluminium alloys, nickel or alloys containing 60% or more nickel and UF₆-resistant fully fluorinated hydrocarbon polymers.

5.5.1. Separation nozzles

Especially designed or prepared separation nozzles and assemblies thereof. The separation nozzles consist of slit-shaped, curved channels having a radius of curvature less than 1 mm (typically 0.1 to 0.05 mm), resistant to corrosion by UF₆ and having a knife-edge within the nozzle that separates the gas flowing through the nozzle into two fractions.

5.5.2. Vortex tubes

Especially designed or prepared vortex tubes and assemblies thereof. The vortex tubes are cylindrical or tapered, made of or protected by materials resistant to corrosion by UF₆, having a diameter of between 0.5 cm and 4 cm, a length to diameter ratio of 20:1 or less and with one or more tangential inlets. The tubes may be equipped with nozzle-type appendages at either or both ends.

EXPLANATORY NOTE

The feed gas enters the vortex tube tangentially at one end or through swirl vanes or at numerous tangential positions along the periphery of the tube.

5.5.3. Compressors and gas blowers

Especially designed or prepared axial, centrifugal or positive displacement compressors or gas blowers made of or protected by materials resistant to corrosion by UF₆ and with a suction volume capacity of 2 m³/min or more of UF₆/carrier gas (hydrogen or helium) mixture.

EXPLANATORY NOTE

These compressors and gas blowers typically have a pressure ratio between 1.2:1 and 6:1.

5.5.4. Rotary shaft seals

Especially designed or prepared rotary shaft seals, with seal feed and seal exhaust connections, for sealing the shaft connecting the compressor rotor or the gas blower rotor with the driver motor so as to ensure a reliable seal against out-leakage of process gas or in-leakage of air or seal gas into the inner chamber of the compressor or gas blower which is filled with a UF₆/carrier gas mixture.

5.5.5. Heat exchangers for gas cooling

Especially designed or prepared heat exchangers made of or protected by materials resistant to corrosion by UF₆.

5.5.6. Separation element housings

Especially designed or prepared separation element housings, made of or protected by materials resistant to corrosion by UF₆, for containing vortex tubes or separation nozzles.

EXPLANATORY NOTE

These housings may be cylindrical vessels greater than 300 mm in diameter and greater than 900 mm in length, or may be rectangular vessels of comparable dimensions, and may be designed for horizontal or vertical installation.

5.5.7. Feed systems/product and tails withdrawal systems

Especially designed or prepared process systems or equipment for enrichment plants made of or protected by materials resistant to corrosion by UF₆, including:

- (a) Feed autoclaves, ovens, or systems used for passing UF₆ to the enrichment process;
- (b) Desublimers (or cold traps) used to remove UF₆ from the enrichment process for subsequent transfer upon heating;
- (c) Solidification or liquefaction stations used to remove UF₆ from the enrichment process by compressing and converting UF₆ to a liquid or solid form;

(d) 'Product' or 'tails' stations used for transferring UF₆ into containers.

5.5.8. Header piping systems

Especially designed or prepared header piping systems, made of or protected by materials resistant to corrosion by UF₆, for handling UF₆ within the aerodynamic cascades. This piping network is normally of the 'double' header design with each stage or group of stages connected to each of the headers.

5.5.9. Vacuum systems and pumps

- (a) Especially designed or prepared vacuum systems having a suction capacity of 5 m³/min or more, consisting of vacuum manifolds, vacuum headers and vacuum pumps, and designed for service in UF₆-bearing atmospheres,
- (b) Vacuum pumps especially designed or prepared for service in UF₆-bearing atmospheres and made of or protected by materials resistant to corrosion by UF₆. These pumps may use fluorocarbon seals and special working fluids.

5.5.10. Special shut-off and control valves

Especially designed or prepared manual or automated shut-off and control bellows valves made of or protected by materials resistant to corrosion by UF₆ with a diameter of 40 to 1500 mm for installation in main and auxiliary systems of aerodynamic enrichment plants.

5.5.11. UF₆ mass spectrometers/Ion sources

Especially designed or prepared magnetic or quadrupole mass spectrometers capable of taking 'on-line' samples of feed, 'product' or 'tails', from UF₆ gas streams and having all of the following characteristics:

1. Unit resolution for mass greater than 320;
2. Ion sources constructed of or lined with nichrome or monel or nickel plated;
3. Electron bombardment ionization sources;
4. Collector system suitable for isotopic analysis.

5.5.12. UF₆/carrier gas separation systems

Especially designed or prepared process systems for separating UF₆ from carrier gas (hydrogen or helium).

EXPLANATORY NOTE

These systems are designed to reduce the UF₆ content in the carrier gas to 1 ppm or less and may incorporate equipment such as:

- (a) Cryogenic heat exchangers and cryoseparators capable of temperatures of -120°C or less, or
- (b) Cryogenic refrigeration units capable of temperatures of -120°C or less, or
- (c) Separation nozzle or vortex tube units for the separation of UF₆ from carrier gas, or
- (d) UF₆ cold traps capable of temperatures of -20°C or less.

5.6. Especially designed or prepared systems, equipment and components for use in chemical exchange or ion exchange enrichment plants.

INTRODUCTORY NOTE

The slight difference in mass between the isotopes of uranium causes small changes in chemical reaction equilibria that can be used as a basis for separation of the isotopes. Two processes have been successfully developed: liquid-liquid chemical exchange and solid-liquid ion exchange.

In the liquid-liquid chemical exchange process, immiscible liquid phases (aqueous and organic) are countercurrently contacted to give the cascading effect of thousands of separation stages. The aqueous phase consists of uranium chloride in hydrochloric acid solution; the organic phase consists of an extractant containing uranium chloride in an organic solvent. The contactors employed in the separation cascade can be liquid-liquid exchange columns (such as pulsed columns with sieve plates) or liquid centrifugal contactors. Chemical conversions (oxidation and reduction) are required at both ends of the separation cascade in order to provide for the reflux requirements at each end. A major design concern is to avoid contamination of the process streams with certain metal ions. Plastic, plastic-lined (including use of fluorocarbon polymers) and/or glass-lined columns and piping are therefore used.

In the solid-liquid ion-exchange process, enrichment is accomplished by uranium adsorption/desorption on a special, very fast-acting, ion-exchange resin or adsorbent. A solution of uranium in hydrochloric acid and other chemical agents is passed through cylindrical enrichment columns containing packed beds of the adsorbent. For a continuous process, a reflux system is necessary to release the uranium from the adsorbent back into the liquid flow so that 'product' and 'tails' can be collected. This is accomplished with the use of suitable reduction/oxidation chemical agents that are fully regenerated in separate external circuits and that may be partially regenerated within the isotopic separation columns themselves. The presence of hot concentrated hydrochloric acid solutions in the process requires that the equipment be made of or protected by special corrosion-resistant materials.

5.6.1. Liquid-liquid exchange columns (Chemical exchange)

Countercurrent liquid-liquid exchange columns having mechanical power input (i.e., pulsed columns with sieve plates, reciprocating plate columns, and columns with internal turbine mixers), especially designed or prepared for uranium enrichment using the chemical exchange process. For corrosion resistance to concentrated hydrochloric acid solutions, these columns and their internals are made of or protected by suitable plastic materials (such as fluorocarbon polymers) or glass. The stage residence time of the columns is designed to be short (30 seconds or less).

5.6.2. Liquid-liquid centrifugal contactors (Chemical exchange)

Liquid-liquid centrifugal contactors especially designed or prepared for uranium enrichment using the chemical exchange process. Such contactors use rotation to achieve dispersion of the organic and aqueous streams and then centrifugal force to separate the phases. For corrosion resistance to concentrated hydrochloric acid

solutions, the contactors are made of or are lined with suitable plastic materials (such as fluorocarbon polymers) or are lined with glass. The stage residence time of the centrifugal contactors is designed to be short (30 seconds or less).

5.6.3. Uranium reduction systems and equipment (Chemical exchange)

- (a) Especially designed or prepared electrochemical reduction cells to reduce uranium from one valence state to another for uranium enrichment using the chemical exchange process. The cell materials in contact with process solutions must be corrosion resistant to concentrated hydrochloric acid solutions.

EXPLANATORY NOTE

The cell cathodic compartment must be designed to prevent re-oxidation of uranium to its higher valence state. To keep the uranium in the cathodic compartment, the cell may have an impervious diaphragm membrane constructed of special cation exchange material. The cathode consists of a suitable solid conductor such as graphite.

- (b) Especially designed or prepared systems at the product end of the cascade for taking the U^{+4} out of the organic stream, adjusting the acid concentration and feeding to the electrochemical reduction cells.

EXPLANATORY NOTE

These systems consist of solvent extraction equipment for stripping the U^{+4} from the organic stream into an aqueous solution, evaporation and/or other equipment to accomplish solution pH adjustment and control, and pumps or other transfer devices for feeding to the electrochemical reduction cells. A major design concern is to avoid contamination of the aqueous stream with certain metal ions. Consequently, for those parts in contact with the process stream, the system is constructed of equipment made of or protected by suitable materials (such as glass, fluorocarbon polymers, polyphenyl sulfate, polyether sulfone, and resin-impregnated graphite).

5.6.4. Feed preparation systems (Chemical exchange)

Especially designed or prepared systems for producing high-purity uranium chloride feed solutions for chemical exchange uranium isotope separation plants.

EXPLANATORY NOTE

These systems consist of dissolution, solvent extraction and/or ion exchange equipment for purification and electrolytic cells for reducing the uranium U^{+6} or U^{+4} to U^{+3} . These systems produce uranium chloride solutions having only a few parts per million of metallic impurities such as chromium, iron, vanadium, molybdenum and other bivalent or higher multi-valent cations. Materials of construction for portions of the system processing high-purity U^{+3} include glass, fluorocarbon polymers, polyphenyl sulfate or polyether sulfone plastic-lined and resin-impregnated graphite.

5.6.5. Uranium oxidation systems (Chemical exchange)

Especially designed or prepared systems for oxidation of U^{+3} to U^{+4} for return to the uranium isotope separation cascade in the chemical exchange enrichment process.

EXPLANATORY NOTE

These systems may incorporate equipment such as:

- (a) Equipment for contacting chlorine and oxygen with the aqueous effluent from the isotope separation equipment and extracting the resultant U^{+4} into the stripped organic stream returning from the product end of the cascade,
- (b) Equipment that separates water from hydrochloric acid so that the water and the concentrated hydrochloric acid may be reintroduced to the process at the proper locations.

5.6.6. Fast-reacting ion exchange resins/adsorbents (Ion exchange)

Fast-reacting ion-exchange resins or adsorbents especially designed or prepared for uranium enrichment using the ion exchange process, including porous macroreticular resins, and/or pellicular structures in which the active chemical exchange groups are limited to a coating on the surface of an inactive porous support structure, and other composite structures in any suitable form including particles or fibers. These ion exchange resins/adsorbents have diameters of 0.2 mm or less and must be chemically resistant to concentrated hydrochloric acid solutions as well as physically strong enough so as not to degrade in the exchange columns. The resins/adsorbents are especially designed to achieve very fast uranium isotope exchange kinetics (exchange rate half-time of less than 10 seconds) and are capable of operating at a temperature in the range of 100°C to 200°C.

5.6.7. Ion exchange columns (Ion exchange)

Cylindrical columns greater than 1000 mm in diameter for containing and supporting packed beds of ion exchange resin/adsorbent, especially designed or prepared for uranium enrichment using the ion exchange process. These columns are made of or protected by materials (such as titanium or fluorocarbon plastics) resistant to corrosion by concentrated hydrochloric acid solutions and are capable of operating at a temperature in the range of 100°C to 200°C and pressures above 0.7 MPa (102 psi).

5.6.8. Ion exchange reflux systems (Ion exchange)

- (a) Especially designed or prepared chemical or electrochemical reduction systems for regeneration of the chemical reducing agent(s) used in ion exchange uranium enrichment cascades.
- (b) Especially designed or prepared chemical or electrochemical oxidation systems for regeneration of the chemical oxidizing agent(s) used in ion exchange uranium enrichment cascades.

EXPLANATORY NOTE

The ion exchange enrichment process may use, for example, trivalent titanium (Ti^{+3}) as a reducing cation in which case the reduction system would regenerate Ti^{+3} by reducing Ti^{+4} .

The process may use, for example, trivalent iron (Fe^{+3}) as an oxidant in which case the oxidation system would regenerate Fe^{+3} by oxidizing Fe^{+2} .

5.7. Especially designed or prepared systems, equipment and components for use in laser-based enrichment plants.

INTRODUCTORY NOTE

Present systems for enrichment processes using lasers fall into two categories: those in which the process medium is atomic uranium vapor and those in which the process medium is the vapor of a uranium compound. Common nomenclature for such processes include: first category - atomic vapor laser isotope separation (AVLIS or SILVA); second category - molecular laser isotope separation (MLIS or MOLIS) and chemical reaction by isotope selective laser activation (CRISLA). The systems, equipment and components for laser enrichment plants embrace: (a) devices to feed uranium-metal vapor (for selective photo-ionization) or devices to feed the vapor of a uranium compound (for photo-dissociation or chemical activation); (b) devices to collect enriched and depleted uranium metal as 'product' and 'tails' in the first category, and devices to collect dissociated or reacted compounds as 'product' and unaffected material as 'tails' in the second category; (c) process laser systems to selectively excite the uranium-235 species; and (d) feed preparation and product conversion equipment. The complexity of the spectroscopy of uranium atoms and compounds may require incorporation of any of a number of available laser technologies.

EXPLANATORY NOTE

Many of the items listed in this section come into direct contact with uranium metal vapor or liquid or with process gas consisting of UF_6 or a mixture of UF_6 and other gases. All surfaces that come into contact with the uranium or UF_6 are wholly made of or protected by corrosion-resistant materials. For the purposes of the section relating to laser-based enrichment items, the materials resistant to corrosion by the vapor or liquid of uranium metal or uranium alloys include yttria-coated graphite and tantalum; and the materials resistant to corrosion by UF_6 include copper, stainless steel, aluminium, aluminium alloys, nickel or alloys containing 60% or more nickel and UF_6 -resistant fully fluorinated hydrocarbon polymers.

5.7.1. Uranium vaporization systems (AVLIS)

Especially designed or prepared uranium vaporization systems which contain high-power strip or scanning electron beam guns with a delivered power on the target of more than 2.5 kW/cm.

5.7.2. Liquid uranium metal handling systems (AVLIS)

Especially designed or prepared liquid metal handling systems for molten uranium or uranium alloys, consisting of crucibles and cooling equipment for the crucibles.

EXPLANATORY NOTE

The crucibles and other parts of this system that come into contact with molten uranium or uranium alloys are made of or protected by materials of suitable corrosion and heat resistance. Suitable materials include tantalum, yttria-coated graphite,

graphite coated with other rare earth oxides (see INFCIRC/254/Part 2 - (as amended)) or mixtures thereof.

5.7.3. Uranium metal 'product' and 'tails' collector assemblies (AVLIS)

Especially designed or prepared 'product' and 'tails' collector assemblies for uranium metal in liquid or solid form.

EXPLANATORY NOTE

Components for these assemblies are made of or protected by materials resistant to the heat and corrosion of uranium metal vapor or liquid (such as yttria-coated graphite or tantalum) and may include pipes, valves, fittings, 'gutters', feed-throughs, heat exchangers and collector plates for magnetic, electrostatic or other separation methods.

5.7.4. Separator module housings (AVLIS)

Especially designed or prepared cylindrical or rectangular vessels for containing the uranium metal vapor source, the electron beam gun, and the 'product' and 'tails' collectors.

EXPLANATORY NOTE

These housings have multiplicity of ports for electrical and water feed-throughs, laser beam windows, vacuum pump connections and instrumentation diagnostics and monitoring. They have provisions for opening and closure to allow refurbishment of internal components.

5.7.5. Supersonic expansion nozzles (MLIS)

Especially designed or prepared supersonic expansion nozzles for cooling mixtures of UF_6 and carrier gas to 150 K or less and which are corrosion resistant to UF_6 .

5.7.6. Uranium pentafluoride product collectors (MLIS)

Especially designed or prepared uranium pentafluoride (UF_5) solid product collectors consisting of filter, impact, or cyclone-type collectors, or combinations thereof, and which are corrosion resistant to the UF_5/UF_6 environment.

5.7.7. UF_6 /carrier gas compressors (MLIS)

Especially designed or prepared compressors for UF_6 /carrier gas mixtures, designed for long term operation in a UF_6 environment. The components of these compressors that come into contact with process gas are made of or protected by materials resistant to corrosion by UF_6 .

5.7.8. Rotary shaft seals (MLIS)

Especially designed or prepared rotary shaft seals, with seal feed and seal exhaust connections, for sealing the shaft connecting the compressor rotor with the driver motor so as to ensure a reliable seal against out-leakage of process gas or in-leakage of air or seal gas into the inner chamber of the compressor which is filled with a UF₆/carrier gas mixture.

5.7.9. Fluorination systems (MLIS)

Especially designed or prepared systems for fluorinating UF₅ (solid) to UF₆ (gas).

EXPLANATORY NOTE

These systems are designed to fluorinate the collected UF₅ powder to UF₆ for subsequent collection in product containers or for transfer as feed to MLIS units for additional enrichment. In one approach, the fluorination reaction may be accomplished within the isotope separation system to react and recover directly off the 'product' collectors. In another approach, the UF₅ powder may be removed/transferred from the 'product' collectors into a suitable reaction vessel (e.g., fluidized-bed reactor, screw reactor or flame tower) for fluorination. In both approaches, equipment for storage and transfer of fluorine (or other suitable fluorinating agents) and for collection and transfer of UF₆ are used.

5.7.10. UF₆ mass spectrometers/ion sources (MLIS)

Especially designed or prepared magnetic or quadrupole mass spectrometers capable of taking 'on-line' samples of feed, 'product' or 'tails', from UF₆ gas streams and having all of the following characteristics:

1. Unit resolution for mass greater than 320;
2. Ion sources constructed of or lined with nichrome or monel or nickel plated;
3. Electron bombardment ionization sources;
4. Collector system suitable for isotopic analysis.

5.7.11. Feed systems/product and tails withdrawal systems (MLIS)

Especially designed or prepared process systems or equipment for enrichment plants made of or protected by materials resistant to corrosion by UF₆, including:

- (a) Feed autoclaves, ovens, or systems used for passing UF₆ to the enrichment process;
- (b) Desublimers (or cold traps) used to remove UF₆ from the enrichment process for subsequent transfer upon heating;
- (c) Solidification or liquefaction stations used to remove UF₆ from the enrichment process by compressing and converting UF₆ to a liquid or solid form;

(d) 'Product' or 'tails' stations used for transferring UF₆ into containers.

5.7.12. UF₆/carrier gas separation systems (MLIS)

Especially designed or prepared process systems for separating UF₆ from carrier gas. The carrier gas may be nitrogen, argon, or other gas.

EXPLANATORY NOTE

These systems may incorporate equipment such as:

- (a) Cryogenic heat exchangers or cryoseparators capable of temperatures of -120°C or less, or
- (b) Cryogenic refrigeration units capable of temperatures of -120°C or less, or
- (c) UF₆ cold traps capable of temperatures of -20°C or less.

5.7.13. Laser systems (AVLIS, MLIS and CRISLA)

Lasers or laser systems especially designed or prepared for the separation of uranium isotopes.

EXPLANATORY NOTE

The lasers and laser components of importance in laser-based enrichment processes include those identified in INFCIRC/254/Part 2 - (as amended). The laser system for the AVLIS process usually consists of two lasers: a copper vapor laser and a dye laser. The laser system for MLIS usually consists of a CO₂ or excimer laser and a multi-pass optical cell with revolving mirrors at both ends. Lasers or laser systems for both processes require a spectrum frequency stabilizer for operation over extended periods of time.

5.8. Especially designed or prepared systems, equipment and components for use in plasma separation enrichment plants.

INTRODUCTORY NOTE

In the plasma separation process, a plasma of uranium ions passes through an electric field tuned to the ^{235}U ion resonance frequency so that they preferentially absorb energy and increase the diameter of their corkscrew-like orbits. Ions with a large-diameter path are trapped to produce a product enriched in ^{235}U . The plasma, which is made by ionizing uranium vapor, is contained in a vacuum chamber with a high-strength magnetic field produced by a superconducting magnet. The main technological systems of the process include the uranium plasma generation system, the separator module with superconducting magnet (see INFCIRC/254/Part 2 - (as amended)), and metal removal systems for the collection of 'product' and 'tails'.

5.8.1. Microwave power sources and antennae

Especially designed or prepared microwave power sources and antennae for producing or accelerating ions and having the following characteristics: greater than 30 GHz frequency and greater than 50 kW mean power output for ion production.

5.8.2. Ion excitation coils

Especially designed or prepared radio frequency ion excitation coils for frequencies of more than 100 kHz and capable of handling more than 40 kW mean power.

5.8.3. Uranium plasma generation systems

Especially designed or prepared systems for the generation of uranium plasma, which may contain high-power strip or scanning electron beam guns with a delivered power on the target of more than 2.5 kW/cm.

5.8.4. Liquid uranium metal handling systems

Especially designed or prepared liquid metal handling systems for molten uranium or uranium alloys, consisting of crucibles and cooling equipment for the crucibles.

EXPLANATORY NOTE

The crucibles and other parts of this system that come into contact with molten uranium or uranium alloys are made of or protected by materials of suitable corrosion and heat resistance. Suitable materials include tantalum, yttria-coated graphite, graphite coated with other rare earth oxides (see INFCIRC/254/Part 2 - (as amended)) or mixtures thereof.

5.8.5. Uranium metal 'product' and 'tails' collector assemblies

Especially designed or prepared 'product' and 'tails' collector assemblies for uranium metal in solid form. These collector assemblies are made of or protected by materials resistant to the heat and corrosion of uranium metal vapor, such as yttria-coated graphite or tantalum.

5.8.6. Separator module housings

Cylindrical vessels especially designed or prepared for use in plasma separation enrichment plants for containing the uranium plasma source, radio-frequency drive coil and the 'product' and 'tails' collectors.

EXPLANATORY NOTE

These housings have a multiplicity of ports for electrical feed-throughs, diffusion pump connections and instrumentation diagnostics and monitoring. They have provisions for opening and closure to allow for refurbishment of internal components and are constructed of a suitable non-magnetic material such as stainless steel.

5.9. Especially designed or prepared systems, equipment and components for use in electromagnetic enrichment plants.

INTRODUCTORY NOTE

In the electromagnetic process, uranium metal ions produced by ionization of a salt feed material (typically UCl_4) are accelerated and passed through a magnetic field that has the effect of causing the ions of different isotopes to follow different paths. The major components of an electromagnetic isotope separator include: a magnetic field for ion-beam diversion/separation of the isotopes, an ion source with its acceleration system, and a collection system for the separated ions. Auxiliary systems for the process include the magnet power supply system, the ion source high-voltage power supply system, the vacuum system, and extensive chemical handling systems for recovery of product and cleaning/recycling of components.

5.9.1. Electromagnetic isotope separators

Electromagnetic isotope separators especially designed or prepared for the separation of uranium isotopes, and equipment and components therefor, including:

(a) Ion sources

Especially designed or prepared single or multiple uranium ion sources consisting of a vapor source, ionizer, and beam accelerator, constructed of suitable materials such as graphite, stainless steel, or copper, and capable of providing a total ion beam current of 50 mA or greater.

(b) Ion collectors

Collector plates consisting of two or more slits and pockets especially designed or prepared for collection of enriched and depleted uranium ion beams and constructed of suitable materials such as graphite or stainless steel.

(c) Vacuum housings

Especially designed or prepared vacuum housings for uranium electromagnetic separators, constructed of suitable non-magnetic materials such as stainless steel and designed for operation at pressures of 0.1 Pa or lower.

EXPLANATORY NOTE

The housings are specially designed to contain the ion sources, collector plates and water-cooled liners and have provision for diffusion pump connections and opening and closure for removal and reinstallation of these components.

(d) Magnet pole pieces

Especially designed or prepared magnet pole pieces having a diameter greater than 2 m used to maintain a constant magnetic field within an electromagnetic isotope separator and to transfer the magnetic field between adjoining separators.

5.9.2. High voltage power supplies

Especially designed or prepared high-voltage power supplies for ion sources, having all of the following characteristics: capable of continuous operation, output voltage of 20,000 V or greater, output current of 1 A or greater, and voltage regulation of better than 0.01% over a time period of 8 hours.

5.9.3. Magnet power supplies

Especially designed or prepared high-power, direct current magnet power supplies having all of the following characteristics: capable of continuously producing a current output of 500 A or greater at a voltage of 100 V or greater and with a current or voltage regulation better than 0.01% over a period of 8 hours.

6. Plants for the production or concentration of heavy water, deuterium and deuterium compounds and equipment especially designed or prepared therefor

INTRODUCTORY NOTE

Heavy water can be produced by a variety of processes. However, the two processes that have proven to be commercially viable are the water-hydrogen sulphide exchange process (GS process) and the ammonia-hydrogen exchange process.

The GS process is based upon the exchange of hydrogen and deuterium between water and hydrogen sulphide within a series of towers which are operated with the top section cold and the bottom section hot. Water flows down the towers while the hydrogen sulphide gas circulates from the bottom to the top of the towers. A series of perforated trays are used to promote mixing between the gas and the water. Deuterium migrates to the water at low temperatures and to the hydrogen sulphide at high temperatures. Gas or water, enriched in deuterium, is removed from the first stage towers at the junction of the hot and cold sections and the process is repeated in subsequent stage towers. The product of the last stage, water enriched up to 30% in deuterium, is sent to a distillation unit to produce reactor grade heavy water; i.e., 99.75% deuterium oxide.

The ammonia-hydrogen exchange process can extract deuterium from synthesis gas through contact with liquid ammonia in the presence of a catalyst. The synthesis gas is fed into exchange towers and to an ammonia converter. Inside the towers the gas flows from the bottom to the top while the liquid ammonia flows from the top to the bottom. The deuterium is stripped from the hydrogen in the synthesis gas and concentrated in the ammonia. The ammonia then flows into an ammonia cracker at the bottom of the tower while the gas flows into an ammonia converter at the top. Further enrichment takes place in subsequent stages and reactor grade heavy water is produced through final distillation. The synthesis gas feed can be provided by an ammonia plant that, in turn, can be constructed in association with a heavy water ammonia-hydrogen exchange plant. The ammonia-hydrogen exchange process can also use ordinary water as a feed source of deuterium.

Many of the key equipment items for heavy water production plants using GS or the ammonia-hydrogen exchange processes are common to several segments of the chemical and petroleum industries. This is particularly so for small plants using the GS process. However, few of the items are available "off-the-shelf". The GS and ammonia-hydrogen processes require the handling of large quantities of flammable, corrosive and toxic fluids at elevated pressures. Accordingly, in establishing the design and operating standards for plants and equipment using these processes, careful attention to the materials selection and specifications is required to ensure long service life with high safety and reliability factors. The choice of scale is primarily a function of economics and need. Thus, most of the equipment items would be prepared according to the requirements of the customer.

Finally, it should be noted that, in both the GS and the ammonia-hydrogen exchange processes, items of equipment which individually are not especially designed or prepared for heavy water production can be assembled into systems which are especially designed or prepared for producing heavy water. The catalyst production

system used in the ammonia-hydrogen exchange process and water distillation systems used for the final concentration of heavy water to reactor-grade in either process are examples of such systems.

The items of equipment which are especially designed or prepared for the production of heavy water utilizing either the water-hydrogen sulphide exchange process or the ammonia-hydrogen exchange process include the following:

6.1. Water - Hydrogen Sulphide Exchange Towers

Exchange towers fabricated from fine carbon steel (such as ASTM A516) with diameters of 6 m (20 ft) to 9 m (30 ft), capable of operating at pressures greater than or equal to 2 MPa (300 psi) and with a corrosion allowance of 6 mm or greater, especially designed or prepared for heavy water production utilizing the water-hydrogen sulphide exchange process.

6.2. Blowers and Compressors

Single stage, low head (i.e., 0.2 MPa or 30 psi) centrifugal blowers or compressors for hydrogen-sulphide gas circulation (i.e., gas containing more than 70% H₂S) especially designed or prepared for heavy water production utilizing the water-hydrogen sulphide exchange process. These blowers or compressors have a throughput capacity greater than or equal to 56 m³/second (120,000 SCFM) while operating at pressures greater than or equal to 1.8 MPa (260 psi) suction and have seals designed for wet H₂S service.

6.3. Ammonia-Hydrogen Exchange Towers

Ammonia-hydrogen exchange towers greater than or equal to 35 m (114.3 ft) in height with diameters of 1.5 m (4.9 ft) to 2.5 m (8.2 ft) capable of operating at pressures greater than 15 MPa (2225 psi) especially designed or prepared for heavy water production utilizing the ammonia-hydrogen exchange process. These towers also have at least one flanged, axial opening of the same diameter as the cylindrical part through which the tower internals can be inserted or withdrawn.

6.4. Tower Internals and Stage Pumps

Tower internals and stage pumps especially designed or prepared for towers for heavy water production utilizing the ammonia-hydrogen exchange process. Tower internals include especially designed stage contactors which promote intimate gas/liquid contact. Stage pumps include especially designed submersible pumps for circulation of liquid ammonia within a contacting stage internal to the stage towers.

6.5. Ammonia Crackers

Ammonia crackers with operating pressures greater than or equal to 3 MPa (450 psi) especially designed or prepared for heavy water production utilizing the ammonia-hydrogen exchange process.

6.6. Infrared Absorption Analyzers

Infrared absorption analyzers capable of "on-line" hydrogen/deuterium ratio analysis where deuterium concentrations are equal to or greater than 90%.

6.7. Catalytic Burners

Catalytic burners for the conversion of enriched deuterium gas into heavy water especially designed or prepared for heavy water production utilizing the ammonia-hydrogen exchange process.

6.8. Complete heavy water upgrade systems or columns therefor

Complete heavy water upgrade systems, or columns therefor, especially designed or prepared for the upgrade of heavy water to reactor-grade deuterium concentration.

EXPLANATORY NOTE

These systems, which usually employ water distillation to separate heavy water from light water, are especially designed or prepared to produce reactor-grade heavy water (i.e., typically 99.75% deuterium oxide) from heavy water feedstock of lesser concentration.

7. **Plants for the conversion of uranium and plutonium for use in the fabrication of fuel elements and the separation of uranium isotopes as defined in sections 4 and 5 respectively, and equipment especially designed or prepared therefor**

EXPORTS

The export of the whole set of major items within this boundary will take place only in accordance with the procedures of the Guidelines. All of the plants, systems, and especially designed or prepared equipment within this boundary can be used for the processing, production, or use of special fissionable material.

- 7.1. **Plants for the conversion of uranium and equipment especially designed or prepared therefor**

INTRODUCTORY NOTE

Uranium conversion plants and systems may perform one or more transformations from one uranium chemical species to another, including: conversion of uranium ore concentrates to UO_3 , conversion of UO_3 to UO_2 , conversion of uranium oxides to UF_4 , UF_6 , or UCl_4 , conversion of UF_4 to UF_6 , conversion of UF_6 to UF_4 , conversion of UF_4 to uranium metal, and conversion of uranium fluorides to UO_2 . Many of the key equipment items for uranium conversion plants are common to several segments of the chemical process industry. For example, the types of equipment employed in these processes may include: furnaces, rotary kilns, fluidized bed reactors, flame tower reactors, liquid centrifuges, distillation columns and liquid-liquid extraction columns. However, few of the items are available "off-the-shelf"; most would be prepared according to the requirements and specifications of the customer. In some instances, special design and construction considerations are required to address the corrosive properties of some of the chemicals handled (HF , F_2 , ClF_3 , and uranium fluorides) as well as nuclear criticality concerns. Finally, it should be noted that, in all of the uranium conversion processes, items of equipment which individually are not especially designed or prepared for uranium conversion can be assembled into systems which are especially designed or prepared for use in uranium conversion.

- 7.1.1. **Especially designed or prepared systems for the conversion of uranium ore concentrates to UO_3**

EXPLANATORY NOTE

Conversion of uranium ore concentrates to UO_3 can be performed by first dissolving the ore in nitric acid and extracting purified uranyl nitrate using a solvent such as tributyl phosphate. Next, the uranyl nitrate is converted to UO_3 either by concentration and denitration or by neutralization with gaseous ammonia to produce ammonium diuranate with subsequent filtering, drying, and calcining.

7.1.2. Especially designed or prepared systems for the conversion of UO_3 to UF_6

EXPLANATORY NOTE

Conversion of UO_3 to UF_6 can be performed directly by fluorination. The process requires a source of fluorine gas or chlorine trifluoride.

7.1.3. Especially designed or prepared systems for the conversion of UO_3 to UO_2

EXPLANATORY NOTE

Conversion of UO_3 to UO_2 can be performed through reduction of UO_3 with cracked ammonia gas or hydrogen.

7.1.4. Especially designed or prepared systems for the conversion of UO_2 to UF_4

EXPLANATORY NOTE

Conversion of UO_2 to UF_4 can be performed by reacting UO_2 with hydrogen fluoride gas (HF) at 300-500°C.

7.1.5. Especially designed or prepared systems for the conversion of UF_4 to UF_6

EXPLANATORY NOTE

Conversion of UF_4 to UF_6 is performed by exothermic reaction with fluorine in a tower reactor. UF_6 is condensed from the hot effluent gases by passing the effluent stream through a cold trap cooled to -10°C. The process requires a source of fluorine gas.

7.1.6. Especially designed or prepared systems for the conversion of UF_4 to U metal

EXPLANATORY NOTE

Conversion of UF_4 to U metal is performed by reduction with magnesium (large batches) or calcium (small batches). The reaction is carried out at temperatures above the melting point of uranium (1130 °C).

7.1.7. Especially designed or prepared systems for the conversion of UF_6 to UO_2

EXPLANATORY NOTE

Conversion of UF_6 to UO_2 can be performed by one of three processes. In the first, UF_6 is reduced and hydrolyzed to UO_2 using hydrogen and steam. In the second, UF_6 is hydrolyzed by solution in water, ammonia is added to precipitate ammonium diuranate, and the diuranate is reduced to UO_2 with hydrogen at 820°C. In the third process, gaseous UF_6 , CO_2 , and NH_3 are combined in water, precipitating ammonium uranyl carbonate. The ammonium uranyl carbonate is combined with steam and hydrogen at 500-600°C to yield UO_2 .

UF₆ to UO₂ conversion is often performed as the first stage of a fuel fabrication plant.

7.1.8. Especially designed or prepared systems for the conversion of UF₆ to UF₄

EXPLANATORY NOTE

Conversion of UF₆ to UF₄ is performed by reduction with hydrogen.

7.1.9. Especially designed or prepared systems for the conversion of UO₂ to UCl₄

EXPLANATORY NOTE

Conversion of UO₂ to UCl₄ can be performed by one of two processes. In the first, UO₂ is reacted with carbon tetrachloride (CCl₄) at approximately 400°C. In the second, UO₂ is reacted at approximately 700°C in the presence of carbon black (CAS 1333-86-4), carbon monoxide, and chlorine to yield UCl₄.

7.2. Plants for the conversion of plutonium and equipment especially designed or prepared therefor

INTRODUCTORY NOTE

Plutonium conversion plants and systems perform one or more transformations from one plutonium chemical species to another, including: conversion of plutonium nitrate to PuO₂, conversion of PuO₂ to PuF₄, and conversion of PuF₄ to plutonium metal. Plutonium conversion plants are usually associated with reprocessing facilities, but may also be associated with plutonium fuel fabrication facilities. Many of the key equipment items for plutonium conversion plants are common to several segments of the chemical process industry. For example, the types of equipment employed in these processes may include: furnaces, rotary kilns, fluidized bed reactors, flame tower reactors, liquid centrifuges, distillation columns and liquid-liquid extraction columns. Hot cells, glove boxes and remote manipulators may also be required. However, few of the items are available "off-the-shelf"; most would be prepared according to the requirements and specifications of the customer. Particular care in designing for the special radiological, toxicity and criticality hazards associated with plutonium is essential. In some instances, special design and construction considerations are required to address the corrosive properties of some of the chemicals handled (e.g. HF). Finally, it should be noted that, for all plutonium conversion processes, items of equipment which individually are not especially designed or prepared for plutonium conversion can be assembled into systems which are especially designed or prepared for use in plutonium conversion.

7.2.1. Especially designed or prepared systems for the conversion of plutonium nitrate to oxide

EXPLANATORY NOTE

The main functions involved in this process are: process feed storage and adjustment, precipitation and solid/liquor separation, calcination, product handling, ventilation, waste management, and process control. The process systems are particularly adapted

so as to avoid criticality and radiation effects and to minimize toxicity hazards. In most reprocessing facilities, this process involves the conversion of plutonium nitrate to plutonium dioxide. Other processes can involve the precipitation of plutonium oxalate or plutonium peroxide.

7.2.2. Especially designed or prepared systems for plutonium metal production

EXPLANATORY NOTE

This process usually involves the fluorination of plutonium dioxide, normally with highly corrosive hydrogen fluoride, to produce plutonium fluoride which is subsequently reduced using high purity calcium metal to produce metallic plutonium and a calcium fluoride slag. The main functions involved in this process are fluorination (e.g. involving equipment fabricated or lined with a precious metal), metal reduction (e.g. employing ceramic crucibles), slag recovery, product handling, ventilation, waste management and process control. The process systems are particularly adapted so as to avoid criticality and radiation effects and to minimize toxicity hazards. Other processes include the fluorination of plutonium oxalate or plutonium peroxide followed by a reduction to metal.

ANNEX C

CRITERIA FOR LEVELS OF PHYSICAL PROTECTION

1. The purpose of physical protection of nuclear materials is to prevent unauthorized use and handling of these materials. Paragraph 3(a) of the Guidelines document calls for agreement among suppliers on the levels of protection to be ensured in relation to the type of materials, and equipment and facilities containing these materials, taking account of international recommendations.
2. Paragraph 3(b) of the Guidelines document states that implementation of measures of physical protection in the recipient country is the responsibility of the Government of that country. However, the levels of physical protection on which these measures have to be based should be the subject of an agreement between supplier and recipient. In this context these requirements should apply to all States.
3. The document INFCIRC/225 of the International Atomic Energy Agency entitled "The Physical Protection of Nuclear Material" and similar documents which from time to time are prepared by international groups of experts and updated as appropriate to account for changes in the state of the art and state of knowledge with regard to physical protection of nuclear material are a useful basis for guiding recipient States in designing a system of physical protection measures and procedures.
4. The categorization of nuclear material presented in the attached table or as it may be updated from time to time by mutual agreement of suppliers shall serve as the agreed basis for designating specific levels of physical protection in relation to the type of materials, and equipment and facilities containing these materials, pursuant to paragraph 3(a) and 3(b) of the Guidelines document.
5. The agreed levels of physical protection to be ensured by the competent national authorities in the use, storage and transportation of the materials listed in the attached table shall as a minimum include protection characteristics as follows:

CATEGORY III

Use and Storage within an area to which access is controlled.

Transportation under special precautions including prior arrangements among sender, recipient and carrier, and prior agreement between entities subject to the jurisdiction and regulation of supplier and recipient States, respectively, in case of international transport, specifying time, place and procedures for transferring transport responsibility.

CATEGORY II

Use and Storage within a protected area to which access is controlled, i.e., an area under constant surveillance by guards or electronic devices, surrounded by a physical barrier with a limited number of points of entry under appropriate control, or any area with an equivalent level of physical protection.

Transportation under special precautions including prior arrangements among sender, recipient, and carrier, and prior agreement between entities subject to the jurisdiction and regulation of supplier and recipient States, respectively, in case of international transport, specifying time, place and procedures for transferring transport responsibility.

CATEGORY I

Materials in this category shall be protected with highly reliable systems against unauthorized use as follows:

Use and storage within a highly protected area, i.e., a protected area as defined for Category II above, to which, in addition, access is restricted to person whose trustworthiness has been determined, and which is under surveillance by guards who are in close communication with appropriate response forces. Specific measures taken in this context should have as their objective the detection and prevention of any assault, unauthorized access or unauthorized removal of material.

Transportation under special precautions as identified above for transportation of Category II and III materials and, in addition, under constant surveillance by escorts and under conditions which assure close communication with appropriate response forces.

6. Suppliers should request identification by recipients of those agencies or authorities having responsibility for ensuring that levels of protection are adequately met and having responsibility for internally co-ordinating response/recovery operations in the event of unauthorized use or handling of protected materials. Suppliers and recipients should also designate points of contact within their national authorities to co-operate on matters of out-of-country transportation and other matters of mutual concern.

TABLE: CATEGORIZATION OF NUCLEAR MATERIAL

Material	Form	Category		
		I	II	III
1. Plutonium* [a]	Unirradiated* [b]	2 kg or more	Less than 2 kg but more than 500 g	500 g or less* [c]
		2. Uranium-235	Unirradiated* [b]	1 kg or less* [c]
3. Uranium-233	Unirradiated* [b]	- uranium enriched to 20% ²³⁵ U or more	-	Less than 10 kg or more
		- uranium enriched to 10% ²³⁵ U but less than 20%	-	10 kg or more
		- uranium enriched above natural, but less than 10% ²³⁵ U* [d]	-	-
4. Irradiated fuel	Unirradiated* [b]	2 kg or more	Less than 2 kg but more than 500 g	500 g or less* [c]
			Depleted or natural uranium, thorium or low-enriched fuel (less than 10% fissile content)* [e][f]	

[a] As identified in the Trigger List.

[b] Material not irradiated in a reactor or material irradiated in a reactor but with a radiation level equal to or less than 100 rads/hour at one metre unshielded.

[c] Less than a radiologically significant quantity should be exempted.

- [d] Natural uranium, depleted uranium, and thorium and quantities of uranium enriched to less than 10% not falling in Category III should be protected in accordance with prudent management practice.
- [e] Although this level of protection is recommended, it would be open to States, upon evaluation of the specific circumstances, to assign a different category of physical protection.
- [f] Other fuel which by virtue of its original fissile material content is classified as Category I or II before irradiation may be reduced one category levels while the radiation level from the fuel exceed 100 rads/hour at one metre unshielded.

Comparison Table of Changes to the Guidelines for Nuclear Transfers (INFCIRC/254/Part 1)

Old (Revision 8)	New (Revision 9)
<p>Annex A – General Note</p>	<p>3. <u>Suppliers recognize the close relationship for certain isotope separation processes between plants, equipment and technology for uranium enrichment and that for the separation of stable isotopes for research, medical and other non-nuclear industrial purposes. In that regard, suppliers should carefully review their legal measures, including export licensing regulations and information/technology classification and security practices, for stable isotope separation activities to ensure the implementation of appropriate protection measures as warranted. Suppliers recognize that, in particular cases, appropriate protection measures for stable isotope separation activities will be essentially the same as those for uranium enrichment. (See Introductory Note in Section 5 of the Trigger List.) In accordance with Paragraph 16(a) of the Guidelines, suppliers shall consult with other suppliers as appropriate, in order to promote uniform policies and procedures in the transfer and protection of stable isotope separation plants, equipment and technology.</u></p>
<p>Annex A</p> <p>2.5. Plants for the separation of isotopes of uranium and equipment, other than analytical instruments, especially designed or prepared therefor (see Annex B, section 5.);</p>	<p>Annex A</p> <p>2.5. Plants for the separation of isotopes of <u>natural</u> uranium, <u>depleted uranium or special fissionable material</u> and equipment, other than analytical instruments, especially designed or prepared therefor (see Annex B, section 5.);</p>

<p>Annex B</p> <p>5. Plants for the separation of isotopes of uranium and equipment, other than analytical instruments, especially designed or prepared therefor</p>	<p>Annex B</p> <p>5. Plants for the separation of isotopes of <u>natural uranium</u>, <u>depleted uranium</u> or <u>special fissionable material</u> and equipment, other than analytical instruments, especially designed or prepared therefor</p>
	<p>Annex B, Section 5</p> <p><u>INTRODUCTORY NOTE</u></p> <p><u>Plants, equipment and technology for the separation of uranium isotopes have, in many instances, a close relationship to plants, equipment and technology for the separation of stable isotopes. In particular cases, the controls under Section 5 also apply accordingly to plants and equipment that are intended for the separation of stable isotopes. These controls of plants and equipment for the separation of stable isotopes are complementary to controls on plants and equipment especially designed or prepared for the processing, use or production of special fissionable material covered by the Trigger List. These complementary Section 5 controls for stable isotope uses do not apply to the electromagnetic isotope separation process, which is addressed under Part 2 of the Guidelines.</u></p> <p><u>Processes for which the controls in Section 5 equally apply whether the intended use is uranium isotope separation or stable isotope separation are: gas centrifuge, gaseous diffusion, the plasma separation process, and aerodynamic processes.</u></p> <p><u>For some processes, the relationship to uranium isotope separation depends on the element (stable isotope) being separated. These processes are: laser-based processes</u></p>

	<p><u>(e.g., molecular laser isotope separation and atomic vapor laser isotope separation), chemical exchange, and ion exchange. Suppliers must therefore evaluate these processes on a case-by-case basis to apply Section 5 controls for stable isotope uses accordingly.</u></p>
	<p>Annex B</p> <p><u>5.2.3 Special shut-off and control valves</u></p> <p><u>Especially designed or prepared bellows-sealed valves, manual or automated, shut-off or control, made of or protected by materials resistant to corrosion by UF₆, with a diameter of 10 to 160 mm, for use in main or auxiliary systems of gas centrifuge enrichment plants.</u></p>
5.2.3.	5.2.4.
5.2.4.	5.2.5.

Communications Received from Certain Member States Regarding Guidelines for Transfers of Nuclear-related Dual-use Equipment, Materials, Software and Related Technology

1. The Director General of the International Atomic Energy Agency has received Notes Verbales, dated 1 December 2005, from the Resident Representatives to the Agency of Argentina, Australia, Austria, Belarus, Belgium, Brazil, Bulgaria, Canada, Croatia, Czech Republic, Estonia, Finland, France, Germany, Greece, Hungary, Ireland, Italy, Japan, Republic of Korea, Latvia, Lithuania, Luxembourg, Malta, the Netherlands, New Zealand, Poland, Portugal, Slovenia, South Africa, Spain, Sweden, Switzerland, Turkey, Ukraine, the United Kingdom of Great Britain and Northern Ireland and the United States of America, relating to transfers of nuclear-related dual-use equipment, materials, software and related technology.
2. The purpose of the Notes Verbales is to provide further information on those Governments' guidelines for transfers of nuclear-related dual-use equipment, materials, software and related technology.
3. In the light of the wish expressed at the end of each Note Verbale, the text of the Notes Verbales is attached. The attachment to the Notes Verbales is also reproduced in full.

^a INFCIRC/254/Part.1, as amended, contains Guidelines for the export of nuclear material, equipment and technology.

NOTE VERBALE

The Permanent Mission of [Country Name] presents its compliments to the Director General of the International Atomic Energy Agency (IAEA) and has the honour to refer to its [relevant previous communication(s)] concerning the decision of the Government of [Country Name] to act in accordance with the Guidelines for Transfers of Nuclear-Related Dual-Use Equipment, Material and Related Technology currently published as document INFCIRC/254/Rev. 6/Part 2, including its Annex.

The Government of [Country Name] has decided to amend the Guidelines to reflect the need for effective export controls as a relevant factor for Part 2 transfers. Accordingly, Paragraph 4 (i) has been introduced.

The Government of [Country Name] has also decided to amend the Annex entries on machine tools (1.B.2.b and 1.B.2.c) to reflect the changes in current technology and to control new technology. Accordingly, a new Paragraph 3 has been added to both 1.B.2.b and 1.B.2.c to reflect new technological characteristics, the Technical note 2 of the Annex entry 1.B.2 has been amended and new Technical notes 4, 5 and 6 have been added to clarify the scope of controls.

The Government of [Country Name] has also clarified the scope of control for laser lights. Item 1.B.3.c. was amended to reflect that the scope of control does not control laser-based autocollimators. This is in accordance with recent changes made in Wassenaar.

In the interest of clarity, the complete text of the modified Guidelines and its Annex is reproduced in the attachment, as well as a "Comparison Table of Changes to the Guidelines for Transfers of Nuclear-Related Dual-Use Equipment, Material and Related Technology (INFCIRC/254/Rev. 6/Part 2)".

The Government of [Country Name] has decided to act in accordance with the Guidelines so revised.

In reaching this decision, the Government of [Country Name] is fully aware of the need to contribute to economic development while avoiding contributing in any way to a proliferation of nuclear weapons or other nuclear explosive devices or the diversion to acts of nuclear terrorism, and of the need to separate the issue of non-proliferation or non-diversion assurances from that of commercial competition.

[The Government of (Country Name), so far as trade within the European Union is concerned, will implement this decision in the light of its commitments as a Member States of the Union.]¹

¹ This paragraph is included only in notes verbales from members of the European Union.

The Government of [Country Name] would be grateful if the Director General of the IAEA would bring this Note and its attachment to the attention of all Member States.

The Permanent Mission of [Country Name] avails itself of this opportunity to renew to the Director General of the International Atomic Energy Agency the assurances of its highest consideration.

**GUIDELINES FOR TRANSFERS OF NUCLEAR-RELATED
DUAL-USE EQUIPMENT, MATERIALS, SOFTWARE, AND
RELATED TECHNOLOGY**

OBJECTIVE

1. With the objective of averting the proliferation of nuclear weapons and preventing acts of nuclear terrorism, suppliers have had under consideration procedures in relation to the transfer of certain equipment, materials, software, and related technology that could make a major contribution to a "nuclear explosive activity," an "unsafeguarded nuclear fuel-cycle activity" or acts of nuclear terrorism. In this connection, suppliers have agreed on the following principles, common definitions, and an export control list of equipment, materials, software, and related technology. The Guidelines are not designed to impede international co-operation as long as such co-operation will not contribute to a nuclear explosive activity, an unsafeguarded nuclear fuel-cycle activity or acts of nuclear terrorism. Suppliers intend to implement the Guidelines in accordance with national legislation and relevant international commitments.

BASIC PRINCIPLE

2. Suppliers should not authorize transfers of equipment, materials, software, or related technology identified in the Annex:
 - for use in a non-nuclear-weapon state in a nuclear explosive activity or an unsafeguarded nuclear fuel-cycle activity, or
 - in general, when there is an unacceptable risk of diversion to such an activity, or when the transfers are contrary to the objective of averting the proliferation of nuclear weapons, or
 - when there is an unacceptable risk of diversion to acts of nuclear terrorism.

EXPLANATION OF TERMS

3. (a) "Nuclear explosive activity" includes research on or development, design, manufacture, construction, testing or maintenance of any nuclear explosive device or components or subsystems of such a device.
- (b) "Unsafeguarded nuclear fuel-cycle activity" includes research on or development, design, manufacture, construction, operation or maintenance of any reactor, critical facility, conversion plant, fabrication plant, reprocessing plant, plant for the separation of isotopes of source or special fissionable material, or separate storage installation, where there is no obligation to accept International Atomic Energy Agency (IAEA) safeguards at the relevant facility or installation, existing or future, when it contains any source or special fissionable material; or of any heavy water production plant where there is no obligation to accept IAEA safeguards on any nuclear material produced by or used in connection with any heavy water produced therefrom; or where any such obligation is not met.

ESTABLISHMENT OF EXPORT LICENSING PROCEDURES

4. Suppliers should have in place legal measures to ensure the effective implementation of the Guidelines, including export licensing regulations, enforcement measures, and penalties for violations. In considering whether to authorize transfers, suppliers should exercise prudence in order to carry out the Basic Principle and should take relevant factors into account, including:
 - (a) Whether the recipient state is a party to the Nuclear Non-Proliferation Treaty (NPT) or to the Treaty for the Prohibition of Nuclear Weapons in Latin America (Treaty of Tlatelolco), or to a similar international legally-binding nuclear non-proliferation agreement, and has an IAEA safeguards agreement in force applicable to all its peaceful nuclear activities;
 - (b) Whether any recipient state that is not party to the NPT, Treaty of Tlatelolco, or a similar international legally-binding nuclear non-proliferation agreement has any facilities or installations listed in paragraph 3(b) above that are operational or being designed or constructed that are not, or will not be, subject to IAEA safeguards;
 - (c) Whether the equipment, materials, software, or related technology to be transferred is appropriate for the stated end-use and whether that stated end-use is appropriate for the end-user;
 - (d) Whether the equipment, materials, software, or related technology to be transferred is to be used in research on or development, design, manufacture, construction, operation, or maintenance of any reprocessing or enrichment facility;
 - (e) Whether governmental actions, statements, and policies of the recipient state are supportive of nuclear non-proliferation and whether the recipient state is in compliance with its international obligations in the field of non-proliferation;
 - (f) Whether the recipients have been engaged in clandestine or illegal procurement activities; and
 - (g) Whether a transfer has not been authorized to the end-user or whether the end-user has diverted for purposes inconsistent with the Guidelines any transfer previously authorized.
 - (h) Whether there is reason to believe that there is a risk of diversion to acts of nuclear terrorism.
 - (i) Whether there is a risk of retransfers of equipment, material, software, or related technology identified in the Annex or of transfers of any replica thereof contrary to the Basic Principle, as a result of a failure by the recipient State to develop and maintain appropriate, effective national export and transshipment controls, as identified by UNSC Resolution 1540.
5. Suppliers should ensure that their national legislation requires an authorisation for the transfer of items not listed in the Annex if the items in question are or may be intended, in their entirety or in part, for use in connection with a “nuclear explosive activity.”

Suppliers will implement such an authorisation requirement in accordance with their domestic licensing practices.

Suppliers are encouraged to share information on "catch all" denials.

CONDITIONS FOR TRANSFERS

6. In the process of determining that the transfer will not pose any unacceptable risk of diversion, in accordance with the Basic Principle and to meet the objectives of the Guidelines, the supplier should obtain, before authorizing the transfer and in a manner consistent with its national law and practices, the following:
 - (a) a statement from the end-user specifying the uses and end-use locations of the proposed transfers; and
 - (b) an assurance explicitly stating that the proposed transfer or any replica thereof will not be used in any nuclear explosive activity or unsafeguarded nuclear fuel-cycle activity.

CONSENT RIGHTS OVER RETRANSFERS

7. Before authorizing the transfer of equipment, materials, software, or related technology identified in the Annex to a country not adhering to the Guidelines, suppliers should obtain assurances that their consent will be secured, in a manner consistent with their national law and practices, prior to any retransfer to a third country of the equipment, materials, software, or related technology, or any replica thereof.

CONCLUDING PROVISIONS

8. The supplier reserves to itself discretion as to the application of the Guidelines to other items of significance in addition to those identified in the Annex, and as to the application of other conditions for transfer that it may consider necessary in addition to those provided for in paragraph 5 of the Guidelines.
9. In furtherance of the effective implementation of the Guidelines, suppliers should, as necessary and appropriate, exchange relevant information and consult with other states adhering to the Guidelines.
10. In the interest of international peace and security, the adherence of all states to the Guidelines would be welcome.

ANNEX

**LIST OF NUCLEAR-RELATED DUAL-USE
EQUIPMENT, MATERIALS, SOFTWARE, AND
RELATED TECHNOLOGY**

ANNEX

Note: The International System of Units (SI) is used in this Annex. In all cases the physical quantity defined in SI units should be considered the official recommended control value. However, some machine tool parameters are given in their customary units, which are not SI.

Commonly used abbreviations (and their prefixes denoting size) in this Annex are as follows:

A	---	ampere(s)
Bq	---	becquerel(s)
°C	---	degree(s) Celsius
CAS	---	chemical abstracts service
Ci	---	curie(s)
cm	---	centimeter(s)
dB	---	decibel(s)
dBm	---	decibel referred to 1 milliwatt
g	---	gram(s); also, acceleration of gravity (9.81 m/s ²)
GBq	---	gigabecquerel(s)
GHz	---	gigahertz
GPa	---	gigapascal(s)
Gy	---	gray
h	---	hour(s)
Hz	---	hertz
J	---	joule(s)
K	---	kelvin
keV	---	thousand electron volt(s)
kg	---	kilogram(s)
kHz	---	kilohertz
kN	---	kilonewton(s)
kPa	---	kilopascal(s)
kV	---	kilovolt(s)
kW	---	kilowatt(s)
m	---	meter(s)
mA	---	milliampere(s)
MeV	---	million electron volt(s)
MHz	---	megahertz
ml	---	milliliter(s)
mm	---	millimeter(s)
MPa	---	megapascal(s)
mPa	---	millipascal(s)
MW	---	megawatt(s)
μF	---	microfarad(s)
μm	---	micrometer(s)
μs	---	microsecond(s)
N	---	newton(s)
nm	---	nanometer(s)
ns	---	nanosecond(s)
nH	---	nanohenry(ies)
ps	---	picosecond(s)
RMS	---	root mean square
rpm	---	revolutions per minute
s	---	second(s)
T	---	tesla(s)
TIR	---	total indicator reading
V	---	volt(s)
W	---	watt(s)

GENERAL NOTE

The following paragraphs are applied to the List of Nuclear-Related Dual-Use Equipment, Material, Software, and Related Technology.

1. The description of any item on the List includes that item in either new or second-hand condition.
2. When the description of any item on the List contains no qualifications or specifications, it is regarded as including all varieties of that item. Category captions are only for convenience in reference and do not affect the interpretation of item definitions.
3. The object of these controls should not be defeated by the transfer of any non-controlled item (including plants) containing one or more controlled components when the controlled component or components are the principal element of the item and can feasibly be removed or used for other purposes.

Note: In judging whether the controlled component or components are to be considered the principal element, governments should weigh the factors of quantity, value, and technological know-how involved and other special circumstances which might establish the controlled component or components as the principal element of the item being procured.

4. The object of these controls should not be defeated by the transfer of component parts. Each government will take such action as it can to achieve this aim and will continue to seek a workable definition for component parts, which could be used by all the suppliers.

TECHNOLOGY CONTROLS

The transfer of "technology" is controlled according to the Guidelines and as described in each section of the Annex. "Technology" directly associated with any item in the Annex will be subject to as great a degree of scrutiny and control as will the item itself, to the extent permitted by national legislation.

The approval of any Annex item for export also authorizes the export to the same end user of the minimum "technology" required for the installation, operation, maintenance, and repair of the item.

Note: Controls on "technology" transfer do not apply to information "in the public domain" or to "basic scientific research".

GENERAL SOFTWARE NOTE

The transfer of "software" is controlled according to the Guidelines and as described in the Annex.

Note: Controls on "software" transfers do not apply to "software" as follows:

1. Generally available to the public by being:
 - a. Sold from stock at retail selling points without restriction; and
 - b. Designed for installation by the user without further substantial support by the supplier;or
2. "In the public domain".

DEFINITIONS

"Accuracy" --

Usually measured in terms of inaccuracy, defined as the maximum deviation, positive or negative, of an indicated value from an accepted standard or true value.

"Angular position deviation" --

The maximum difference between angular position and the actual, very accurately measured angular position after the workpiece mount of the table has been turned out of its initial position. (Ref. VDI/VDE 2617 Draft: "Rotary table on coordinate measuring machines")

"Basic scientific research" --

Experimental or theoretical work undertaken principally to acquire new knowledge of the fundamental principles of phenomena and observable facts, not primarily directed toward a specific practical aim or objective.

"Contouring control" --

Two or more "numerically controlled" motions operating in accordance with instructions that specify the next required position and the required feed rates to that position. These feed rates are varied in relation to each other so that a desired contour is generated. (Ref. ISO 2806-1980 as amended)

"Development" --

is related to all phases before "production" such as:

- design
- design research
- design analysis
- design concepts
- assembly and testing of prototypes
- pilot production schemes
- design data
- process of transforming design data into a product
- configuration design
- integration design
- layouts

"Fibrous or filamentary materials" --

means continuous 'monofilaments', 'yarns', 'rovings', 'tows' or 'tapes'.

N.B.:

1. 'Filament' or 'monofilament' --

is the smallest increment of fiber, usually several μm in diameter.

2. 'Roving' --

is a bundle (typically 12-120) of approximately parallel 'strands'.

3. 'Strand' --

is a bundle of 'filaments' (typically over 200) arranged approximately parallel.

4. 'Tape' --

is a material constructed of interlaced or unidirectional 'filaments', 'strands', 'rovings', 'tows' or 'yarns', etc., usually preimpregnated with resin.

5. 'Tow' --

is a bundle of 'filaments', usually approximately parallel.

6. 'Yarn' --

is a bundle of twisted 'strands'.

'Filament' --

See "Fibrous or filamentary materials".

"In the public domain" --

"In the public domain", as it applies herein, means "technology" or "software" that has been made available without restrictions upon its further dissemination. (Copyright restrictions do not remove "technology" or "software" from being "in the public domain".)

"Linearity" --

(Usually measured in terms of non-linearity) is the maximum deviation of the actual characteristic (average of upscale and downscale readings), positive or negative, from a straight line so positioned as to equalize and minimize the maximum deviations.

"Measurement uncertainty" --

The characteristic parameter which specifies in what range around the output value the correct value of the measurable variable lies with a confidence level of 95%. It includes the uncorrected systematic deviations, the uncorrected backlash, and the random deviations. (Ref. VDI/VDE 2617)

"Microprogram" --

A sequence of elementary instructions, maintained in a special storage, the execution of which is initiated by the introduction of its reference instruction into an instruction register.

'Monofilament' --

See "Fibrous or filamentary materials".

"Numerical control" --

The automatic control of a process performed by a device that makes use of numeric data usually introduced as the operation is in progress. (Ref. ISO 2382)

"Positioning accuracy" --

of "numerically controlled" machine tools is to be determined and presented in accordance with Item 1.B.2., in conjunction with the requirements below:

(a) Test conditions (ISO 230/2 (1988), paragraph 3):

- (1) For 12 hours before and during measurements, the machine tool and accuracy measuring equipment will be kept at the same ambient temperature. During the premeasurement time, the slides of the machine will be continuously cycled identically to the way they will be cycled during the accuracy measurements;
- (2) The machine shall be equipped with any mechanical, electronic, or software compensation to be exported with the machine;
- (3) Accuracy of measuring equipment for the measurements shall be at least four times more accurate than the expected machine tool accuracy;
- (4) Power supply for slide drives shall be as follows:
 - (i) Line voltage variation shall not be greater than $\pm 10\%$ of nominal rated voltage;
 - (ii) Frequency variation shall not be greater than ± 2 Hz of normal frequency;
 - (iii) Lineouts or interrupted service are not permitted.

(b) Test Program (paragraph 4):

- (1) Feed rate (velocity of slides) during measurement shall be the rapid traverse rate;

N.B.: In the case of machine tools which generate optical quality surfaces, the feed rate shall be equal to or less than 50 mm per minute;

- (2) Measurements shall be made in an incremental manner from one limit of the axis travel to the other without returning to the starting position for each move to the target position;
- (3) Axes not being measured shall be retained at mid-travel during test of an axis.

(c) Presentation of the test results (paragraph 2):

The results of the measurements must include:

- (1) "positioning accuracy" (A) and
- (2) The mean reversal error (B).

"Production" --

means all production phases such as:

- construction
- production engineering
- manufacture
- integration
- assembly (mounting)
- inspection
- testing
- quality assurance

"Program" --

A sequence of instructions to carry out a process in, or convertible into, a form executable by an electronic computer.

"Resolution" --

The least increment of a measuring device; on digital instruments, the least significant bit.
(Ref. ANSI B-89.1.12)

"Roving" --

See "Fibrous or filamentary materials".

"Software" --

A collection of one or more "programs" or "microprograms" fixed in any tangible medium of expression.

'Strand' --

See "Fibrous or filamentary materials".

'Tape' --

See "Fibrous or filamentary materials".

"Technical assistance" --

"Technical assistance" may take forms such as: instruction, skills, training, working knowledge, consulting services.

Note: "Technical assistance" may involve transfer of "technical data".

"Technical data" --

"Technical data" may take forms such as blueprints, plans, diagrams, models, formulae, engineering designs and specifications, manuals and instructions written or recorded on other media or devices such as disk, tape, read-only memories.

"Technology" --

means specific information required for the "development", "production", or "use" of any item contained in the List. This information may take the form of "technical data" or "technical assistance".

"Tow" --

See "Fibrous or filamentary materials".

"Use" --

Operation, installation (including on-site installation), maintenance (checking), repair, overhaul, and refurbishing.

"Yarn" --

See "Fibrous or filamentary materials".

ANNEX CONTENTS

1. INDUSTRIAL EQUIPMENT

1.A.	EQUIPMENT, ASSEMBLIES AND COMPONENTS	
1.A.1.	High-density radiation shielding windows	1 - 1
1.A.2.	Radiation-hardened TV cameras, or lenses therefor	1 - 1
1.A.3.	Robots, end-effectors' and control units	1 - 1
1.A.4.	Remote manipulators	1 - 3
1.B.	TEST AND PRODUCTION EQUIPMENT	
1.B.1.	Flow-forming machines, spin-forming machines capable of flow-forming functions, and mandrels	1 - 3
1.B.2.	Machine tools	1 - 4
1.B.3.	Dimensional inspection machines, instruments, or systems	1 - 6
1.B.4.	Controlled atmosphere induction furnaces, and power supplies therefor	1 - 7
1.B.5.	Isostatic presses, and related equipment	1 - 7
1.B.6.	Vibration test systems, equipment, and components	1 - 8
1.B.7.	Vacuum or other controlled atmosphere metallurgical melting and casting furnaces and related equipment	1 - 8
1.C.	MATERIALS	1 - 9
1.D.	SOFTWARE	1 - 9
1.E.	TECHNOLOGY	1 - 9

ANNEX CONTENTS

2. MATERIALS

2.A.	EQUIPMENT, ASSEMBLIES AND COMPONENTS	
2.A.1.	Crucibles made of materials resistant to liquid actinide metals	2 – 1
2.A.2.	Platinized catalysts	2 – 1
2.A.3.	Composite structures in the forms of tubes	2 – 2
2.B.	TEST AND PRODUCTION EQUIPMENT	
2.B.1.	Tritium facilities or plants, and equipment therefor	2 – 2
2.B.2.	Lithium isotope separation facilities or plants, and equipment therefor	2 – 2
2.C.	MATERIALS	
2.C.1.	Aluminium	2 – 2
2.C.2.	Beryllium	2 – 3
2.C.3.	Bismuth	2 – 3
2.C.4.	Boron	2 – 3
2.C.5.	Calcium	2 – 3
2.C.6.	Chlorine trifluoride	2 – 3
2.C.7.	Fibrous or filamentary materials, and preregs	2 – 3
2.C.8.	Hafnium	2 – 4
2.C.9.	Lithium	2 – 4
2.C.10.	Magnesium	2 – 4
2.C.11.	Maraging steel	2 – 4
2.C.12.	Radium-226	2 – 4
2.C.13.	Titanium	2 – 5
2.C.14.	Tungsten	2 – 5
2.C.15.	Zirconium	2 – 5
2.C.16.	Nickel powder and porous nickel metal	2 – 5
2.C.17.	Tritium	2 – 6
2.C.18.	Helium-3	2 – 6
2.C.19.	Alpha-emitting radionuclides	2 – 6
2.D.	SOFTWARE	2 – 6
2.E.	TECHNOLOGY	2 – 6

ANNEX CONTENTS

3. URANIUM ISOTOPE SEPARATION EQUIPMENT AND COMPONENTS
(Other Than Trigger List Items)

3.A.	EQUIPMENT, ASSEMBLIES AND COMPONENTS	
3.A.1.	Frequency changers or generators	3 – 1
3.A.2.	Lasers, laser amplifiers and oscillators	3 – 1
3.A.3.	Valves	3 – 3
3.A.4.	Superconducting solenoidal electromagnets	3 – 3
3.A.5.	High-power direct current power supplies	3 – 3
3.A.6.	High-voltage direct current power supplies	3 – 3
3.A.7.	Pressure transducers	3 – 4
3.A.8.	Vacuum pumps	3 – 4
3.B.	TEST AND PRODUCTION EQUIPMENT	
3.B.1.	Electrolytic cells for fluorine production	3 – 4
3.B.2.	Rotor fabrication or assembly equipment, rotor straightening equipment, bellows-forming mandrels and dies	3 – 4
3.B.3.	Centrifugal multiplane balancing machines	3 – 5
3.B.4.	Filament winding machines and related equipment	3 – 5
3.B.5.	Electromagnetic isotope separators	3 – 6
3.B.6.	Mass spectrometers	3 – 6
3.C.	MATERIALS	3 – 7
3.D.	SOFTWARE	3 – 7
3.E.	TECHNOLOGY	3 – 7

4. HEAVY WATER PRODUCTION PLANT RELATED EQUIPMENT
(Other Than Trigger List Items)

4.A.	EQUIPMENT, ASSEMBLIES AND COMPONENTS	
4.A.1.	Specialized packings	4 – 1
4.A.2.	Pumps	4 – 1
4.A.3.	Turboexpanders or turboexpander-compressor sets	4 – 1
4.B.	TEST AND PRODUCTION EQUIPMENT	
4.B.1.	Water-hydrogen sulfide exchange tray columns and internal contactors	4 – 1
4.B.2.	Hydrogen-cryogenic distillation columns	4 – 2
4.B.3.	Ammonia synthesis converters or synthesis units	4 – 2
4.C.	MATERIALS	4 – 2
4.D.	SOFTWARE	4 – 2
4.E.	TECHNOLOGY	4 – 2

5. TEST AND MEASUREMENT EQUIPMENT FOR THE DEVELOPMENT OF NUCLEAR EXPLOSIVE
DEVICES

5.A.	EQUIPMENT, ASSEMBLIES AND COMPONENTS	
5.A.1.	Photomultiplier tubes	5 – 1
5.B.	TEST AND PRODUCTION EQUIPMENT	
5.B.1.	Flash X-ray generators or pulsed electron accelerators	5 – 1
5.B.2.	Multistage light gas guns or other high-velocity gun systems	5 – 1
5.B.3.	Mechanical rotating mirror cameras	5 – 2
5.B.4.	Electronic streak cameras, electronic framing cameras, tubes and devices	5 – 2
5.B.5.	Specialized instrumentation for hydrodynamic experiments	5 – 2
5.B.6.	High-speed pulse generators	5 – 3
5.C.	MATERIALS	5 – 3
5.D.	SOFTWARE	5 – 3
5.E.	TECHNOLOGY	5 – 3

ANNEX CONTENTS

6. COMPONENTS FOR NUCLEAR EXPLOSIVE DEVICES

6.A.	EQUIPMENT, ASSEMBLIES AND COMPONENTS	
6.A.1.	Detonators and multipoint initiation systems	6-1
6.A.2.	Firing sets and equivalent high-current pulse generators	6-1
6.A.3.	Switching devices	6-2
6.A.4.	Pulse discharge capacitors	6-2
6.A.5.	Neutron generator systems	6-3
6.B.	TEST AND PRODUCTION EQUIPMENT	6-3
6.C.	MATERIALS	
6.C.1.	High explosive substances or mixtures	6-3
6.D.	SOFTWARE	6-3
6.E.	TECHNOLOGY	6-3

1. INDUSTRIAL EQUIPMENT

1.A. EQUIPMENT, ASSEMBLIES AND COMPONENTS

1.A.1. High-density (lead glass or other) radiation shielding windows, having all of the following characteristics, and specially designed frames therefor:

- a. A 'cold area' greater than 0.09 m²;
- b. A density greater than 3 g/cm³; and
- c. A thickness of 100 mm or greater.

Technical Note: In Item 1.A.1.a. the term 'cold area' means the viewing area of the window exposed to the lowest level of radiation in the design application.

1.A.2. Radiation-hardened TV cameras, or lenses therefor, specially designed or rated as radiation hardened to withstand a total radiation dose greater than 5 x 10⁴ Gy (silicon) without operational degradation.

Technical Note: The term Gy (silicon) refers to the energy in Joules per kilogram absorbed by an unshielded silicon sample when exposed to ionizing radiation.

1.A.3. 'Robots', 'end-effectors' and control units as follows:

- a. 'Robots' or 'end-effectors' having either of the following characteristics:
 1. Specially designed to comply with national safety standards applicable to handling high explosives (for example, meeting electrical code ratings for high explosives); or
 2. Specially designed or rated as radiation hardened to withstand a total radiation dose greater than 5 x 10⁴ Gy (silicon) without operational degradation;

Technical Note: The term Gy (silicon) refers to the energy in Joules per kilogram absorbed by an unshielded silicon sample when exposed to ionizing radiation.

- b. Control units specially designed for any of the 'robots' or 'end-effectors' specified in Item 1.A.3.a.

Note: Item 1.A.3. does not control 'robots' specially designed for non-nuclear industrial applications such as automobile paint-spraying booths.

Technical Notes: 1. 'Robots'

In Item 1.A.3. 'robot' means a manipulation mechanism, which may be of the continuous path or of the point-to-point variety, may use 'sensors', and has all of the following characteristics:

(a) is multifunctional;

- (b) *is capable of positioning or orienting material, parts, tools, or special devices through variable movements in three-dimensional space;*
- (c) *incorporates three or more closed or open loop servo-devices which may include stepping motors; and*
- (d) *has 'user-accessible programmability' by means of teach/playback method or by means of an electronic computer which may be a programmable logic controller, i.e., without mechanical intervention.*

N.B.1:

In the above definition 'sensors' means detectors of a physical phenomenon, the output of which (after conversion into a signal that can be interpreted by a control unit) is able to generate "programs" or modify programmed instructions or numerical "program" data. This includes 'sensors' with machine vision, infrared imaging, acoustical imaging, tactile feel, inertial position measuring, optical or acoustic ranging or force or torque measuring capabilities.

N.B.2:

In the above definition 'user-accessible programmability' means the facility allowing a user to insert, modify or replace "programs" by means other than:

- (a) *a physical change in wiring or interconnections; or*
- (b) *the setting of function controls including entry of parameters.*

N.B.3:

The above definition does not include the following devices:

- (a) *Manipulation mechanisms which are only manually/teleoperator controllable;*
- (b) *Fixed sequence manipulation mechanisms which are automated moving devices operating according to mechanically fixed programmed motions. The "program" is mechanically limited by fixed stops, such as pins or cams. The sequence of motions and the selection of paths or angles are not variable or changeable by mechanical, electronic, or electrical means;*
- (c) *Mechanically controlled variable sequence manipulation mechanisms which are automated moving devices operating according to mechanically fixed programmed motions. The "program" is mechanically limited by fixed, but adjustable, stops such as pins or cams. The sequence of motions and the selection of paths or angles are variable within the fixed "program" pattern. Variations or modifications of the "program" pattern (e.g.,*

changes of pins or exchanges of cams) in one or more motion axes are accomplished only through mechanical operations;

(d) Non-servo-controlled variable sequence manipulation mechanisms which are automated moving devices, operating according to mechanically fixed programmed motions. The "program" is variable but the sequence proceeds only by the binary signal from mechanically fixed electrical binary devices or adjustable stops;

(e) Stacker cranes defined as Cartesian coordinate manipulator systems manufactured as an integral part of a vertical array of storage bins and designed to access the contents of those bins for storage or retrieval.

2. 'End-effectors'

In Item 1.A.3. 'end-effectors' are grippers, 'active tooling units', and any other tooling that is attached to the baseplate on the end of a 'robot' manipulator arm.

N.B.:

In the above definition 'active tooling units' is a device for applying motive power, process energy or sensing to the workpiece.

- 1.A.4. Remote manipulators that can be used to provide remote actions in radiochemical separation operations or hot cells, having either of the following characteristics:
- a. A capability of penetrating 0.6 m or more of hot cell wall (through-the-wall operation); or
 - b. A capability of bridging over the top of a hot cell wall with a thickness of 0.6 m or more (over-the-wall operation).

Technical Note: *Remote manipulators provide translation of human operator actions to a remote operating arm and terminal fixture. They may be of a master/slave type or operated by joystick or keypad.*

1.B. TEST AND PRODUCTION EQUIPMENT

- 1.B.1. Flow-forming machines, spin-forming machines capable of flow-forming functions, and mandrels, as follows:
- a. Machines having both of the following characteristics:
 1. Three or more rollers (active or guiding); and
 2. Which, according to the manufacturer's technical specification, can be equipped with "numerical control" units or a computer control;

- b. Rotor-forming mandrels designed to form cylindrical rotors of inside diameter between 75 and 400 mm.

Note: Item 1.B.1.a. includes machines which have only a single roller designed to deform metal plus two auxiliary rollers which support the mandrel, but do not participate directly in the deformation process.

- 1.B.2. Machine tools, as follows, and any combination thereof, for removing or cutting metals, ceramics, or composites, which, according to the manufacturer's technical specifications, can be equipped with electronic devices for simultaneous "contouring control" in two or more axes:

N.B.: For "numerical control" units controlled by their associated "software", see Item 1.D.3.

- a. Machine tools for turning, that have "positioning accuracies" with all compensations available better (less) than 6 μm according to ISO 230/2 (1988) along any linear axis (overall positioning) for machines capable of machining diameters greater than 35 mm;

Note: Item 1.B.2.a. does not control bar machines (Swissturn), limited to machining only bar feed thru, if maximum bar diameter is equal to or less than 42 mm and there is no capability of mounting chucks. Machines may have drilling and/or milling capabilities for machining parts with diameters less than 42 mm.

- b. Machine tools for milling, having any of the following characteristics:

- 1. "Positioning accuracies" with all compensations available better (less) than 6 μm according to ISO 230/2 (1988) along any linear axis (overall positioning);
- 2. Two or more contouring rotary axes; or
- 3. Five or more axes, which can be coordinated simultaneously for "contouring control".

Note: Item 1.B.2.b. does not control milling machines having both of the following characteristics:

- 1. X-axis travel greater than 2 m; and
- 2. Overall "positioning accuracy" on the x-axis worse (more) than 30 μm according to ISO 230/2 (1988).

- c. Machine tools for grinding, having any of the following characteristics:

- 1. "Positioning accuracies" with all compensations available better (less) than 4 μm according to ISO 230/2 (1988) along any linear axis (overall positioning);
- 2. Two or more contouring rotary axes; or
- 3. Five or more axes, which can be coordinated simultaneously for "contouring control."

Note: Item 1.B.2.c. does not control grinding machines as follows:

- 1. Cylindrical external, internal, and external-internal grinding machines having all the following characteristics:

- a. Limited to a maximum workpiece capacity of 150 mm outside diameter or length; and
 - b. Axes limited to x, z and c.
2. Jig grinders that do not have a z-axis or a w-axis with an overall positioning accuracy less (better) than 4 microns. Positioning accuracy is according to ISO 230/2 (1988).
- d. Non-wire type Electrical Discharge Machines (EDM) that have two or more contouring rotary axes and that can be coordinated simultaneously for "contouring control".

Notes: 1. Stated "positioning accuracy" levels derived under the following procedures from measurements made according to ISO 230/2 (1988) or national equivalents may be used for each machine tool model if provided to, and accepted by, national authorities instead of individual machine tests.

Stated "positioning accuracy" are to be derived as follows:

- a. Select five machines of a model to be evaluated;
 - b. Measure the linear axis accuracies according to ISO 230/2 (1988);
 - c. Determine the accuracy values (A) for each axis of each machine. The method of calculating the accuracy value is described in the ISO 230/2 (1988) standard;
 - d. Determine the average accuracy value of each axis. This average value becomes the stated "positioning accuracy" of each axis for the model ($\hat{A}_x, \hat{A}_y, \dots$);
 - e. Since Item 1.B.2. refers to each linear axis, there will be as many stated "positioning accuracy" values as there are linear axes;
 - f. If any axis of a machine tool not controlled by Items 1.B.2.a., 1.B.2.b., or 1.B.2.c. has a stated "positioning accuracy" of 6 μm or better (less) for grinding machines, and 8 μm or better (less) for milling and turning machines, both according to ISO 230/2 (1988), then the builder should be required to reaffirm the accuracy level once every eighteen months.
2. Item 1.B.2. does not control special purpose machine tools limited to the manufacture of any of the following parts:
- a. Gears
 - b. Crankshafts or camshafts
 - c. Tools or cutters
 - d. Extruder worms

Technical Notes: 1. Axis nomenclature shall be in accordance with International Standard ISO 841, "Numerical Control Machines - Axis and Motion Nomenclature".

2. *Not counted in the total number of contouring axes are secondary parallel contouring axes (e.g., the w-axis on horizontal boring mills or a secondary rotary axis the centerline of which is parallel to the primary rotary axis).*
3. *Rotary axes do not necessarily have to rotate over 360 degrees. A rotary axis can be driven by a linear device, e.g., a screw or a rack-and-pinion.*
4. *For the purposes of 1.B.2. the number of axes which can be coordinated simultaneously for "contouring control" is the number of axes along or around which, during processing of the workpiece, simultaneous and interrelated motions are performed between the workpiece and a tool. This does not include any additional axes along or around which other relative motions within the machine are performed, such as:
 - a. *Wheel-dressing systems in grinding machines;*
 - b. *Parallel rotary axes designed for mounting of separate workpieces;*
 - c. *Co-linear rotary axes designed for manipulating the same workpiece by holding it in a chuck from different ends.**
5. *A machine tool having at least 2 of the 3 turning, milling or grinding capabilities (e.g., a turning machine with milling capability) must be evaluated against each applicable entry, 1.B.2.a., 1.B.2.b. and 1.B.2.c.*
6. *Items 1.B.2.b.3 and 1.B.2.c.3 include machines based on a parallel linear kinematic design (e.g., hexapods) that have 5 or more axes none of which are rotary axes.*

1.B.3. Dimensional inspection machines, instruments, or systems, as follows:

- a. Computer controlled or numerically controlled dimensional inspection machines having both of the following characteristics:
 1. Two or more axes; and
 2. A one-dimensional length "measurement uncertainty" equal to or better (less) than $(1.25 + L/1000) \mu\text{m}$ tested with a probe of an "accuracy" of better (less) than $0.2 \mu\text{m}$ (L is the measured length in millimeters) (Ref: VDI/VDE 2617 parts 1 and 2);
- b. Linear displacement measuring instruments, as follows:
 1. Non-contact type measuring systems with a "resolution" equal to or better (less) than $0.2 \mu\text{m}$ within a measuring range up to 0.2 mm;
 2. Linear variable differential transformer (LVDT) systems having both of the following characteristics:
 - a. "Linearity" equal to or better (less) than 0.1% within a measuring range up to 5 mm; and
 - b. Drift equal to or better (less) than 0.1% per day at a standard ambient test room temperature $\pm 1 \text{ K}$;

3. Measuring systems having both of the following characteristics:
 - a. Contain a laser; and
 - b. Maintain for at least 12 hours, over a temperature range of ± 1 K around a standard temperature and a standard pressure:
 1. A "resolution" over their full scale of $0.1 \mu\text{m}$ or better; and
 2. With a "measurement uncertainty" equal to or better (less) than $(0.2 + L/2000) \mu\text{m}$ (L is the measured length in millimeters);

Note: Item 1.B.3.b.3. does not control measuring interferometer systems, without closed or open loop feedback, containing a laser to measure slide movement errors of machine tools, dimensional inspection machines, or similar equipment.

Technical Note: *In Item 1.B.3.b. 'linear displacement' means the change of distance between the measuring probe and the measured object.*

- c. Angular displacement measuring instruments having an "angular position deviation" equal to or better (less) than 0.00025° ;

Note: Item 1.B.3.c. does not control optical instruments, such as autocollimators, using collimated light (e.g., laser light) to detect angular displacement of a mirror.

- d. Systems for simultaneous linear-angular inspection of hemishells, having both of the following characteristics:

1. "Measurement uncertainty" along any linear axis equal to or better (less) than $3.5 \mu\text{m}$ per 5 mm; and
2. "Angular position deviation" equal to or less than 0.02° .

- Notes:
1. Item 1.B.3. includes machine tools that can be used as measuring machines if they meet or exceed the criteria specified for the measuring machine function.
 2. Machines described in Item 1.B.3. are controlled if they exceed the threshold specified anywhere within their operating range.

- Technical Notes:
1. *The probe used in determining the measurement uncertainty of a dimensional inspection system shall be as described in VDI/VDE 2617 parts 2, 3 and 4.*
 2. *All parameters of measurement values in this item represent plus/minus, i.e., not total band.*

- 1.B.4. Controlled atmosphere (vacuum or inert gas) induction furnaces, and power supplies therefor, as follows:

- a. Furnaces having all of the following characteristics:
 1. Capable of operation at temperatures above 1123 K (850 °C);
 2. Induction coils 600 mm or less in diameter; and

3. Designed for power inputs of 5 kW or more;

Note: Item 1.B.4.a. does not control furnaces designed for the processing of semiconductor wafers.

b. Power supplies, with a specified output power of 5 kW or more, specially designed for furnaces specified in Item 1.B.4.a.

1.B.5. 'Isostatic presses', and related equipment, as follows:

a. 'Isostatic presses' having both of the following characteristics:

1. Capable of achieving a maximum working pressure of 69 MPa or greater; and

2. A chamber cavity with an inside diameter in excess of 152 mm;

b. Dies, molds, and controls specially designed for the 'isostatic presses' specified in Item 1.B.5.a.

Technical Notes: 1. *In Item 1.B.5. 'Isostatic presses' means equipment capable of pressurizing a closed cavity through various media (gas, liquid, solid particles, etc.) to create equal pressure in all directions within the cavity upon a workpiece or material.*

2. *In Item 1.B.5. the inside chamber dimension is that of the chamber in which both the working temperature and the working pressure are achieved and does not include fixtures. That dimension will be the smaller of either the inside diameter of the pressure chamber or the inside diameter of the insulated furnace chamber, depending on which of the two chambers is located inside the other.*

1.B.6. Vibration test systems, equipment, and components as follows:

a. Electrodynamic vibration test systems, having all of the following characteristics:

1. Employing feedback or closed loop control techniques and incorporating a digital control unit;

2. Capable of vibrating at 10 g RMS or more between 20 and 2000 Hz; and

3. Capable of imparting forces of 50 kN or greater measured 'bare table';

b. Digital control units, combined with "software" specially designed for vibration testing, with a real-time bandwidth greater than 5 kHz and being designed for a system specified in Item 1.B.6.a.;

c. Vibration thrusters (shaker units), with or without associated amplifiers, capable of imparting a force of 50 kN or greater measured 'bare table', which are usable for the systems specified in Item 1.B.6.a.;

d. Test piece support structures and electronic units designed to combine multiple shaker units into a complete shaker system capable of providing an effective combined force of 50 kN or greater, measured 'bare table', which are usable for the systems specified in Item 1.B.6.a.

Technical Note: *In Item 1.B.6. 'bare table' means a flat table, or surface, with no fixtures or fittings.*

- 1.B.7. Vacuum or other controlled atmosphere metallurgical melting and casting furnaces and related equipment, as follows:
- a. Arc remelt and casting furnaces having both of the following characteristics:
 - 1. Consumable electrode capacities between 1000 and 20000 cm³; and
 - 2. Capable of operating with melting temperatures above 1973 K (1700 °C);
 - b. Electron beam melting furnaces and plasma atomization and melting furnaces, having both of the following characteristics:
 - 1. A power of 50 kW or greater; and
 - 2. Capable of operating with melting temperatures above 1473 K (1200 °C);
 - c. Computer control and monitoring systems specially configured for any of the furnaces specified in Item 1.B.7.a. or 1.B.7.b.
- 1.C. MATERIALS
- None.
- 1.D. SOFTWARE
- 1.D.1. "Software" specially designed for the "use" of equipment specified in Item 1.A.3., 1.B.1., 1.B.3., 1.B.5., 1.B.6.a., 1.B.6.b., 1.B.6.d. or 1.B.7.
- Note: "Software" specially designed for systems specified in Item 1.B.3.d. includes "software" for simultaneous measurements of wall thickness and contour.
- 1.D.2. "Software" specially designed or modified for the "development", "production", or "use" of equipment specified in Item 1.B.2.
- 1.D.3. "Software" for any combination of electronic devices or system enabling such device(s) to function as a "numerical control" unit capable of controlling five or more interpolating axes that can be coordinated simultaneously for "contouring control".
- Notes:
- 1. "Software" is controlled whether exported separately or residing in a "numerical control" unit or any electronic device or system.
 - 2. Item 1.D.3. does not control "software" specially designed or modified by the manufacturers of the control unit or machine tool to operate a machine tool that is not specified in Item 1.B.2.
- 1.E. TECHNOLOGY
- 1.E.1. "Technology" according to the Technology Controls for the "development", "production" or "use" of equipment, material or "software" specified in 1.A. through 1.D.

2. MATERIALS

- 2.A. EQUIPMENT, ASSEMBLIES AND COMPONENTS
- 2.A.1. Crucibles made of materials resistant to liquid actinide metals, as follows:
- a. Crucibles having both of the following characteristics:
 1. A volume of between 150 cm³ (150 ml) and 8000 cm³ (8 liters); and
 2. Made of or coated with any of the following materials, having a purity of 98% or greater by weight:
 - a. Calcium fluoride (CaF₂);
 - b. Calcium zirconate (metazirconate) (CaZrO₃);
 - c. Cerium sulfide (Ce₂S₃);
 - d. Erbium oxide (erbia) (Er₂O₃);
 - e. Hafnium oxide (hafnia) (HfO₂);
 - f. Magnesium oxide (MgO);
 - g. Nitrided niobium-titanium-tungsten alloy (approximately 50% Nb, 30% Ti, 20% W);
 - h. Yttrium oxide (yttria) (Y₂O₃); or
 - i. Zirconium oxide (zirconia) (ZrO₂);
 - b. Crucibles having both of the following characteristics:
 1. A volume of between 50 cm³ (50 ml) and 2000 cm³ (2 liters); and
 2. Made of or lined with tantalum, having a purity of 99.9% or greater by weight;
 - c. Crucibles having all of the following characteristics:
 1. A volume of between 50 cm³ (50 ml) and 2000 cm³ (2 liters);
 2. Made of or lined with tantalum, having a purity of 98% or greater by weight; and
 3. Coated with tantalum carbide, nitride, boride, or any combination thereof.
- 2.A.2. Platinized catalysts specially designed or prepared for promoting the hydrogen isotope exchange reaction between hydrogen and water for the recovery of tritium from heavy water or for the production of heavy water.

- 2.A.3. Composite structures in the form of tubes having both of the following characteristics:
- a. An inside diameter of between 75 and 400 mm; and
 - b. Made with any of the "fibrous or filamentary materials" specified in Item 2.C.7.a. or carbon prepreg materials specified in Item 2.C.7.c.
- 2.B. TEST AND PRODUCTION EQUIPMENT
- 2.B.1. Tritium facilities or plants, and equipment therefor, as follows:
- a. Facilities or plants for the production, recovery, extraction, concentration or handling of tritium;
 - b. Equipment for tritium facilities or plants, as follows:
 1. Hydrogen or helium refrigeration units capable of cooling to 23 K (-250 °C) or less, with heat removal capacity greater than 150 W;
 2. Hydrogen isotope storage or purification systems using metal hydrides as the storage or purification medium.
- 2.B.2. Lithium isotope separation facilities or plants, and equipment therefor, as follows:
- a. Facilities or plants for the separation of lithium isotopes;
 - b. Equipment for the separation of lithium isotopes, as follows:
 1. Packed liquid-liquid exchange columns specially designed for lithium amalgams;
 2. Mercury or lithium amalgam pumps;
 3. Lithium amalgam electrolysis cells;
 4. Evaporators for concentrated lithium hydroxide solution.
- 2.C. MATERIALS
- 2.C.1. Aluminium alloys having both of the following characteristics:
- a. 'Capable of an ultimate tensile strength of 460 MPa or more at 293 K (20 °C); and
 - b. In the form of tubes or cylindrical solid forms (including forgings) with an outside diameter of more than 75 mm.

Technical Note: In Item 2.C.1. the phrase 'capable of' encompasses aluminium alloys before or after heat treatment.

2.C.2. Beryllium metal, alloys containing more than 50% beryllium by weight, beryllium compounds, manufactures thereof, and waste or scrap of any of the foregoing.

Note: Item 2.C.2. does not control the following:

- a. Metal windows for X-ray machines or for bore-hole logging devices;
- b. Oxide shapes in fabricated or semi-fabricated forms specially designed for electronic component parts or as substrates for electronic circuits;
- c. Beryl (silicate of beryllium and aluminium) in the form of emeralds or aquamarines.

2.C.3. Bismuth having both of the following characteristics:

- a. A purity of 99.99% or greater by weight; and
- b. Containing less than 10 parts per million by weight of silver.

2.C.4. Boron enriched in the boron-10 (^{10}B) isotope to greater than its natural isotopic abundance, as follows: elemental boron, compounds, mixtures containing boron, manufactures thereof, waste or scrap of any of the foregoing.

Note: In Item 2.C.4. mixtures containing boron include boron loaded materials.

Technical Note: *The natural isotopic abundance of boron-10 is approximately 18.5 weight percent (20 atom percent).*

2.C.5. Calcium having both of the following characteristics:

- a. Containing less than 1000 parts per million by weight of metallic impurities other than magnesium; and
- b. Containing less than 10 parts per million by weight of boron.

2.C.6. Chlorine trifluoride (ClF_3).

2.C.7. "Fibrous or filamentary materials", and preregs, as follows:

a. Carbon or aramid "fibrous or filamentary materials" having either of the following characteristics:

1. A 'specific modulus' of 12.7×10^6 m or greater; or
2. A 'specific tensile strength' of 23.5×10^4 m or greater;

Note: Item 2.C.7.a. does not control aramid "fibrous or filamentary materials" having 0.25% or more by weight of an ester based fiber surface modifier.

b. Glass "fibrous or filamentary materials" having both of the following characteristics:

1. A 'specific modulus' of 3.18×10^6 m or greater; and

2. A 'specific tensile strength' of 7.62×10^4 m or greater;
- c. Thermoset resin impregnated continuous "yarns", "rovings", "tows" or "tapes" with a width of 15 mm or less (prepregs), made from carbon or glass "fibrous or filamentary materials" specified in Item 2.C.7.a. or Item 2.C.7.b.

Technical Note: *The resin forms the matrix of the composite.*

- Technical Notes:
1. *In Item 2.C.7. 'Specific modulus' is the Young's modulus in N/m^2 divided by the specific weight in N/m^3 when measured at a temperature of 296 ± 2 K (23 ± 2 °C) and a relative humidity of $50 \pm 5\%$.*
 2. *In Item 2.C.7. 'Specific tensile strength' is the ultimate tensile strength in N/m^2 divided by the specific weight in N/m^3 when measured at a temperature of 296 ± 2 K (23 ± 2 °C) and a relative humidity of $50 \pm 5\%$.*

- 2.C.8. Hafnium metal, alloys containing more than 60% hafnium by weight, hafnium compounds containing more than 60% hafnium by weight, manufactures thereof, and waste or scrap of any of the foregoing.
- 2.C.9. Lithium enriched in the lithium-6 (^6Li) isotope to greater than its natural isotopic abundance and products or devices containing enriched lithium, as follows: elemental lithium, alloys, compounds, mixtures containing lithium, manufactures thereof, waste or scrap of any of the foregoing.

Note: Item 2.C.9. does not control thermoluminescent dosimeters.

Technical Note: *The natural isotopic abundance of lithium-6 is approximately 6.5 weight percent (7.5 atom percent).*

- 2.C.10. Magnesium having both of the following characteristics:
- a. Containing less than 200 parts per million by weight of metallic impurities other than calcium; and
 - b. Containing less than 10 parts per million by weight of boron.
- 2.C.11. Maraging steel 'capable of' an ultimate tensile strength of 2050 MPa or more at 293 K (20 °C).

Note: Item 2.C.11. does not control forms in which all linear dimensions are 75 mm or less.

Technical Note: *In Item 2.C.11. the phrase 'capable of' encompasses maraging steel before or after heat treatment.*

- 2.C.12. Radium-226 (^{226}Ra), radium-226 alloys, radium-226 compounds, mixtures containing radium-226, manufactures thereof, and products or devices containing any of the foregoing.

Note: Item 2.C.12. does not control the following:

- a. Medical applicators;
- b. A product or device containing less than 0.37 GBq of radium-226.

2.C.13. Titanium alloys having both of the following characteristics:

- a. 'Capable of' an ultimate tensile strength of 900 MPa or more at 293 K (20 °C); and
- b. In the form of tubes or cylindrical solid forms (including forgings) with an outside diameter of more than 75 mm.

Technical Note: In Item 2.C.13. the phrase 'capable of' encompasses titanium alloys before or after heat treatment.

2.C.14. Tungsten, tungsten carbide, and alloys containing more than 90% tungsten by weight, having both of the following characteristics:

- a. In forms with a hollow cylindrical symmetry (including cylinder segments) with an inside diameter between 100 and 300 mm; and
- b. A mass greater than 20 kg.

Note: Item 2.C.14. does not control manufactures specially designed as weights or gamma-ray collimators.

2.C.15. Zirconium with a hafnium content of less than 1 part hafnium to 500 parts zirconium by weight, as follows: metal, alloys containing more than 50% zirconium by weight, compounds, manufactures thereof, waste or scrap of any of the foregoing.

Note: Item 2.C.15. does not control zirconium in the form of foil having a thickness of 0.10 mm or less.

2.C.16. Nickel powder and porous nickel metal, as follows:

N.B.: For nickel powders which are especially prepared for the manufacture of gaseous diffusion barriers see INFCIRC/254/Part 1 (as amended).

- a. Nickel powder having both of the following characteristics:
 1. A nickel purity content of 99.0% or greater by weight; and
 2. A mean particle size of less than 10 µm measured by the ASTM B 330 standard;
- b. Porous nickel metal produced from materials specified in Item 2.C.16.a.

Note: Item 2.C.16. does not control the following:

- a. Filamentary nickel powders;
- b. Single porous nickel metal sheets with an area of 1000 cm² per sheet or less.

Technical Note: Item 2.C.16.b. refers to porous metal formed by compacting and sintering the material in Item 2.C.16.a. to form a metal material with fine pores interconnected throughout the structure.

- 2.C.17. Tritium, tritium compounds, mixtures containing tritium in which the ratio of tritium to hydrogen atoms exceeds 1 part in 1000, and products or devices containing any of the foregoing.

Note: Item 2.C.17. does not control a product or device containing less than 1.48×10^3 GBq of tritium.

- 2.C.18. Helium-3 (^3He), mixtures containing helium-3, and products or devices containing any of the foregoing.

Note: Item 2.C.18. does not control a product or device containing less than 1 g of helium-3.

- 2.C.19. Alpha-emitting radionuclides having an alpha half-life of 10 days or greater but less than 200 years, in the following forms:

- a. Elemental;
- b. Compounds having a total alpha activity of 37 GBq per kg or greater;
- c. Mixtures having a total alpha activity of 37 GBq per kg or greater;
- d. Products or devices containing any of the foregoing.

Note: Item 2.C.19. does not control a product or device containing less than 3.7 GBq of alpha activity.

2.D. SOFTWARE

None

2.E. TECHNOLOGY

- 2.E.1. "Technology" according to the Technology Controls for the "development", "production" or "use" of equipment, material or "software" specified in 2.A. through 2.D.

3. URANIUM ISOTOPE SEPARATION EQUIPMENT AND COMPONENTS
(Other Than Trigger List Items)

3.A. EQUIPMENT, ASSEMBLIES AND COMPONENTS

3.A.1. Frequency changers or generators having all of the following characteristics:

N.B.: Frequency changers and generators especially designed or prepared for the gas centrifuge process are controlled under INFCIRC/254/Part 1 (as amended).

- a. Multiphase output capable of providing a power of 40 W or greater;
- b. Capable of operating in the frequency range between 600 and 2000 Hz;
- c. Total harmonic distortion better (less) than 10%; and
- d. Frequency control better (less) than 0.1%.

Technical Note: *Frequency changers in Item 3.A.1. are also known as converters or inverters.*

3.A.2. Lasers, laser amplifiers and oscillators as follows:

- a. Copper vapor lasers having both of the following characteristics:
 1. Operating at wavelengths between 500 and 600 nm; and
 2. An average output power equal to or greater than 40 W;
- b. Argon ion lasers having both of the following characteristics:
 1. Operating at wavelengths between 400 and 515 nm; and
 2. An average output power greater than 40 W;
- c. Neodymium-doped (other than glass) lasers with an output wavelength between 1000 and 1100 nm having either of the following:
 1. Pulse-excited and Q-switched with a pulse duration equal to or greater than 1 ns, and having either of the following:
 - a. A single-transverse mode output with an average output power greater than 40 W; or
 - b. A multiple-transverse mode output with an average output power greater than 50 W;

or
 2. Incorporating frequency doubling to give an output wavelength between 500 and 550 nm with an average output power of greater than 40 W;

- d. Tunable pulsed single-mode dye laser oscillators having all of the following characteristics:
 1. Operating at wavelengths between 300 and 800 nm;
 2. An average output power greater than 1 W;
 3. A repetition rate greater than 1 kHz; and
 4. Pulse width less than 100 ns;
- e. Tunable pulsed dye laser amplifiers and oscillators having all of the following characteristics:
 1. Operating at wavelengths between 300 and 800 nm;
 2. An average output power greater than 30 W;
 3. A repetition rate greater than 1 kHz; and
 4. Pulse width less than 100 ns;
- Note: Item 3.A.2.e. does not control single mode oscillators.
- f. Alexandrite lasers having all of the following characteristics:
 1. Operating at wavelengths between 720 and 800 nm;
 2. A bandwidth of 0.005 nm or less;
 3. A repetition rate greater than 125 Hz; and
 4. An average output power greater than 30 W;
- g. Pulsed carbon dioxide lasers having all of the following characteristics:
 1. Operating at wavelengths between 9000 and 11000 nm;
 2. A repetition rate greater than 250 Hz;
 3. An average output power greater than 500 W; and
 4. Pulse width of less than 200 ns;

Note: Item 3.A.2.g. does not control the higher power (typically 1 to 5 kW) industrial CO₂ lasers used in applications such as cutting and welding, as these latter lasers are either continuous wave or are pulsed with a pulse width greater than 200 ns.

- h. Pulsed excimer lasers (XeF, XeCl, KrF) having all of the following characteristics:
 - 1. Operating at wavelengths between 240 and 360 nm;
 - 2. A repetition rate greater than 250 Hz; and
 - 3. An average output power greater than 500 W;
- i. Para-hydrogen Raman shifters designed to operate at 16 μm output wavelength and at a repetition rate greater than 250 Hz.

3.A.3. Valves having all of the following characteristics:

- a. A nominal size of 5 mm or greater;
- b. Having a bellows seal; and
- c. Wholly made of or lined with aluminium, aluminium alloy, nickel, or nickel alloy containing more than 60% nickel by weight.

Technical Note: For valves with different inlet and outlet diameter, the nominal size parameter in Item 3.A.3.a. refers to the smallest diameter.

3.A.4. Superconducting solenoidal electromagnets having all of the following characteristics:

- a. Capable of creating magnetic fields greater than 2 T;
- b. A ratio of length to inner diameter greater than 2;
- c. Inner diameter greater than 300 mm; and
- d. Magnetic field uniform to better than 1% over the central 50% of the inner volume.

Note: Item 3.A.4. does not control magnets specially designed for and exported as part of medical nuclear magnetic resonance (NMR) imaging systems.

N.B.: As part of, does not necessarily mean physical part in the same shipment. Separate shipments from different sources are allowed, provided the related export documents clearly specify the as part of relationship.

3.A.5. High-power direct current power supplies having both of the following characteristics:

- a. Capable of continuously producing, over a time period of 8 hours, 100 V or greater with current output of 500 A or greater; and
- b. Current or voltage stability better than 0.1% over a time period of 8 hours.

3.A.6. High-voltage direct current power supplies having both of the following characteristics:

- a. Capable of continuously producing, over a time period of 8 hours, 20 kV or greater with current output of 1 A or greater; and

- b. Current or voltage stability better than 0.1% over a time period of 8 hours.
- 3.A.7. Pressure transducers capable of measuring absolute pressures at any point in the range 0 to 13 kPa and having both of the following characteristics:
- a. Pressure sensing elements made of or protected by aluminium, aluminium alloy, nickel, or nickel alloy with more than 60% nickel by weight; and
 - b. Having either of the following characteristics:
 - 1. A full scale of less than 13 kPa and an “accuracy” of better than $\pm 1\%$ of full scale; or
 - 2. A full scale of 13 kPa or greater and an “accuracy” of better than ± 130 Pa.

Technical Notes:

1. In Item 3.A.7. pressure transducers are devices that convert pressure measurements into an electrical signal.
2. In Item 3.A.7. “accuracy” includes non-linearity, hysteresis and repeatability at ambient temperature.

- 3.A.8. Vacuum pumps having all of the following characteristics:
- a. Input throat size equal to or greater than 380 mm;
 - b. Pumping speed equal to or greater than $15 \text{ m}^3/\text{s}$; and
 - c. Capable of producing an ultimate vacuum better than 13.3 mPa.

Technical Notes:

1. The pumping speed is determined at the measurement point with nitrogen gas or air.
2. The ultimate vacuum is determined at the input of the pump with the input of the pump blocked off.

3.B. TEST AND PRODUCTION EQUIPMENT

- 3.B.1. Electrolytic cells for fluorine production with an output capacity greater than 250 g of fluorine per hour.
- 3.B.2. Rotor fabrication or assembly equipment, rotor straightening equipment, bellows-forming mandrels and dies, as follows:
- a. Rotor assembly equipment for assembly of gas centrifuge rotor tube sections, baffles, and end caps;

Note: Item 3.B.2.a. includes precision mandrels, clamps, and shrink fit machines.

- b. Rotor straightening equipment for alignment of gas centrifuge rotor tube sections to a common axis;

Technical Note: In Item 3.B.2.b. such equipment normally consists of precision measuring probes linked to a computer that subsequently controls the action of, for example, pneumatic rams used for aligning the rotor tube sections.

- c. Bellows-forming mandrels and dies for producing single-convolution bellows.

Technical Note: The bellows referred to in Item 3.B.2.c. have all of the following characteristics:

1. Inside diameter between 75 and 400 mm;
2. Length equal to or greater than 12.7 mm;
3. Single convolution depth greater than 2 mm; and
4. Made of high-strength aluminium alloys, maraging steel, or high strength "fibrous or filamentary materials".

3.B.3. Centrifugal multiplane balancing machines, fixed or portable, horizontal or vertical, as follows:

- a. Centrifugal balancing machines designed for balancing flexible rotors having a length of 600 mm or more and having all of the following characteristics:
 1. Swing or journal diameter greater than 75 mm;
 2. Mass capability of from 0.9 to 23 kg; and
 3. Capable of balancing speed of revolution greater than 5000 rpm;
- b. Centrifugal balancing machines designed for balancing hollow cylindrical rotor components and having all of the following characteristics:
 1. Journal diameter greater than 75 mm;
 2. Mass capability of from 0.9 to 23 kg;
 3. Capable of balancing to a residual imbalance equal to or less than 0.010 kg x mm/kg per plane; and
 4. Belt drive type.

3.B.4. Filament winding machines and related equipment, as follows:

- a. Filament winding machines having all of the following characteristics:
 1. Having motions for positioning, wrapping, and winding fibers coordinated and programmed in two or more axes;

2. Specially designed to fabricate composite structures or laminates from "fibrous or filamentary materials"; and
 3. Capable of winding cylindrical rotors of diameter between 75 and 400 mm and lengths of 600 mm or greater;
- b. Coordinating and programming controls for the filament winding machines specified in Item 3.B.4.a.;
 - c. Precision mandrels for the filament winding machines specified in Item 3.B.4.a.
- 3.B.5. Electromagnetic isotope separators designed for, or equipped with, single or multiple ion sources capable of providing a total ion beam current of 50 mA or greater.

Notes: 1. Item 3.B.5. includes separators capable of enriching stable isotopes as well as those for uranium.

N.B.: A separator capable of separating the isotopes of lead with a one-mass unit difference is inherently capable of enriching the isotopes of uranium with a three-unit mass difference.

2. Item 3.B.5. includes separators with the ion sources and collectors both in the magnetic field and those configurations in which they are external to the field.

Technical Note: *A single 50 mA ion source cannot produce more than 3 g of separated highly enriched uranium (HEU) per year from natural abundance feed.*

- 3.B.6. Mass spectrometers capable of measuring ions of 230 atomic mass units or greater and having a resolution of better than 2 parts in 230, as follows, and ion sources therefor:

N.B.: Mass spectrometers especially designed or prepared for analyzing on-line samples of uranium hexafluoride are controlled under INFCIRC/254/Part 1 (as amended).

- a. Inductively coupled plasma mass spectrometers (ICP/MS);
- b. Glow discharge mass spectrometers (GDMS);
- c. Thermal ionization mass spectrometers (TIMS);
- d. Electron bombardment mass spectrometers which have a source chamber constructed from, lined with or plated with materials resistant to UF_6 ;
- e. Molecular beam mass spectrometers having either of the following characteristics:
 1. A source chamber constructed from, lined with or plated with stainless steel or molybdenum, and equipped with a cold trap capable of cooling to 193 K (-80 °C) or less;
or
 2. A source chamber constructed from, lined with or plated with materials resistant to UF_6 ;

- f. Mass spectrometers equipped with a microfluorination ion source designed for actinides or actinide fluorides.

3.C. MATERIALS

None.

3.D. SOFTWARE

- 3.D.1. "Software" specially designed for the "use" of equipment specified in Item 3.B.3. or 3.B.4.

3.E. TECHNOLOGY

- 3.E.1. "Technology" according to the Technology Controls for the "development", "production" or "use" of equipment, material or "software" specified in 3.A. through 3.D.

4. HEAVY WATER PRODUCTION PLANT RELATED EQUIPMENT
(Other Than Trigger List Items)

4.A. EQUIPMENT, ASSEMBLIES AND COMPONENTS

4.A.1. Specialized packings which may be used in separating heavy water from ordinary water, having both of the following characteristics:

- a. Made of phosphor bronze mesh chemically treated to improve wettability; and
- b. Designed to be used in vacuum distillation towers.

4.A.2. Pumps capable of circulating solutions of concentrated or dilute potassium amide catalyst in liquid ammonia (KNH_2/NH_3), having all of the following characteristics:

- a. Airtight (i.e., hermetically sealed);
- b. A capacity greater than $8.5 \text{ m}^3/\text{h}$; and
- c. Either of the following characteristics:
 1. For concentrated potassium amide solutions (1% or greater), an operating pressure of 1.5 to 60 MPa; or
 2. For dilute potassium amide solutions (less than 1%), an operating pressure of 20 to 60 MPa.

4.A.3. Turboexpanders or turboexpander-compressor sets having both of the following characteristics:

- a. Designed for operation with an outlet temperature of 35 K (-238 °C) or less; and
- b. Designed for a throughput of hydrogen gas of 1000 kg/h or greater.

4.B. TEST AND PRODUCTION EQUIPMENT

4.B.1. Water-hydrogen sulfide exchange tray columns and internal contactors, as follows:

N.B.: For columns which are especially designed or prepared for the production of heavy water, see INFCIRC/254/Part 1 (as amended).

- a. Water-hydrogen sulfide exchange tray columns, having all of the following characteristics:
 1. Can operate at pressures of 2 MPa or greater;
 2. Constructed of carbon steel having an austenitic ASTM (or equivalent standard) grain size number of 5 or greater; and
 3. With a diameter of 1.8 m or greater;

- b. Internal contactors for the water-hydrogen sulfide exchange tray columns specified in Item 4.B.1.a.

Technical Note: Internal contactors of the columns are segmented trays which have an effective assembled diameter of 1.8 m or greater; are designed to facilitate countercurrent contacting and are constructed of stainless steels with a carbon content of 0.03% or less. These may be sieve trays, valve trays, bubble cap trays or turbogrid trays.

- 4.B.2. Hydrogen-cryogenic distillation columns having all of the following characteristics:
 - a. Designed for operation at internal temperatures of 35 K (-238 °C) or less;
 - b. Designed for operation at internal pressures of 0.5 to 5 MPa;
 - c. Constructed of either:
 - 1. Stainless steel of the 300 series with low sulfur content and with an austenitic ASTM (or equivalent standard) grain size number of 5 or greater; or
 - 2. Equivalent materials which are both cryogenic and H₂-compatible; and
 - d. With internal diameters of 1 m or greater and effective lengths of 5 m or greater.
- 4.B.3. Ammonia synthesis converters or synthesis units, in which the synthesis gas (nitrogen and hydrogen) is withdrawn from an ammonia/hydrogen high-pressure exchange column and the synthesized ammonia is returned to said column.
- 4.C. MATERIALS
None.
- 4.D. SOFTWARE
None.
- 4.E. TECHNOLOGY
- 4.E.1. "Technology" according to the Technology Controls for the "development", "production" or "use" of equipment, material or "software" specified in 4.A. through 4.D.

5. TEST AND MEASUREMENT EQUIPMENT FOR THE DEVELOPMENT OF NUCLEAR
EXPLOSIVE DEVICES

5.A. EQUIPMENT, ASSEMBLIES AND COMPONENTS

5.A.1. Photomultiplier tubes having both of the following characteristics:

- a. Photocathode area of greater than 20 cm²; and
- b. Anode pulse rise time of less than 1 ns.

5.B. TEST AND PRODUCTION EQUIPMENT

5.B.1. Flash X-ray generators or pulsed electron accelerators having either of the following sets of characteristics:

- a. 1. An accelerator peak electron energy of 500 keV or greater but less than 25 MeV; and
2. With a figure of merit (K) of 0.25 or greater; or
- b. 1. An accelerator peak electron energy of 25 MeV or greater; and
2. A peak power greater than 50 MW.

Note: Item 5.B.1. does not control accelerators that are component parts of devices designed for purposes other than electron beam or X-ray radiation (electron microscopy, for example) nor those designed for medical purposes.

- Technical Notes:
1. The figure of merit K is defined as: $K=1.7 \times 10^3 V^{2.65}Q$. V is the peak electron energy in million electron volts. If the accelerator beam pulse duration is less than or equal to 1 μ s, then Q is the total accelerated charge in Coulombs. If the accelerator beam pulse duration is greater than 1 μ s, then Q is the maximum accelerated charge in 1 μ s. Q equals the integral of i with respect to t , over the lesser of 1 μ s or the time duration of the beam pulse ($Q = \int idt$) where i is beam current in amperes and t is the time in seconds.
 2. Peak power = (peak potential in volts) x (peak beam current in amperes).
 3. In machines based on microwave accelerating cavities, the time duration of the beam pulse is the lesser of 1 μ s or the duration of the bunched beam packet resulting from one microwave modulator pulse.
 4. In machines based on microwave accelerating cavities, the peak beam current is the average current in the time duration of a bunched beam packet.

5.B.2. Multistage light gas guns or other high-velocity gun systems (coil, electromagnetic, and electrothermal types, and other advanced systems) capable of accelerating projectiles to 2 km/s or greater.

5.B.3. Mechanical rotating mirror cameras, as follows, and specially designed components therefor:

- a. Framing cameras with recording rates greater than 225000 frames per second;
- b. Streak cameras with writing speeds greater than 0.5 mm/ μ s.

Note: In Item 5.B.3. components of such cameras include their synchronizing electronics units and rotor assemblies consisting of turbines, mirrors, and bearings.

5.B.4. Electronic streak cameras, electronic framing cameras, tubes and devices, as follows:

- a. Electronic streak cameras capable of 50 ns or less time resolution;
- b. Streak tubes for cameras specified in Item 5.B.4.a.;
- c. Electronic (or electronically shuttered) framing cameras capable of 50 ns or less frame exposure time;
- d. Framing tubes and solid-state imaging devices for use with cameras specified in Item 5.B.4.c., as follows:
 1. Proximity focused image intensifier tubes having the photocathode deposited on a transparent conductive coating to decrease photocathode sheet resistance;
 2. Gate silicon intensifier target (SIT) vidicon tubes, where a fast system allows gating the photoelectrons from the photocathode before they impinge on the SIT plate;
 3. Kerr or Pockels cell electro-optical shuttering;
 4. Other framing tubes and solid-state imaging devices having a fast image gating time of less than 50 ns specially designed for cameras specified in Item 5.B.4.c.

5.B.5. Specialized instrumentation for hydrodynamic experiments, as follows:

- a. Velocity interferometers for measuring velocities exceeding 1 km/s during time intervals of less than 10 μ s;
- b. Manganin gauges for pressures greater than 10 GPa;
- c. Quartz pressure transducers for pressures greater than 10 GPa.

Note: Item 5.B.5.a. includes velocity interferometers such as VISARs (Velocity interferometer systems for any reflector) and DLIs (Doppler laser interferometers).

- 5.B.6. High-speed pulse generators having both of the following characteristics:
- a. Output voltage greater than 6 V into a resistive load of less than 55 ohms; and
 - b. 'Pulse transition time' less than 500 ps.

Technical Note: In Item 5.B.6.b. 'pulse transition time' is defined as the time interval between 10% and 90% voltage amplitude.

5.C. MATERIALS

None.

5.D. SOFTWARE

None.

5.E. TECHNOLOGY

- 5.E.1. "Technology" according to the Technology Controls for the "development", "production" or "use" of equipment, material or "software" specified in 5.A. through 5.D.

6. COMPONENTS FOR NUCLEAR EXPLOSIVE DEVICES

6.A. EQUIPMENT, ASSEMBLIES AND COMPONENTS

6.A.1. Detonators and multipoint initiation systems, as follows:

a. Electrically driven explosive detonators, as follows:

1. Exploding bridge (EB);
2. Exploding bridge wire (EBW);
3. Slapper;
4. Exploding foil initiators (EFI);

b. Arrangements using single or multiple detonators designed to nearly simultaneously initiate an explosive surface over an area greater than 5000 mm² from a single firing signal with an initiation timing spread over the surface of less than 2.5 μs.

Note: Item 6.A.1. does not control detonators using only primary explosives, such as lead azide.

Technical Note: *In Item 6.A.1. the detonators of concern all utilize a small electrical conductor (bridge, bridge wire, or foil) that explosively vaporizes when a fast, high-current electrical pulse is passed through it. In nonslapper types, the exploding conductor starts a chemical detonation in a contacting high-explosive material such as PETN (pentaerythritoltetranitrate). In slapper detonators, the explosive vaporization of the electrical conductor drives a flyer or slapper across a gap, and the impact of the slapper on an explosive starts a chemical detonation. The slapper in some designs is driven by magnetic force. The term exploding foil detonator may refer to either an EB or a slapper-type detonator. Also, the word initiator is sometimes used in place of the word detonator.*

6.A.2. Firing sets and equivalent high-current pulse generators, as follows:

- a. Explosive detonator firing sets designed to drive multiple controlled detonators specified by Item 6.A.1. above;
- b. Modular electrical pulse generators (pulsers) having all of the following characteristics:
 1. Designed for portable, mobile, or ruggedized-use;
 2. Enclosed in a dust-tight enclosure;
 3. Capable of delivering their energy in less than 15 μs;
 4. Having an output greater than 100 A;
 5. Having a 'rise time' of less than 10 μs into loads of less than 40 ohms;

6. No dimension greater than 25.4 cm;
7. Weight less than 25 kg ; and
8. Specified to operate over an extended temperature range of 223 to 373 K (-50 °C to 100 °C) or specified as suitable for aerospace applications.

Note: Item 6.A.2.b. includes xenon flashlamp drivers.

Technical Note: In Item 6.A.2.b.5. 'rise time' is defined as the time interval from 10% to 90% current amplitude when driving a resistive load.

6.A.3. Switching devices as follows:

- a. Cold-cathode tubes, whether gas filled or not, operating similarly to a spark gap, having all of the following characteristics:

1. Containing three or more electrodes;
2. Anode peak voltage rating of 2.5 kV or more;
3. Anode peak current rating of 100 A or more; and
4. Anode delay time of 10 μ s or less;

Note: Item 6.A.3.a. includes gas krytron tubes and vacuum sprytron tubes.

- b. Triggered spark-gaps having both of the following characteristics:

1. Anode delay time of 15 μ s or less; and
2. Rated for a peak current of 500 A or more;

- c. Modules or assemblies with a fast switching function having all of the following characteristics:

1. Anode peak voltage rating greater than 2 kV;
2. Anode peak current rating of 500 A or more; and
3. Turn-on time of 1 μ s or less.

6.A.4. Pulse discharge capacitors having either of the following sets of characteristics:

- a.
 1. Voltage rating greater than 1.4 kV;
 2. Energy storage greater than 10 J;
 3. Capacitance greater than 0.5 μ F; and
 4. Series inductance less than 50 nH; or

- b. 1. Voltage rating greater than 750 V;
2. Capacitance greater than 0.25 μF ; and
3. Series inductance less than 10 nH.

6.A.5. Neutron generator systems, including tubes, having both of the following characteristics:

- a. Designed for operation without an external vacuum system; and
- b. Utilizing electrostatic acceleration to induce a tritium-deuterium nuclear reaction.

6.B. TEST AND PRODUCTION EQUIPMENT

None.

6.C. MATERIALS

6.C.1. High explosive substances or mixtures, containing more than 2 % by weight of any of the following:

- a. Cyclotetramethylenetetranitramine (HMX) (CAS 2691-41-0);
- b. Cyclotrimethylenetrinitramine (RDX) (CAS 121-82-4);
- c. Triaminotrinitrobenzene (TATB) (CAS 3058-38-6);
- d. Hexanitrostilbene (HNS) (CAS 20062-22-0); or
- e. Any explosive with a crystal density greater than 1.8 g/cm^3 and having a detonation velocity greater than 8000 m/s.

6.D. SOFTWARE

None.

6.E. TECHNOLOGY

6.E.1. "Technology" according to the Technology Controls for the "development", "production" or "use" of equipment, material or "software" specified in 6.A. through 6.D.

COMPARISON TABLE OF CHANGES TO THE GUIDELINES FOR NUCLEAR TRANSFERS (INFCIRC/254/Rev. 6/Part 2)

Old	New
<p>ESTABLISHMENT OF EXPORT LICENSING PROCEDURES</p>	<p>ESTABLISHMENT OF EXPORT LICENSING PROCEDURES</p> <p>4. <u>(1) Whether there is a risk of retransfers of equipment, material, software, or related technology identified in the Annex or of transfers of any replica thereof contrary to the Basic Principle, as a result of a failure by the recipient State to develop and maintain appropriate, effective national export and transshipment controls, as identified by UNSC Resolution 1540.</u></p>
<p>1.B.2. Machine tools, as follows, for removing or cutting metals, ceramics, or composites, which, according to the manufacturer's technical specifications, can be equipped with electronic devices for simultaneous "contouring control" in two or more axes:</p> <p><u>N.B.:</u> For "numerical control" units ...</p> <p>a. Machine tools for turning, ...</p> <p><u>Note:</u> Item 1.B.2.a. does not control bar machines ...</p> <p>b. Machine tools for milling, ...</p> <p>1. "Positioning accuracies" with all ...</p> <p>2. Two or more contouring rotary axes;</p> <p><u>Note:</u> Item 1.B.2.b. does not control ... characteristics:</p> <p>1. X-axis travel greater than 2 m; <u>and</u></p> <p>2. Overall "positioning accuracy" on ...</p>	<p>1.B.2. Machine tools, as follows, <u>and any combination thereof</u>, for removing or cutting metals, ceramics, or composites, which, according to the manufacturer's technical specifications, can be equipped with electronic devices for simultaneous "contouring control" in two or more axes:</p> <p><u>N.B.:</u> For "numerical control" units ...</p> <p>a. Machine tools for turning, ...</p> <p><u>Note:</u> Item 1.B.2.a. does not control bar machines ...</p> <p>b. Machine tools for milling, ...</p> <p>1. "Positioning accuracies" with all ...</p> <p>2. Two or more contouring rotary axes;</p> <p>3. <u>Five or more axes which can be coordinated simultaneously for "contouring control."</u></p> <p><u>Note:</u> Item 1.B.2.b. does not control ... characteristics:</p> <p>1. X-axis travel greater than 2 m; <u>and</u></p> <p>2. Overall "positioning accuracy" on ...</p>

COMPARISON TABLE OF CHANGES TO THE GUIDELINES FOR NUCLEAR TRANSFERS (INFCIRC/254/Rev. 6/Part 2)

Old	New
<p>c. Machine tools for grinding, having any of the following characteristics:</p> <ol style="list-style-type: none"> 1. "Positioning accuracies" with ... 2. Two or more contouring rotary axes; <p><u>Note:</u> Item 1.B.2.c. does not control grinding machines as follows:</p> <ol style="list-style-type: none"> 1. Cylindrical external, internal, and external-internal grinding machines having all the following characteristics: <ol style="list-style-type: none"> a. Limited to cylindrical grinding; b. A maximum workpiece outside diameter or length of 150 mm; c. Not more than two axes that can be coordinated simultaneously for "contouring control", <u>and</u> d. No contouring c-axis; 2. Jig grinders with axes limited to x,y,c, and a, where c-axis is used to maintain the grinding wheel 	<p>c. Machine tools for grinding, having any of the following characteristics:</p> <ol style="list-style-type: none"> 1. "Positioning accuracies" with ... 2. Two or more contouring rotary axes; or 3. <u>Five or more axes which can be coordinated simultaneously for "contouring control."</u> <p><u>Note:</u> Item 1.B.2.c. does not control grinding machines as follows:</p> <ol style="list-style-type: none"> 1. Cylindrical external, internal, and external-internal grinding machines having all the following characteristics: <ol style="list-style-type: none"> a. Limited to cylindrical grinding; b. A maximum workpiece outside diameter or length of 150 mm; Limited to a maximum workpiece capacity of 150 mm outside diameter or length; and c. Not more than two axes that can be coordinated simultaneously for "contouring control", and <u>axes limited to x, z and c.</u> d. No contouring e-axis;

COMPARISON TABLE OF CHANGES TO THE GUIDELINES FOR NUCLEAR TRANSFERS (INFCIRC/254/Rev. 6/Part 2)

Old	New
<p>normal to the work surface, and the a-axis is configured to grind barrel cams;</p> <p>3. Tool or cutter grinding machines with "software" specially designed for the manufacturing of tools or cutters;</p> <p>4. Crankshaft or camshaft grinding machines.</p> <p>d. Non-wire type Electrical Discharge Machines (EDM)...</p> <p><u>Note:</u> Stated "positioning accuracy" levels derived under the following procedures from measurements made according to ISO 230/2 (1988) or national equivalents may be used for each machine tool model if provided to, and accepted by, national authorities instead of individual machine tests.</p> <p>Stated "positioning accuracy" are to be derived as follows:</p> <ol style="list-style-type: none"> 1. Select five machines of a model to be evaluated; 2. Measure the linear axis accuracies according to ISO 230/2 (1988); 3. Determine the accuracy values (A) ...; 4. Determine the average accuracy value of each axis. This average value becomes the stated "positioning accuracy" of each axis for the model ($\bar{A}_x, \bar{A}_y, \dots$); 	<p>2. Jig grinders with axes limited to x, y, z, and a, where e-axis is used to maintain the grinding wheel normal to the work surface, and the a-axis is configured to grind barrel cams; Jig grinders that do not have a z-axis or a w-axis with an overall positioning accuracy less (better) than 4 microns. Positioning accuracy is according to ISO 230/2 (1988).</p> <p>3. Tool or cutter grinding machines with "software" specially designed for the manufacturing of tools or cutters;</p> <p>4. Crankshaft or camshaft grinding machines.</p> <p>d. Non-wire type Electrical Discharge Machines (EDM)...</p> <p><u>Notes:</u> 1. Stated "positioning accuracy" levels derived under the following procedures from measurements made according to ISO 230/2 (1988) or national equivalents may be used for each machine tool model if provided to, and accepted by, national authorities instead of individual machine tests.</p> <p>Stated "positioning accuracy" are to be derived as follows:</p> <ol style="list-style-type: none"> 1-a. Select five machines of a model to be evaluated; 1-b. Measure the linear axis accuracies...; 1-c. Determine the accuracy values (A) ...; 1-d. Determine the average accuracy value...;

COMPARISON TABLE OF CHANGES TO THE GUIDELINES FOR NUCLEAR TRANSFERS (INFCIRC/254/Rev. 6/Part 2)

Old	New
<p>5. Since Item 1.B.2. refers to each linear axis, there will be as many stated "positioning accuracy" values as there are linear axes;</p> <p>6. If any axis of a machine tool not controlled by Items 1.B.2.a., 1.B.2.b., or 1.B.2.c. has a stated "positioning accuracy" of 6 µm or better (less) for grinding machines, and 8 µm or better (less) for milling and turning machines, both according to ISO 230/2 (1988), then the builder should be required to reaffirm the accuracy level once every eighteen months.</p> <p><i>Technical Notes:</i></p> <ol style="list-style-type: none"> 1. Axis nomenclature shall be in accordance with International Standard ISO 841... 2. Not counted in the total number of contouring rotary axes are secondary parallel contouring rotary axes the center line of which is parallel to the primary rotary axis. 3. Rotary axes do not ... 	<p>5.e. Since Item 1.B.2. refers to each linear axis, there will be as many stated "positioning accuracy" values as there are linear axes;</p> <p>6.f. If any axis of a machine tool not controlled by Items 1.B.2.a., 1.B.2.b., or 1.B.2.c. has a stated "positioning accuracy" of 6 µm or better (less) for grinding machines, and 8 µm or better (less) for milling and turning machines, both according to ISO 230/2 (1988), then the builder should be required to reaffirm the accuracy level once every eighteen months.</p> <p>2. <u>Item 1.B.2. does not control special purpose machine tools limited to the manufacture of any of the following parts:</u></p> <ol style="list-style-type: none"> a. Gears b. Crankshafts or cam shafts c. Tools or cutters d. Extruder worms <p><i>Technical Notes:</i></p> <ol style="list-style-type: none"> 1. Axis nomenclature shall be in accordance with International Standard ISO 841... 2. Not counted in the total number of contouring rotary axes are secondary parallel contouring rotary axes the center line of which is parallel to the primary rotary axis. <u>(E.g., the w-axis on horizontal boring mills or a secondary rotary axis the centerline of which is parallel to the primary rotary axis).</u> 3. Rotary axes do not ...

COMPARISON TABLE OF CHANGES TO THE GUIDELINES FOR NUCLEAR TRANSFERS (INFCIRC/254/Rev. 6/Part 2)

Old

New

	<p><u>4. For the purposes of 1.B.2, the number of axes which can be coordinated simultaneously for "contouring control" is the number of axes along or around which, during processing of the workpiece, simultaneous and interrelated motions are performed between the workpiece and a tool. This does not include any additional axes along or around which other relative motions within the machine are performed, such as:</u></p> <ul style="list-style-type: none"> <u>a. Wheel-dressing systems in grinding machines;</u> <u>b. Parallel rotary axes designed for mounting of separate workpieces;</u> <u>c. Co-linear rotary axes designed for manipulating the same workpiece by holding it in a chuck from different ends.</u> <p><u>5. A machine tool having at least 2 of the 3 turning, milling or grinding capabilities (e.g. a turning machine with milling capability) must be evaluated against each applicable entry, 1.B.2.a, 1.B.2.b, and 1.B.2.c.</u></p> <p><u>6. Items 1.B.2.b.3 and 1.B.2.c.3 include</u></p>
--	--

COMPARISON TABLE OF CHANGES TO THE GUIDELINES FOR NUCLEAR TRANSFERS (INFCIRC/254/Rev. 6/Part 2)

Old	New
<p>1.B.3. Dimensional inspection machines, instruments, or systems, as follows...</p> <p>b. Linear displacement measuring instruments...</p> <p>3. Measuring systems having both of the following characteristics...</p> <p>c. Angular displacement measuring instruments having an "angular position deviation" equal to or better (less) than 0.00025°;</p> <p><u>Note:</u> Item 1.B.3.c. does not control optical instruments, such as autocollimators, using collimated light to detect angular displacement of a mirror.</p>	<p><i>machines based on a parallel linear kinematic design (e.g. hexapods) that have 5 or more axes none of which are rotary axes.</i></p> <p>1.B.3. Dimensional inspection machines, instruments, or systems, as follows...</p> <p>b. Linear displacement measuring instruments...</p> <p>3. Measuring systems having both of the following characteristics...</p> <p>c. Angular displacement measuring instruments having an "angular position deviation" equal to or better (less) than 0.00025°;</p> <p><u>Note:</u> Item 1.B.3.c. does not control optical instruments, such as autocollimators, using collimated light (e.g., laser light) to detect angular displacement of a mirror.</p>



Security Council

Distr.: General
28 May 2010

Original: English

**Letter dated 27 May 2010 from the Permanent Representative
of the United Kingdom of Great Britain and Northern Ireland
to the United Nations addressed to the President of the
Security Council**

Please find attached a list of items, materials, equipment, goods and technology related to ballistic missile-related programmes (see annex). This list updates the list contained in the annex to document S/2009/205 and may be useful for the Council's discussions on the agenda item of non-proliferation.

I would be grateful if you would make the necessary arrangements for the present letter and its annex to be issued as a document of the Security Council.

(Signed) Mark Lyall Grant



Annex to the letter dated 27 May 2010 from the Permanent Representative of the United Kingdom of Great Britain and Northern Ireland to the United Nations addressed to the President of the Security Council

List of items, materials, equipment, goods and technology related to ballistic missile-related programmes*

* Changes to the list contained in the annex to document S/2009/205 are denoted by bold type in the following sections: 2 (definition of "Production facilities"), 3.A.1 (deletion), 3.A.2, 3.B.3.b, 4.C.2.b.14, 4.C.2.b.17, 4.C.2.f, 4.C.4.a.6, 4.C.6.c.2.h, 4.C.6.c.2.o, 6.C.7, 9.A.3, 12.A.6 and 19.A.3.

TABLE OF CONTENTS

1. INTRODUCTION

- (a) Category I and Category II items
- (b) Trade off "range" and "payload"
- (c) General Technology Note
- (d) General Software Note
- (e) Chemical Abstracts Service (CAS) Numbers

2. DEFINITIONS

- "Accuracy"
- "Basic scientific research"
- "Development"
- "In the public domain"
- "Microcircuit"
- "Microprogrammes"
- "Payload"
 - Ballistic Missiles
 - Space Launch Vehicles
 - Sounding Rocket
 - Cruise Missiles
 - Other UAVs
- "Production"
- "Production equipment"
- "Production facilities"
- "Programmes"
- "Radiation hardened"
- "Range"
- "Software"
- "Technology"
- "Technical assistance"
- "Technical data"
- "Use"

3. TERMINOLOGY

- "Specially designed"
- "Designed or modified"
- "Usable in", "usable for", "usable as" or "capable of"
- "Modified"

CATEGORY I - ITEM 1 COMPLETE DELIVERY SYSTEMS

- 1.A.1 Complete rocket systems (≥ 300 km "range" & ≥ 500 kg "payload")
- 1.A.2 Complete unmanned aerial vehicle systems (UAVs) (≥ 300 km "range" & ≥ 500 kg "payload")
 - 1.B.1. "Production facilities"
- 1.C. None
- 1.D.1. "Software"
- 1.D.2. "Software"
- 1.E.1. "Technology"

CATEGORY I - ITEM 2

COMPLETE SUBSYSTEMS USABLE FOR COMPLETE DELIVERY SYSTEMS

- 2.A.1. "Complete subsystems"
- 2.B.1. "Production facilities"
- 2.B.2. "Production equipment"
- 2.C. None
- 2.D.1. "Software"
- 2.D.2. "Software"
- 2.D.3. "Software"
- 2.D.4. "Software"
- 2.D.5. "Software"
- 2.D.6. "Software"
- 2.E.1. "Technology"

CATEGORY II - ITEM 3

PROPULSION COMPONENTS AND EQUIPMENT

- 3.A.1. Turbojet and turbofan engines (including turbocompound)
- 3.A.2. Ramjet/scramjet/pulse jet/combined cycle engines
- 3.A.3. Rocket motor cases "insulation components and nozzles"
- 3.A.4. Staging mechanisms, separation mechanisms and interstages
- 3.A.5. Liquid and slurry propellant (including oxidisers) control systems
- 3.A.6. Hybrid rocket motors
- 3.A.7. Radial ball bearings
- 3.A.8. Liquid propellant tanks
- 3.A.9. Turboprop engine systems
- 3.B.1. "Production facilities"
- 3.B.2. "Production equipment"
- 3.B.3. Flow-forming machines
- 3.C.1. 'Interior lining' usable for rocket motor cases
- 3.C.2. 'Insulation' material in bulk form usable for rocket motor cases
- 3.D.1. "Software"
- 3.D.2. "Software"
- 3.D.3. "Software"
- 3.E.1. "Technology"

CATEGORY II - ITEM 4

PROPELLANTS, CHEMICALS AND PROPELLANT PRODUCTION

- 4.A. None
- 4.B.1. "Production equipment"
- 4.B.2. "Production equipment"
- 4.B.3.a. Batch mixers
 - b. Continuous mixers
 - c. Fluid energy mills
 - d. Metal powder "production equipment"

TABLE OF CONTENTS

4.C.1. Composite and composite modified double base propellants	6.C.3. Fine grain graphites
4.C.2. Fuel substances	6.C.4. Pyrolytic or fibrous reinforced graphites
a. Hydrazine	6.C.5. Ceramic composite materials for missile radomes
b. Hydrazine derivatives	6.C.6. Silicon-carbide materials
c. Spherical aluminium powder	6.C.7. Tungsten molybdenum and alloys
d. Zirconium beryllium magnesium and alloys	6.C.8. Maraging steel
e. Boron and boron alloys	6.C.9. Titanium-stabilized duplex stainless steel
f. High energy density materials	6.D.1. "Software"
4.C.3. Perchlorates, chlorates or chromates	6.D.2. "Software"
4.C.4.a. Oxidiser substances – liquid propellant rocket engines	6.E.1. "Technology"
b. Oxidiser substances – solid propellant rocket motors	6.E.2. "Technical data"
4.C.5. Polymeric substances	6.E.3. "Technology"
4.C.6. Other propellant additives and agents	CATEGORY II - ITEM 7
a. Bonding agents	Intentionally left blank
b. Curing reaction catalysts	CATEGORY II - ITEM 8
c. Burning rate modifiers	Intentionally left blank
d. Esters and plasticisers	CATEGORY II - ITEM 9
e. Stabilisers	<u>INSTRUMENTATION, NAVIGATION AND DIRECTION FINDING</u>
4.D.1. "Software"	9.A.1. Integrated flight instrument systems
4.E.1. "Technology"	9.A.2. Gyro-astro compasses
CATEGORY II - ITEM 5	9.A.3. Linear accelerometers
Intentionally left blank	9.A.4. All types of gyros
CATEGORY II - ITEM 6	9.A.5. Accelerometers or gyros
<u>PRODUCTION OF STRUCTURAL COMPOSITES, PYROLYTIC DEPOSITION AND DENSIFICATION, AND STRUCTURAL MATERIALS</u>	9.A.6. Inertial or other equipment
6.A.1. Composite structures, laminates and manufactures thereof	9.A.7. 'Integrated navigation systems'
6.A.2. Resaturated pyrolysed materials	9.A.8. Three axis magnetic heading sensors
6.B.1.a. Filament winding machines or fibre placement machines	9.B.1. "Production equipment", and other test, calibration and alignment equipment
b. Tape-laying machines	9.B.2.a. Balancing machines
c. Multi-directional, multi-dimensional weaving machines or interlacing machines	b. Indicator heads
d. Equipment designed or modified for the production of fibrous or filamentary materials	c. Motion simulators/rate tables
e. Equipment designed or modified for special fibre surface treatment	d. Positioning tables
6.B.2. Nozzles	e. Centrifuges
6.B.3. Isostatic presses	9.C. None
6.B.4. Chemical vapour deposition furnaces	9.D.1. "Software"
6.B.5. Equipment and controls for the densification and pyrolysis process	9.D.2. Integration "Software"
6.C.1. Resin impregnated fibre prepregs and metal coated fibre preforms	9.D.3. Integration "Software"
6.C.2. Resaturated pyrolysed materials	9.D.4. Integration "Software"
	9.E.1. "Technology"
	CATEGORY II - ITEM 10
	<u>FLIGHT CONTROL</u>
	10.A.1. Hydraulic, mechanical, electro-optical or electromechanical flight control systems
	10.A.2. Attitude control equipment
	10.A.3. Flight control servo-valves
	10.B.1. Test calibration and alignment equipment
	10.C. None

TABLE OF CONTENTS

- 10.D.1. "Software"
- 10.E.1. Design "technology" for integration of air vehicle fuselage, propulsion system and lifting control surfaces
- 10.E.2. Design "technology" for integration of the flight control, guidance, and propulsion data into a flight management system
- 10.E.3. "Technology"

CATEGORY II - ITEM 11

AVIONICS

- 11.A.1. Radar and laser radar systems including altimeters
- 11.A.2. Passive sensors
- 11.A.3. Receiving equipment GNSS e.g. GPS, GLONASS or Galileo
- 11.A.4. Electronic assemblies and components
- 11.B. None
- 11.C. None
- 11.D.1. "Software"
- 11.D.2. "Software"
- 11.E.1. Design "technology"
- 11.E.2. "Technology"

CATEGORY II - ITEM 12

LAUNCH SUPPORT

- 12.A.1. Apparatus and devices
- 12.A.2. Vehicles
- 12.A.3. Gravity meters (gravimeters), gravity gradiometers
- 12.A.4. Telemetry and telecontrol equipment, including ground equipment
- 12.A.5. Precision tracking systems
 - a. Tracking Systems
 - b. Range instrumentation radars
- 12.A.6. Thermal Batteries
- 12.B. None
- 12.C. None
- 12.D.1. "Software"
- 12.D.2. "Software"
- 12.D.3. "Software"
- 12.E.1. "Technology"

CATEGORY II - ITEM 13

COMPUTERS

- 13.A.1. Analogue or digital computers or digital differential analysers
- 13.B. None
- 13.C. None
- 13.D. None
- 13.E.1. "Technology"

CATEGORY II - TEM 14

ANALOGUE TO DIGITAL CONVERTERS

- 14.A.1. Analogue-to-digital converters
- 14.B. None
- 14.C. None
- 14.D. None
- 14.E.1. "Technology"

CATEGORY II - ITEM 15

TEST FACILITIES AND EQUIPMENT

- 15.A. None
- 15.B.1. Vibration test equipment
 - a. Vibration test systems
 - b. Digital controllers
 - c. Vibration thrusters (shaker units)
 - d. Test piece support structures and electronic units
- 15.B.2. Wind-tunnels
- 15.B.3. Test benches/stands
- 15.B.4. Environmental chambers
- 15.B.5. Accelerators
- 15.C. None
- 15.D.1. "Software"
- 15.E.1. "Technology"

CATEGORY II - ITEM 16

MODELLING-SIMULATION AND DESIGN INTEGRATION

- 16.A.1. Hybrid (combined analogue/digital) computers
- 16.B. None
- 16.C. None
- 16.D.1. "Software"
- 16.E.1. "Technology"

CATEGORY II - ITEM 17

STEALTH

- 17.A.1. Devices for reduced observables
- 17.B.1. Systems specially designed for radar cross section measurement
- 17.C.1. Materials for reduced observables
- 17.D.1. "Software"
- 17.E.1. "Technology"

CATEGORY II - ITEM 18

NUCLEAR EFFECTS PROTECTION

- 18.A.1. "Radiation Hardened" "microcircuits"
- 18.A.2. 'Detectors'
- 18.A.3. Radomes
- 18.B. None
- 18.C. None
- 18.D. None
- 18.E.1. "Technology"

CATEGORY II - ITEM 19

OTHER COMPLETE DELIVERY SYSTEMS

TABLE OF CONTENTS

- 19.A.1. Other complete rocket systems ($\geq 300\text{km}$ range)
- 19.A.2. Other complete UAV systems ($\geq 300\text{km}$ range)
- 19.A.3. Other complete UAV systems
- 19.B. None
- 19.C. None
- 19.D.1. "Software"
- 19.E.1. "Technology"

CATEGORY II - ITEM 20

OTHER COMPLETE SUBSYSTEMS

- 20.A.1.a. Individual rocket stages
 - b. Solid propellant rocket motors or liquid propellant rocket engines
- 20.B.1. "Production facilities"
- 20.B.2. "Production equipment"
- 20.C. None
- 20.D.1. "Software"
- 20.D.2. "Software"
- 20.E.1. "Technology"

UNITS, CONSTANTS, ACRONYMS AND ABBREVIATIONS USED IN THIS ANNEX

TABLE OF CONVERSIONS

STATEMENT OF UNDERSTANDING

INTRODUCTION, DEFINITIONS, TERMINOLOGY

1. INTRODUCTION

- (a) This Annex consists of two categories of items, which term includes equipment, materials, "software" or "technology". Category I items, all of which are in Annex Items 1 and 2, are those items of greatest sensitivity. If a Category I item is included in a system, that system will also be considered as Category I, except when the incorporated item cannot be separated, removed or duplicated. Category II items are those items in the Annex not designated Category I.
- (b) In reviewing the proposed applications for transfers of complete rocket and unmanned aerial vehicle systems described in Items 1 and 19, and of equipment, materials, "software" or "technology" which is listed in the Technical Annex, for potential use in such systems, the Government will take account of the ability to trade off "range" and "payload".
- (c) **General Technology Note:**
The transfer of "technology" directly associated with any goods controlled in the Annex is controlled according to the provisions in each Item to the extent permitted by national legislation. The approval of any Annex item for export also authorizes the export to the same end-user of the minimum "technology" required for the installation, operation, maintenance, and repair of the item.

Note:

Controls do not apply to "technology" "in the public domain" or to "basic scientific research".

INTRODUCTION, DEFINITIONS, TERMINOLOGY

(d) **General Software Note:**

The Annex does not control "software" which is either:

1. Generally available to the public by being:
 - a. Sold from stock at retail selling points without restriction, by means of:
 1. Over-the-counter transactions;
 2. Mail order transactions; or
 3. Telephone call transactions; and
 - b. Designed for installation by the user without further substantial support by the supplier; or
2. "In the public domain".

Note:

The General Software Note only applies to general purpose, mass market "software".

(e) **Chemical Abstracts Service (CAS) Numbers:**

In some instances chemicals are listed by name and CAS number. Chemicals of the same structural formula (including hydrates) are controlled regardless of name or CAS number. CAS numbers are shown to assist in identifying whether a particular chemical or mixture is controlled, irrespective of nomenclature. CAS numbers cannot be used as unique identifiers because some forms of the listed chemical have different CAS numbers, and mixtures containing a listed chemical may also have different CAS numbers.

INTRODUCTION, DEFINITIONS, TERMINOLOGY

2. DEFINITIONS

For the purpose of this Annex, the following definitions apply:

"Accuracy"

Usually measured in terms of inaccuracy, means the maximum deviation, positive or negative, of an indicated value from an accepted standard or true value.

"Basic scientific research"

Experimental or theoretical work undertaken principally to acquire new knowledge of the fundamental principles of phenomena or observable facts, not primarily directed towards a specific practical aim or objective.

"Development"

Is related to all phases prior to "production" such as:

- design
- design research
- design analysis
- design concepts
- assembly and testing of prototypes
- pilot production schemes
- design data
- process of transforming design data into a product
- configuration design
- integration design
- layouts

"In the public domain"

This means "software" or "technology" which has been made available without restrictions upon its further dissemination. (Copyright restrictions do not remove "software" or "technology" from being "in the public domain".)

"Microcircuit"

A device in which a number of passive and/or active elements are considered as indivisibly associated on or within a continuous structure to perform the function of a circuit.

INTRODUCTION, DEFINITIONS, TERMINOLOGY

"Microprogrammes"

A sequence of elementary instructions maintained in a special storage, the execution of which is initiated by the introduction of its reference instruction register.

"Payload"

The total mass that can be carried or delivered by the specified rocket system or unmanned aerial vehicle (UAV) system that is not used to maintain flight.

Note:

The particular equipment, subsystems, or components to be included in the "payload" depends on the type and configuration of the vehicle under consideration.

Technical Notes:

1. Ballistic Missiles

a. "Payload" for systems with separating re-entry vehicles (RVs) includes:

1. The RVs, including:
 - a. Dedicated guidance, navigation, and control equipment;
 - b. Dedicated countermeasures equipment;
2. Munitions of any type (e.g. explosive or non-explosive);
3. Supporting structures and deployment mechanisms for the munitions (e.g. hardware used to attach to, or separate the RV from, the bus/post-boost vehicle) that can be removed without violating the structural integrity of the vehicle;
4. Mechanisms and devices for safing, arming, fuzing or firing;
5. Any other countermeasures equipment (e.g. decoys, jammers or chaff dispensers) that separate from the RV bus/post-boost vehicle;
6. The bus/post-boost vehicle or attitude control/velocity trim module not including systems/subsystems essential to the operation of the other stages.

b. "Payload" for systems with non-separating re-entry vehicles includes:

1. Munitions of any type (e.g. explosive or non-explosive);
2. Supporting structures and deployment mechanisms for the munitions that can be removed without violating the structural integrity of the vehicle;

INTRODUCTION, DEFINITIONS, TERMINOLOGY

3. *Mechanisms and devices for safing, arming, fuzing or firing;*
4. *Any countermeasures equipment (e.g. decoys, jammers or chaff dispensers) that can be removed without violating the structural integrity of the vehicle.*

2. *Space Launch Vehicles*

"Payload" includes:

- a. *Satellites (single or multiple);*
- b. *Satellite-to-launch vehicle adapters including, if applicable, apogee/perigee kick motors or similar manoeuvring systems.*

3. *Sounding Rockets*

"Payload" includes:

- a. *Equipment required for a mission, such as data gathering, recording or transmitting devices for mission-specific data;*
- b. *Recovery equipment (e.g. parachutes) that can be removed without violating the structural integrity of the vehicle.*

4. *Cruise Missiles*

"Payload" includes:

- a. *Munitions of any type (e.g. explosive or non-explosive);*
- b. *Supporting structures and deployment mechanisms for the munitions that can be removed without violating the structural integrity of the vehicle;*
- c. *Mechanisms and devices for safing, arming, fuzing or firing;*
- d. *Countermeasures equipment (e.g. decoys, jammers or chaff dispensers) that can be removed without violating the structural integrity of the vehicle;*
- e. *Signature alteration equipment that can be removed without violating the structural integrity of the vehicle.*

5. *Other UAVs*

"Payload" includes:

- a. *Munitions of any type (e.g. explosive or non-explosive);*
- b. *Mechanisms and devices for safing, arming, fuzing or firing;*

INTRODUCTION, DEFINITIONS, TERMINOLOGY

- c. Countermeasures equipment (e.g. decoys, jammers or chaff dispensers) that can be removed without violating the structural integrity of the vehicle;*
- d. Signature alteration equipment that can be removed without violating the structural integrity of the vehicle;*
- e. Equipment required for a mission such as data gathering, recording or transmitting devices for mission-specific data and supporting structures that can be removed without violating the structural integrity of the vehicle;*
- f. Recovery equipment (e.g. parachutes) that can be removed without violating the structural integrity of the vehicle.*
- g. Munitions supporting structures and deployment mechanisms that can be removed without violating the structural integrity of the vehicle.*

"Production"

Means all production phases such as:

- production engineering
- manufacture
- integration
- assembly (mounting)
- inspection
- testing
- quality assurance

"Production equipment"

Means tooling, templates, jigs, mandrels, moulds, dies, fixtures, alignment mechanisms, test equipment, other machinery and components therefor, limited to those specially designed or modified for "development" or for one or more phases of "production".

"Production facilities"

Means "**production equipment**" and specially designed "software" therefor integrated into installations for "development" or for one or more phases of "production".

"Programmes"

A sequence of instructions to carry out a process in, or convertible into, a form executable by an electronic computer.

INTRODUCTION, DEFINITIONS, TERMINOLOGY

"Radiation hardened"

Means that the component or equipment is designed or rated to withstand radiation levels which meet or exceed a total irradiation dose of 5×10^5 rads (Si).

"Range"

The maximum distance that the specified rocket system or unmanned aerial vehicle (UAV) system is capable of travelling in the mode of stable flight as measured by the projection of its trajectory over the surface of the Earth.

Technical Notes:

- 1. The maximum capability based on the design characteristics of the system, when fully loaded with fuel or propellant, will be taken into consideration in determining "range".*
- 2. The "range" for both rocket systems and UAV systems will be determined independently of any external factors such as operational restrictions, limitations imposed by telemetry, data links or other external constraints.*
- 3. For rocket systems, the "range" will be determined using the trajectory that maximises "range", assuming ICAO standard atmosphere with zero wind.*
- 4. For UAV systems, the "range" will be determined for a one-way distance using the most fuel-efficient flight profile (e.g. cruise speed and altitude), assuming ICAO standard atmosphere with zero wind.*

"Software"

A collection of one or more "programmes", or "micro-programmes", fixed in any tangible medium of expression.

"Technology"

Means specific information which is required for the "development", "production" or "use" of a product. The information may take the form of "technical data" or "technical assistance".

"Technical assistance"

May take forms such as:

- instruction
- skills

INTRODUCTION, DEFINITIONS, TERMINOLOGY

- training
- working knowledge
- consulting services

"Technical data"

May take forms such as:

- blueprints
- plans
- diagrams
- models
- formulae
- engineering designs and specifications
- manuals and instructions written or recorded on other media or devices such as:
 - disk
 - tape
 - read-only memories

"Use"

Means:

- operation
- installation (including on-site installation)
- maintenance
- repair
- overhaul
- refurbishing

INTRODUCTION, DEFINITIONS, TERMINOLOGY

3. TERMINOLOGY

Where the following terms appear in the text, they are to be understood according to the explanations below:

- (a) "Specially designed" describes equipment, parts, components or "software" which, as a result of "development", have unique properties that distinguish them for certain predetermined purposes. For example, a piece of equipment that is "specially designed" for use in a missile will only be considered so if it has no other function or use. Similarly, a piece of manufacturing equipment that is "specially designed" to produce a certain type of component will only be considered such if it is not capable of producing other types of components.
- (b) "Designed or modified" describes equipment, parts or components which, as a result of "development," or modification, have specified properties that make them fit for a particular application. "Designed or modified" equipment, parts, components or "software" can be used for other applications. For example, a titanium coated pump designed for a missile may be used with corrosive fluids other than propellants.
- (c) "Usable in", "usable for", "usable as" or "capable of" describes equipment, parts, components, materials or "software" which are suitable for a particular purpose. There is no need for the equipment, parts, components or "software" to have been configured, modified or specified for the particular purpose. For example, any military specification memory circuit would be "capable of" operation in a guidance system.
- (d) "Modified" in the context of "software" describes "software" which has been intentionally changed such that it has properties that make it fit for specified purposes or applications. Its properties may also make it suitable for purposes or applications other than those for which it was "modified".

CATEGORY I; ITEM 1

CATEGORY I

ITEM 1 COMPLETE DELIVERY SYSTEMS

1.A. EQUIPMENT, ASSEMBLIES AND COMPONENTS

1.A.1. Complete rocket systems (including ballistic missile systems, space launch vehicles, and sounding rockets) capable of delivering at least a 500 kg "payload" to a "range" of at least 300 km.

1.A.2. Complete unmanned aerial vehicle systems (including cruise missile systems, target drones and reconnaissance drones) capable of delivering at least a 500 kg "payload" to a "range" of at least 300 km.

1.B. TEST AND PRODUCTION EQUIPMENT

1.B.1. "Production facilities" specially designed for the systems specified in 1.A.

1.C. MATERIALS

None.

1.D. SOFTWARE

1.D.1. "Software" specially designed or modified for the "use" of "production facilities" specified in 1.B.

1.D.2. "Software" which coordinates the function of more than one subsystem, specially designed or modified for "use" in systems specified in 1.A.

1.E. TECHNOLOGY

1.E.1. "Technology", in accordance with the General Technology Note, for the "development", "production" or "use" of equipment or "software" specified in 1.A., 1.B., or 1.D.

CATEGORY I; ITEM 2

ITEM 2 COMPLETE SUBSYSTEMS USABLE FOR COMPLETE DELIVERY SYSTEMS

2.A. EQUIPMENT, ASSEMBLIES AND COMPONENTS

2.A.1. Complete subsystems usable in the systems specified in 1.A., as follows:

- a. Individual rocket stages usable in the systems specified in 1.A.;
- b. Re-entry vehicles, and equipment designed or modified therefor, usable in the systems specified in 1.A., as follows, except as provided in the Note below 2.A.1. for those designed for non-weapon payloads:
 1. Heat shields, and components therefor, fabricated of ceramic or ablative materials;
 2. Heat sinks and components therefor, fabricated of light-weight, high heat capacity materials;
 3. Electronic equipment specially designed for re-entry vehicles;
- c. Solid propellant rocket motors or liquid propellant rocket engines, usable in the systems specified in 1.A., having a total impulse capacity equal to or greater than 1.1×10^6 Ns;

Note:

Liquid propellant apogee engines and station-keeping engines specified in 2.A.1.c., designed or modified for use on satellites, may be treated as Category II, if the subsystem is exported subject to end-use statements and quantity limits appropriate for the excepted end-use stated above, when having a vacuum thrust not greater than 1kN.

- d. 'Guidance sets', usable in the systems specified in 1.A., capable of achieving system accuracy of 3.33% or less of the "range" (e.g. a 'CEP' of 10 km or less at a "range" of 300 km), except as provided in the Note below 2.A.1. for those designed for missiles with a "range" under 300 km or manned aircraft;

CATEGORY I; ITEM 2

Technical Notes:

1. A 'guidance set' integrates the process of measuring and computing a vehicle's position and velocity (i.e. navigation) with that of computing and sending commands to the vehicle's flight control systems to correct the trajectory.
 2. 'CEP' (circle of equal probability) is a measure of accuracy, defined as the radius of the circle centred at the target, at a specific range, in which 50% of the payloads impact.
- e. Thrust vector control sub-systems, usable in the systems specified in 1.A., except as provided in the Note below 2.A.1. for those designed for rocket systems that do not exceed the "range"/"payload" capability of systems specified in 1.A.;

Technical Note:

2.A.1.e. includes the following methods of achieving thrust vector control:

- a. Flexible nozzle;
 - b. Fluid or secondary gas injection;
 - c. Movable engine or nozzle;
 - d. Deflection of exhaust gas stream (jet vanes or probes);
 - e. Use of thrust tabs.
- f. Weapon or warhead safing, arming, fuzing, and firing mechanisms, usable in the systems specified in 1.A., except as provided in the Note below 2.A.1. for those designed for systems other than those specified in 1.A.

Note:

The exceptions in 2.A.1.b., 2.A.1.d., 2.A.1.e. and 2.A.1.f. above may be treated as Category II if the subsystem is exported subject to end-use statements and quantity limits appropriate for the excepted end-use stated above.

2.B. TEST AND PRODUCTION EQUIPMENT

- 2.B.1. "Production facilities" specially designed for the subsystems specified in 2.A.

CATEGORY I; ITEM 2

2.B.2. "Production equipment" specially designed for the subsystems specified in 2.A.

2.C. MATERIALS

None.

2.D. SOFTWARE

2.D.1. "Software" specially designed or modified for the "use" of "production facilities" specified in 2.B.1.

2.D.2. "Software" specially designed or modified for the "use" of rocket motors or engines specified in 2.A.1.c.

2.D.3. "Software", specially designed or modified for the "use" of 'guidance sets' specified in 2.A.1.d.

Note:

2.D.3. includes "software", specially designed or modified to enhance the performance of 'guidance sets' to achieve or exceed the accuracy specified in 2.A.1.d.

2.D.4. "Software" specially designed or modified for the "use" of subsystems or equipment specified in 2.A.1.b.3.

2.D.5. "Software" specially designed or modified for the "use" of systems in 2.A.1.e.

2.D.6. "Software" specially designed or modified for the "use" of systems in 2.A.1.f.

Note:

Subject to end-use statements appropriate for the excepted end-use, "software" controlled by 2.D.2. - 2.D.6. may be treated as Category II as follows:

- 1. Under 2.D.2. if specially designed or modified for liquid propellant apogee engines, designed or modified for satellite applications as specified in the Note to 2.A.1.c.;*

CATEGORY I; ITEM 2

2. *Under 2.D.3. if designed for missiles with a "range" of under 300 km or manned aircraft;*
3. *Under 2.D.4. if specially designed or modified for re-entry vehicles designed for non-weapon payloads;*
4. *Under 2.D.5. if designed for rocket systems that do not exceed the "range" "payload" capability of systems specified in 1.A.;*
5. *Under 2.D.6. if designed for systems other than those specified in 1.A.*

2.E. TECHNOLOGY

- 2.E.1. "Technology", in accordance with the General Technology Note, for the "development", "production" or "use" of equipment or "software" specified in 2.A., 2.B. or 2.D.

CATEGORY II; ITEM 3

CATEGORY II

ITEM 3 PROPULSION COMPONENTS AND EQUIPMENT

3.A. EQUIPMENT, ASSEMBLIES AND COMPONENTS

3.A.1. Turbojet and turbofan engines, as follows:

- a. Engines having both of the following characteristics:
 1. Maximum thrust value greater than 400 N (achieved un-installed) excluding civil certified engines with a maximum thrust value greater than 8.89 kN (achieved un-installed); and
 2. Specific fuel consumption of $0.15 \text{ kg N}^{-1} \text{ h}^{-1}$ or less (at maximum continuous power at sea level static and standard conditions);
- b. Engines designed or modified for systems specified in 1.A. or 19.A.2., regardless of thrust or specific fuel consumption.

Note:

Engines specified in 3.A.1. may be exported as part of a manned aircraft or in quantities appropriate for replacement parts for a manned aircraft.

- 3.A.2. Ramjet/scramjet/pulse jet/'combined cycle engines', including devices to regulate combustion, and specially designed components therefor, usable in the systems specified in 1.A. or 19.A.2.

Technical Note:

In Item 3.A.2., 'combined cycle engines' are the engines that employ two or more cycles of the following types of engines: gas-turbine engine (turbojet, turboprop, turbofan and turboshaft), ramjet, scramjet, pulse jet, pulse detonation engine, rocket motor (liquid/solid-propellant and hybrid).

- 3.A.3. Rocket motor cases, 'insulation' components and nozzles therefor, usable in the systems specified in 1.A. or 19.A.1.

CATEGORY II; ITEM 3

Technical Note:

In 3.A.3. 'insulation' intended to be applied to the components of a rocket motor, i.e. the case, nozzle inlets, case closures, includes cured or semi-cured compounded rubber components comprising sheet stock containing an insulating or refractory material. It may also be incorporated as stress relief boots or flaps.

Note:

Refer to 3.C.2. for 'insulation' material in bulk or sheet form.

- 3.A.4. Staging mechanisms, separation mechanisms, and interstages therefor, usable in the systems specified in 1.A.
- 3.A.5. Liquid and slurry propellant (including oxidisers) control systems, and specially designed components therefor, usable in the systems specified in 1.A., designed or modified to operate in vibration environments greater than 10 g rms between 20 Hz and 2 kHz.

Notes:

- 1. *The only servo valves and pumps specified in 3.A.5. are the following:*
 - a. *Servo valves designed for flow rates equal to or greater than 24 litres per minute, at an absolute pressure equal to or greater than 7 MPa, that have an actuator response time of less than 100 ms.*
 - b. *Pumps, for liquid propellants, with shaft speeds equal to or greater than 8,000 rpm or with discharge pressures equal to or greater than 7 MPa.*
- 2. *Systems and components specified in 3.A.5. may be exported as part of a satellite.*

- 3.A.6. Hybrid rocket motors and specially designed components therefor, usable in the systems specified in 1.A., 19.A.1. or 19.A.2.
- 3.A.7. Radial ball bearings having all tolerances specified in accordance with ISO 492 Tolerance Class 2 (or ANSI/ABMA Std 20 Tolerance Class ABEC-9 or other national equivalents), or better and having all the following characteristics:

CATEGORY II; ITEM 3

- a. An inner ring bore diameter between 12 and 50 mm;
 - b. An outer ring outside diameter between 25 and 100 mm; and
 - c. A width between 10 and 20 mm.
- 3.A.8. Liquid propellant tanks specially designed for the propellants controlled in Item 4.C. or other liquid propellants used in the systems specified in 1.A.1.
- 3.A.9. 'Turboprop engine systems' specially designed for the systems in 1.A.2. or 19.A.2., and specially designed components therefor, having a maximum power greater than 10 kW (achieved uninstalled at sea level standard conditions), excluding civil certified engines.

Technical Note:

For the purposes of Item 3.A.9., a 'turboprop engine system' incorporates all of the following:

- a. *Turboshaft engine; and*
 - b. *Power transmission system to transfer the power to a propeller.*
- 3.B. TEST AND PRODUCTION EQUIPMENT
- 3.B.1. "Production facilities" specially designed for equipment or materials specified in 3.A.1., 3.A.2., 3.A.3., 3.A.4., 3.A.5., 3.A.6., 3.A.8., 3.A.9. or 3.C.
- 3.B.2. "Production equipment" specially designed for equipment or materials specified in 3.A.1., 3.A.2., 3.A.3., 3.A.4., 3.A.5., 3.A.6., 3.A.8., 3.A.9. or 3.C.
- 3.B.3. Flow-forming machines, and specially designed components therefor, which:
- a. According to the manufacturers technical specification can be equipped with numerical control units or a computer control, even when not equipped with such units at delivery; and
 - b. Have more than two axes which can be co-ordinated simultaneously for contouring control.

Note:

CATEGORY II; ITEM 3

This item does not include machines that are not usable in the "production" of propulsion components and equipment (e.g. motor cases) for systems specified in 1.A.

Technical Note:

Machines combining the function of spin-forming and flow-forming are, for the purpose of this item, regarded as flow-forming machines.

3.C. MATERIALS

- 3.C.1. 'Interior lining' usable for rocket motor cases in the systems specified in 1.A. or specially designed for systems specified in 19.A.1. or 19.A.2.

Technical Note:

In 3.C.1. 'interior lining' suited for the bond interface between the solid propellant and the case or insulating liner is usually a liquid polymer based dispersion of refractory or insulating materials e.g. carbon filled HTPB or other polymer with added curing agents to be sprayed or screeded over a case interior.

- 3.C.2. 'Insulation' material in bulk form usable for rocket motor cases in the systems specified in 1.A. or specially designed for systems specified in 19.A.1. or 19.A.2.

Technical Note:

In 3.C.2. 'insulation' intended to be applied to the components of a rocket motor, i.e. the case, nozzle inlets, case closures, includes cured or semi-cured compounded rubber sheet stock containing an insulating or refractory material. It may also be incorporated as stress relief boots or flaps specified in 3.A.3.

CATEGORY II; ITEM 3

3.D. SOFTWARE

- 3.D.1. "Software" specially designed or modified for the "use" of "production facilities" and flow forming machines specified in 3.B.1. or 3.B.3.
- 3.D.2. "Software" specially designed or modified for the "use" of equipment specified in 3.A.1., 3.A.2., 3.A.4., 3.A.5., 3.A.6. or 3.A.9.

Notes:

1. *"Software" specially designed or modified for the "use" of engines specified in 3.A.1. may be exported as part of a manned aircraft or as replacement "software" therefor.*
 2. *"Software" specially designed or modified for the "use" of propellant control systems specified in 3.A.5. may be exported as part of a satellite or as replacement "software" therefor.*
- 3.D.3. "Software" specially designed or modified for the "development" of equipment specified in 3.A.2., 3.A.3. or 3.A.4.

3.E. TECHNOLOGY

- 3.E.1. "Technology", in accordance with the General Technology Note, for the "development", "production" or "use" of equipment, materials or "software" specified in 3.A.1., 3.A.2., 3.A.3., 3.A.4., 3.A.5., 3.A.6., 3.A.9., 3.B., 3.C. or 3.D.

CATEGORY II; ITEM 4

ITEM 4 PROPELLANTS, CHEMICALS AND PROPELLANT PRODUCTION

4.A. EQUIPMENT, ASSEMBLIES AND COMPONENTS

None.

4.B. TEST AND PRODUCTION EQUIPMENT

4.B.1. "Production equipment", and specially designed components therefor, for the "production", handling or acceptance testing of liquid propellants or propellant constituents specified in 4.C.

4.B.2. "Production equipment", other than that described in 4.B.3., and specially designed components therefor, for the production, handling, mixing, curing, casting, pressing, machining, extruding or acceptance testing of solid propellants or propellant constituents specified in 4.C.

4.B.3. Equipment as follows, and specially designed components therefor:

- a. Batch mixers with provision for mixing under vacuum in the range of zero to 13.326 kPa and with temperature control capability of the mixing chamber and having all of the following:
 1. A total volumetric capacity of 110 litres or more; and
 2. At least one mixing/kneading shaft mounted off centre;
- b. Continuous mixers with provision for mixing under vacuum in the range of zero to 13.326 kPa and with a temperature control capability of the mixing chamber having any of the following:
 1. Two or more mixing/kneading shafts; or
 2. A single rotating shaft which oscillates and having kneading teeth/pins on the shaft as well as inside the casing of the mixing chamber;
- c. Fluid energy mills usable for grinding or milling substances specified in 4.C.;
- d. Metal powder "production equipment" usable for the "production", in a controlled environment, of spherical or atomised materials specified in 4.C.2.c., 4.C.2.d. or 4.C.2.e.

CATEGORY II; ITEM 4

Note:

4.B.3.d. includes:

- a. Plasma generators (high frequency arc-jet) usable for obtaining sputtered or spherical metallic powders with organization of the process in an argon-water environment;*
- b. Electroburst equipment usable for obtaining sputtered or spherical metallic powders with organization of the process in an argon-water environment;*
- c. Equipment usable for the "production" of spherical aluminium powders by powdering a melt in an inert medium (e.g. nitrogen).*

Notes:

- 1. The only batch mixers, continuous mixers, usable for solid propellants or propellants constituents specified in 4.C., and fluid energy mills specified in 4.B., are those specified in 4.B.3.*
- 2. Forms of metal powder "production equipment" not specified in 4.B.3.d. are to be evaluated in accordance with 4.B.2.*

4.C. MATERIALS

4.C.1. Composite and composite modified double base propellants.

4.C.2. Fuel substances as follows:

- a. Hydrazine (CAS 302-01-2) with a concentration of more than 70%;
- b. Hydrazine derivatives as follows:
 1. Monomethylhydrazine (MMH) (CAS 60-34-4);
 2. Unsymmetrical dimethylhydrazine (UDMH) (CAS 57-14-7);
 3. Hydrazine mononitrate;
 4. Trimethylhydrazine (CAS 1741-01-1);
 5. Tetramethylhydrazine (CAS 6415-12-9);
 6. N,N diallylhydrazine;
 7. Allylhydrazine (CAS 7422-78-8);
 8. Ethylene dihydrazine;
 9. Monomethylhydrazine dinitrate;
 10. Unsymmetrical dimethylhydrazine nitrate;

CATEGORY II; ITEM 4

11. Hydrazinium azide (CAS 14546-44-2);
12. Dimethylhydrazinium azide;
13. Hydrazinium dinitrate;
14. Diimido oxalic acid dihydrazine (CAS 3457-37-2);
15. 2-hydroxyethylhydrazine nitrate (HEHN);
16. Hydrazinium perchlorate (CAS 27978-54-7);
17. Hydrazinium diperchlorate (CAS 13812-39-0);
18. Methylhydrazine nitrate (MHN);
19. Diethylhydrazine nitrate (DEHN);
20. 3,6-dihydrazino tetrazine nitrate (DHTN);

Technical note:

*3,6-dihydrazino tetrazine nitrate is also referred to as
1,4-dihydrazine nitrate*

- c. Spherical aluminium powder (CAS 7429-90-5) with particles of uniform diameter of less than 200×10^{-6} m (200 μ m) and an aluminium content of 97% by weight or more, if at least 10% of the total weight is made up of particles of less than 63 μ m, according to ISO 2591:1988 or national equivalents such as JIS Z8820;

Technical Note:

A particle size of 63 μ m (ISO R-565) corresponds to 250 mesh (Tyler) or 230 mesh (ASTM standard E-11).

- d. Zirconium (CAS 7440-67-7), beryllium (CAS 7440-41-7), magnesium (CAS 7439-95-4) and alloys of these in particle size less than 60×10^{-6} m (60 μ m), whether spherical, atomised, spheroidal, flaked or ground, consisting of 97% by weight or more of any of the above mentioned metals;

Technical Note:

The natural content of hafnium (CAS 7440-58-6) in the zirconium (typically 2% to 7%) is counted with the zirconium.

CATEGORY II; ITEM 4

- e. Boron (CAS 7440-42-8) and boron alloys in particle size less than 60×10^{-6} m (60 μ m), whether spherical, atomised, spheroidal, flaked or ground with a purity of 85% by weight or more;
- f. **High energy density materials, usable in the systems specified in 1.A. or 19.A., as follows:**
 - 1. **Mixed fuels that incorporate both solid and liquid fuels, such as boron slurry, having a mass- based energy density of 40×10^6 J/kg or greater;**
 - 2. **Other high energy density fuels and fuel additives (e.g., cubane, ionic solutions, JP-10) having a volume-based energy density of 37.5×10^9 J/m³ or greater, measured at 20°C and one atmosphere (101.325 kPa) pressure.**

Note:

Item 4.C.2.f.2. does not control fossil refined fuels and biofuels produced from vegetables, including fuels for engines certified for use in civil aviation, unless specifically formulated for systems specified in 1.A. or 19.A.

4.C.3. Oxidisers/Fuels as follows:

Perchlorates, chlorates or chromates mixed with powdered metals or other high energy fuel components.

4.C.4. Oxidiser substances as follows:

- a. Oxidiser substances usable in liquid propellant rocket engines as follows:
 - 1. Dinitrogen trioxide (CAS 10544-73-7);
 - 2. Nitrogen dioxide (CAS 10102-44-0) / dinitrogen tetroxide (CAS 10544-72-6);
 - 3. Dinitrogen pentoxide (CAS 10102-03-1);
 - 4. Mixed Oxides of Nitrogen (MON);
 - 5. Inhibited Red Fuming Nitric Acid (IRFNA) (CAS 8007-58-7);
 - 6. Compounds composed of fluorine and one or more of other halogens, oxygen or nitrogen;

CATEGORY II; ITEM 4

Note:

Item 4.C.4.a.6. does not control Nitrogen Trifluoride (NF₃) (CAS 7783-54-2) in a gaseous state as it is not usable for missile applications.

Technical Note:

Mixed Oxides of Nitrogen (MON) are solutions of Nitric Oxide (NO) in Dinitrogen Tetroxide/Nitrogen Dioxide (N₂O₄/NO₂) that can be used in missile systems. There are a range of compositions that can be denoted as MON_i or MON_{ij} where i and j are integers representing the percentage of Nitric Oxide in the mixture (e.g. MON₃ contains 3% Nitric Oxide, MON₂₅ 25% Nitric Oxide. An upper limit is MON₄₀, 40% by weight).

- b. Oxidiser substances usable in solid propellant rocket motors as follows:
1. Ammonium perchlorate (AP) (CAS 7790-98-9);
 2. Ammonium dinitramide (ADN) (CAS 140456-78-6);
 3. Nitro-amines (cyclotetramethylene - tetranitramine (HMX) (CAS 2691-41-0); cyclotrimethylene - trinitramine (RDX) (CAS 121-82-4);
 4. Hydrazinium nitroformate (HNF) (CAS 20773-28-8);
 5. 2,4,6,8,10,12-Hexanitrohexaazaisowurtzitane (CL-20) (CAS 135285-90-4).

4.C.5. Polymeric substances, as follows:

- a. Carboxy - terminated polybutadiene (including carboxyl - terminated polybutadiene) (CTPB);
- b. Hydroxy - terminated polybutadiene (including hydroxyl - terminated polybutadiene) (HTPB);
- c. Glycidyl azide polymer (GAP);
- d. Polybutadiene - Acrylic Acid (PBAA);
- e. Polybutadiene - Acrylic Acid - Acrylonitrile (PBAN);
- f. Polytetrahydrofuran polyethylene glycol (TPEG).

CATEGORY II; ITEM 4

Technical Note:

Polytetrahydrofuran polyethylene glycol (TPEG) is a block co-polymer of poly 1,4-Butanediol and polyethylene glycol (PEG).

4.C.6. Other propellant additives and agents as follows:

a. Bonding agents as follows:

1. Tris (1-(2-methyl)aziridinyl) phosphine oxide (MAPO) (CAS 57-39-6);
2. 1,1',1''-trimesoyl-tris(2-ethylaziridine) (HX-868, BITA) (CAS 7722-73-8);
3. Tepanol (HX-878), reaction product of tetraethylenepentamine, acrylonitrile and glycidol (CAS 68412-46-4);
4. Tepan (HX-879), reaction product of tetraethylenepentamine and acrylonitrile (CAS 68412-45-3);
5. Polyfunctional aziridine amides with isophthalic, trimesic, isocyanuric, or trimethyladipic backbone also having a 2-methyl or 2-ethyl aziridine group;

Note:

Item 4.C.6.a.5. includes:

1. 1,1'-Isophthaloyl-bis(2-methylaziridine) (HX-752) (CAS 7652-64-4);
2. 2,4,6-tris(2-ethyl-1-aziridinyl)-1,3,5-triazine (HX-874) (CAS 18924-91-9);
3. 1,1'-trimethyladipoylbis(2-ethylaziridine) (HX-877) (CAS 71463-62-2).

b. Curing reaction catalysts as follows:

Triphenyl bismuth (TPB) (CAS 603-33-8);

c. Burning rate modifiers, as follows:

1. Carboranes, decaboranes, pentaboranes and derivatives thereof;
2. Ferrocene derivatives, as follows:
 - a. Catocene (CAS 37206-42-1);
 - b. Ethyl ferrocene (CAS 1273-89-8);
 - c. Propyl ferrocene;
 - d. n-Butyl ferrocene (CAS 31904-29-7);
 - e. Pentyl ferrocene (CAS 1274-00-6);
 - f. Dicyclopentyl ferrocene;

CATEGORY II; ITEM 4

- g. Dicyclohexyl ferrocene;
- h. Diethyl ferrocene (CAS 1273-97-8);
- i. Dipropyl ferrocene;
- j. Dibutyl ferrocene (CAS 1274-08-4);
- k. Dihexyl ferrocene (CAS 93894-59-8);
- l. Acetyl ferrocenes;
- m. Ferrocene Carboxylic acids;
- n. Butacene (CAS 125856-62-4);
- o. Other ferrocene derivatives usable as rocket propellant burning rate modifiers;

Note:

Item 4.C.6.c.2.o does not control ferrocene derivatives that contain a six carbon aromatic functional group attached to the ferrocene molecule.

- d. Esters and plasticisers as follows:
 - 1. Triethylene glycol dinitrate (TEGDN) (CAS 111-22-8);
 - 2. Trimethylolethane trinitrate (TMETN) (CAS 3032-55-1);
 - 3. 1,2,4-butanetriol trinitrate (BTTN) (CAS 6659-60-5);
 - 4. Diethylene glycol dinitrate (DEGDN) (CAS 693-21-0);
 - 5. 4,5 diazidomethyl-2-methyl-1,2,3-triazole (iso- DAMTR);
 - 6. Nitrate ethylnitramine (NENA) based plasticisers, as follows:
 - a. Methyl-NENA (CAS 17096-47-8);
 - b. Ethyl-NENA (CAS 85068-73-1);
 - c. Butyl-NENA (CAS 82486-82-6);
 - 7. Dinitropropyl based plasticisers, as follows:
 - a. Bis (2,2-dinitropropyl) acetal (BDNPA) (CAS 5108-69-0);
 - b. Bis (2,2-dinitropropyl) formal (BDNPF) (CAS 5917-61-3);
- e. Stabilisers as follows:
 - 1. 2-Nitrodiphenylamine (CAS 119-75-5);
 - 2. N-methyl-p-nitroaniline (CAS 100-15-2).

4.D. SOFTWARE

CATEGORY II; ITEM 4

4.D.1. "Software" specially designed or modified for the "use" of equipment specified in 4.B. for the "production" and handling of materials specified in 4.C.

4.E. TECHNOLOGY

4.E.1 "Technology", in accordance with the General Technology Note, for the "development", "production" or "use" of equipment or materials specified in 4.B. and 4.C.

CATEGORY II; ITEM 5

This category is intentionally left blank.

CATEGORY II; ITEM 6

ITEM 6 PRODUCTION OF STRUCTURAL COMPOSITES, PYROLYTIC DEPOSITION AND DENSIFICATION, AND STRUCTURAL MATERIALS

6.A. EQUIPMENT, ASSEMBLIES AND COMPONENTS

6.A.1. Composite structures, laminates, and manufactures thereof, specially designed for use in the systems specified in 1.A., 19.A.1. or 19.A.2. and the subsystems specified in 2.A. or 20.A.

6.A.2. Resaturated pyrolysed (i.e. carbon-carbon) components having all of the following:

a. Designed for rocket systems; and

b. Usable in the systems specified in 1.A. or 19.A.1.

6.B. TEST AND PRODUCTION EQUIPMENT

6.B.1. Equipment for the "production" of structural composites, fibres, prepregs or preforms, usable in the systems specified in 1.A., 19.A.1. or 19.A.2., as follows, and specially designed components, and accessories therefor:

a. Filament winding machines or fibre placement machines, of which the motions for positioning, wrapping and winding fibres can be co-ordinated and programmed in three or more axes, designed to fabricate composite structures or laminates from fibrous or filamentary materials, and co-ordinating and programming controls;

b. Tape-laying machines of which the motions for positioning and laying tape and sheets can be co-ordinated and programmed in two or more axes, designed for the manufacture of composite airframes and missile structures;

c. Multi-directional, multi-dimensional weaving machines or interlacing machines, including adapters and modification kits for weaving, interlacing or braiding fibres to manufacture composite structures;

CATEGORY II; ITEM 6

Note:

6.B.1.c. does not control textile machinery not modified for the end-uses stated.

- d. Equipment designed or modified for the production of fibrous or filamentary materials as follows:
 - 1. Equipment for converting polymeric fibres (such as polyacrylonitrile, rayon, or polycarbosilane) including special provision to strain the fibre during heating;
 - 2. Equipment for the vapour deposition of elements or compounds on heated filament substrates;
 - 3. Equipment for the wet-spinning of refractory ceramics (such as aluminium oxide);
- e. Equipment designed or modified for special fibre surface treatment or for producing prepregs and preforms, including rollers, tension stretchers, coating equipment, cutting equipment and clicker dies.

Note:

Examples of components and accessories for the machines specified in 6.B.1. are moulds, mandrels, dies, fixtures and tooling for the preform pressing, curing, casting, sintering or bonding of composite structures, laminates and manufactures thereof.

- 6.B.2. Nozzles specially designed for the processes referred to in 6.E.3.
- 6.B.3. Isostatic presses having all of the following characteristics:
 - a. Maximum working pressure equal to or greater than 69 MPa;
 - b. Designed to achieve and maintain a controlled thermal environment of 600°C or greater; and
 - c. Possessing a chamber cavity with an inside diameter of 254 mm or greater.
- 6.B.4. Chemical vapour deposition furnaces designed or modified for the densification of carbon-carbon composites.

CATEGORY II; ITEM 6

6.B.5. Equipment and process controls, other than those specified in 6.B.3. or 6.B.4., designed or modified for densification and pyrolysis of structural composite rocket nozzles and re-entry vehicle nose tips.

6.C. MATERIALS

6.C.1. Resin impregnated fibre prepregs and metal coated fibre preforms, for the goods specified in 6.A.1., made either with organic matrix or metal matrix utilising fibrous or filamentary reinforcements having a specific tensile strength greater than 7.62×10^4 m and a specific modulus greater than 3.18×10^6 m.

Note:

The only resin impregnated fibre prepregs specified in 6.C.1. are those using resins with a glass transition temperature (T_g), after cure, exceeding 145°C as determined by ASTM D4065 or national equivalents.

Technical Notes:

1. In Item 6.C.1. 'specific tensile strength' is the ultimate tensile strength in N/m^2 divided by the specific weight in N/m^3 , measured at a temperature of $(296 \pm 2)\text{K}$ ($(23 \pm 2)^\circ\text{C}$) and a relative humidity of $(50 \pm 5)\%$.

2. In Item 6.C.1. 'specific modulus' is the Young's modulus in N/m^2 divided by the specific weight in N/m^3 , measured at a temperature of $(296 \pm 2)\text{K}$ ($(23 \pm 2)^\circ\text{C}$) and a relative humidity of $(50 \pm 5)\%$.

6.C.2. Resaturated pyrolysed (i.e. carbon-carbon) materials having all of the following:

a. Designed for rocket systems; and

b. Usable in the systems specified in 1.A. or 19.A.1.

6.C.3. Fine grain graphites with a bulk density of at least 1.72 g/cc measured at 15°C and having a grain size of 100×10^{-6} m (100 μm) or less, usable for rocket nozzles and re-entry vehicle nose tips, which can be machined to any of the following products:

CATEGORY II; ITEM 6

- a. Cylinders having a diameter of 120 mm or greater and a length of 50 mm or greater;
 - b. Tubes having an inner diameter of 65 mm or greater and a wall thickness of 25 mm or greater and a length of 50 mm or greater; or
 - c. Blocks having a size of 120 mm x 120 mm x 50 mm or greater.
- 6.C.4. Pyrolytic or fibrous reinforced graphites usable for rocket nozzles and re-entry vehicle nose tips usable in systems specified in 1.A. or 19.A.1.
- 6.C.5. Ceramic composite materials (dielectric constant less than 6 at any frequency from 100 MHz to 100 GHz) for use in missile radomes usable in systems specified in 1.A. or 19.A.1.
- 6.C.6. Silicon-carbide materials as follows:
- a. Bulk machinable silicon-carbide reinforced unfired ceramic usable for nose tips usable in systems specified in 1.A. or 19.A.1.;
 - b. Reinforced silicon-carbide ceramic composites usable for nose tips, re-entry vehicles, nozzle flaps, usable in systems specified in 1.A. or 19.A.1.
- 6.C.7. **Materials for the fabrication of missile components in the systems specified in 1.A., 19.A.1. or 19.A.2, as follows:**
- a. **Tungsten and alloys in particulate form with a tungsten content of 97% by weight or more and a particle size of 50×10^{-6} m (50 μ m) or less;**
 - b. **Molybdenum and alloys in particulate form with a molybdenum content of 97% by weight or more and a particle size of 50×10^{-6} m (50 μ m) or less;**
 - c. **Tungsten materials in the solid form having all of the following:**
 - 1. **Any of the following material compositions:**
 - i. **Tungsten and alloys containing 97% by weight or more of tungsten;**

CATEGORY II; ITEM 6

- ii. **Copper infiltrated tungsten containing 80% by weight or more of tungsten; or**
 - iii. **Silver infiltrated tungsten containing 80% by weight or more of tungsten; and**
 - 2. **Able to be machined to any of the following products:**
 - i. **Cylinders having a diameter of 120 mm or greater and a length of 50 mm or greater;**
 - ii. **Tubes having an inner diameter of 65 mm or greater and a wall thickness of 25 mm or greater and a length of 50 mm or greater; or**
 - iii. **Blocks having a size of 120 mm x 120 mm x 50 mm or greater.**
- 6.C.8. Maraging steels having an ultimate tensile strength equal to or greater than 1.5 GPa, measured at 20°C, in the form of sheet, plate or tubing with a wall or plate thickness equal to or less than 5.0 mm usable in systems specified in 1.A. or 19.A.1.

Technical Note:

Maraging steels are iron alloys generally characterised by high nickel, very low carbon content and use substitutional elements or precipitates to produce strengthening and age-hardening of the alloy.

- 6.C.9. Titanium-stabilized duplex stainless steel (Ti-DSS) usable in the systems specified in 1.A. or 19.A.1. and having all of the following:
- a. Having all of the following characteristics:
 - 1. Containing 17.0 - 23.0 weight percent chromium and 4.5 - 7.0 weight percent nickel;
 - 2. Having a titanium content of greater than 0.10 weight percent; and
 - 3. A ferritic-austenitic microstructure (also referred to as a two-phase microstructure) of which at least 10% is austenite by volume (according to ASTM E-1181-87 or national equivalents); and
 - b. Any of the following forms:
 - 1. Ingots or bars having a size of 100 mm or more in each dimension;
 - 2. Sheets having a width of 600 mm or more and a thickness of 3 mm or less; or

CATEGORY II; ITEM 6

3. Tubes having an outer diameter of 600 mm or more and a wall thickness of 3 mm or less.

6.D. SOFTWARE

- 6.D.1. "Software" specially designed or modified for the "use" of equipment specified in 6.B.1.
- 6.D.2. "Software" specially designed or modified for the equipment specified in 6.B.3., 6.B.4. or 6.B.5.

6.E. TECHNOLOGY

- 6.E.1. "Technology", in accordance with the General Technology Note, for the "development", "production" or "use" of equipment, materials or "software" specified in 6.A., 6.B., 6.C. or 6.D.
- 6.E.2. "Technical data" (including processing conditions) and procedures for the regulation of temperature, pressures or atmosphere in autoclaves or hydroclaves when used for the production of composites or partially processed composites, usable for equipment or materials specified in 6.A. or 6.C.
- 6.E.3. "Technology" for producing pyrolytically derived materials formed on a mould, mandrel or other substrate from precursor gases which decompose in the 1,300°C to 2,900°C temperature range at pressures of 130 Pa (1 mm Hg) to 20 kPa (150 mm Hg) including "technology" for the composition of precursor gases, flow-rates, and process control schedules and parameters.

CATEGORY II; ITEM 7

This category is intentionally left blank.

CATEGORY II; ITEM 8

This category is intentionally left blank.

CATEGORY II; ITEM 9

ITEM 9 INSTRUMENTATION, NAVIGATION AND DIRECTION FINDING

9.A. EQUIPMENT, ASSEMBLIES AND COMPONENTS

- 9.A.1. Integrated flight instrument systems which include gyrostabilisers or automatic pilots, designed or modified for use in the systems specified in 1.A., or 19.A.1. or 19.A.2. and specially designed components therefor.
- 9.A.2. Gyro-astro compasses and other devices which derive position or orientation by means of automatically tracking celestial bodies or satellites, and specially designed components therefor.
- 9.A.3. Linear accelerometers, designed for use in inertial navigation systems or in guidance systems of all types, usable in the systems specified in 1.A., 19.A.1. or 19.A.2., having all of the following characteristics, and specially designed components therefor:
- a. 'Scale factor' 'repeatability' less (better) than 1250 ppm; and
 - b. 'Bias' 'repeatability' less (better) than 1250 micro g.

Note:

Item 9.A.3. does not control accelerometers specially designed and developed as Measurement While Drilling (MWD) sensors for use in downhole well service operations.

Technical Notes:

1. 'Bias' is defined as the accelerometer output when no acceleration is applied.
2. 'Scale factor' is defined as the ratio of change in output to a change in the input.
3. The measurement of 'bias' and 'scale factor' refers to one sigma standard deviation with respect to a fixed calibration over a period of one year.
4. 'Repeatability' is defined according to IEEE Standard 528-2001 as follows: 'The closeness of agreement among repeated measurements of the same variable under the same operating conditions when changes in conditions or non-operating periods occur between measurements'.

CATEGORY II; ITEM 9

- 9.A.4. All types of gyros usable in the systems specified in 1.A., 19.A.1 or 19.A.2., with a rated 'drift rate' 'stability' of less than 0.5 degrees (1 sigma or rms) per hour in a 1 g environment, and specially designed components therefor.

Technical Notes:

1. 'Drift rate' is defined as the component of gyro output that is functionally independent of input rotation and is expressed as an angular rate. (IEEE STD 528-2001 paragraph 2.56)
2. 'Stability' is defined as a measure of the ability of a specific mechanism or performance coefficient to remain invariant when continuously exposed to a fixed operating condition. (This definition does not refer to dynamic or servo stability.) (IEEE STD 528-2001 paragraph 2.247)

- 9.A.5. Accelerometers or gyros of any type, designed for use in inertial navigation systems or in guidance systems of all types, specified to function at acceleration levels greater than 100 g, and specially designed components therefor.

Note :

9.A.5. does not include accelerometers that are designed to measure vibration or shock.

- 9.A.6. Inertial or other equipment using accelerometers specified in 9.A.3. or 9.A.5. or gyros specified in 9.A.4. or 9.A.5., and systems incorporating such equipment, and specially designed components therefor.
- 9.A.7. 'Integrated navigation systems', designed or modified for the systems specified in 1.A., 19.A.1. or 19.A.2. and capable of providing a navigational accuracy of 200 m CEP or less.

Technical Note:

An 'integrated navigation system' typically incorporates all of the following components:

- a. *An inertial measurement device (e.g. an attitude and heading reference system, inertial reference unit, or inertial navigation system);*

CATEGORY II; ITEM 9

- b. One or more external sensors used to update the position and/or velocity, either periodically or continuously throughout the flight (e.g. satellite navigation receiver, radar altimeter, and/or Doppler radar); and*
- c. Integration hardware and software.*

N.B. For integration "software", see Item 9.D.4.

- 9.A.8. Three axis magnetic heading sensors having all of the following characteristics, and specially designed components therefor:
- a. Internal tilt compensation in pitch (+/- 90 degrees) and having roll (+/- 180 degrees) axes.
 - b. Capable of providing azimuthal accuracy better (less) than 0.5 degrees rms at latitudes of +/- 80 degrees, referenced to local magnetic field; and
 - c. Designed or modified to be integrated with flight control and navigation systems.

Note:

Flight control and navigation systems in Item 9.A.8. include gyrostabilisers, automatic pilots and inertial navigation systems.

9.B. TEST AND PRODUCTION EQUIPMENT

- 9.B.1. "Production equipment", and other test, calibration and alignment equipment, other than that described in 9.B.2., designed or modified to be used with equipment specified in 9.A.

Note:

Equipment specified in 9.B.1. includes the following:

- a. For laser gyro equipment, the following equipment used to characterise mirrors, having the threshold accuracy shown or better:*
 - 1. Scatterometer (10 ppm);*
 - 2. Reflectometer (50 ppm);*
 - 3. Profilometer (5 Angstroms);*
- b. For other inertial equipment:*
 - 1. Inertial Measurement Unit (IMU) Module Tester;*
 - 2. IMU Platform Tester;*

CATEGORY II; ITEM 9

3. *IMU Stable Element Handling Fixture;*
4. *IMU Platform Balance Fixture;*
5. *Gyro Tuning Test Station;*
6. *Gyro Dynamic Balance Station;*
7. *Gyro Run-In/Motor Test Station;*
8. *Gyro Evacuation and Filling Station;*
9. *Centrifuge Fixture for Gyro Bearings;*
10. *Accelerometer Axis Align Station;*
11. *Accelerometer Test Station.*

9.B.2. Equipment as follows:

- a. Balancing machines having all the following characteristics:
 1. Not capable of balancing rotors/assemblies having a mass greater than 3 kg;
 2. Capable of balancing rotors/assemblies at speeds greater than 12,500 rpm;
 3. Capable of correcting unbalance in two planes or more; and
 4. Capable of balancing to a residual specific unbalance of 0.2 g mm per kg of rotor mass;
- b. Indicator heads (sometimes known as balancing instrumentation) designed or modified for use with machines specified in 9.B.2.a.;
- c. Motion simulators/rate tables (equipment capable of simulating motion) having all of the following characteristics:
 1. Two axes or more;
 2. Designed or modified to incorporate sliprings or integrated non-contact devices capable of transferring electrical power, signal information, or both; and
 3. Having any of the following characteristics:
 - a. For any single axis having all of the following:
 1. Capable of rates of 400 degrees/s or more, or 30 degrees/s or less; and
 2. A rate resolution equal to or less than 6 degrees/s and an accuracy equal to or less than 0.6 degrees/s;
 - b. Having a worst-case rate stability equal to or better (less) than plus or minus 0.05% averaged over 10 degrees or more; or
 - c. A positioning "accuracy" equal to or less (better) than 5 arc second;

CATEGORY II; ITEM 9

- d. Positioning tables (equipment capable of precise rotary positioning in any axes) having the following characteristics:
 - 1. Two axes or more; and
 - 2. A positioning "accuracy" equal to or less (better) than 5 arc second;
- e. Centrifuges capable of imparting accelerations above 100 g and designed or modified to incorporate sliprings or integrated non-contact devices capable of transferring electrical power, signal information, or both.

Notes:

- 1. *The only balancing machines, indicator heads, motion simulators, rate tables, positioning tables and centrifuges specified in Item 9 are those specified in 9.B.2.*
- 2. *9.B.2.a. does not control balancing machines designed or modified for dental or other medical equipment.*
- 3. *9.B.2.c. and 9.B.2.d. do not control rotary tables designed or modified for machine tools or for medical equipment.*
- 4. *Rate tables not controlled by 9.B.2.c. and providing the characteristics of a positioning table are to be evaluated according to 9.B.2.d.*
- 5. *Equipment that has the characteristics specified in 9.B.2.d. which also meets the characteristics of 9.B.2.c. will be treated as equipment specified in 9.B.2.c.*
- 6. *Item 9.B.2.c. applies whether or not sliprings or integrated non-contact devices are fitted at the time of export.*
- 7. *Item 9.B.2.e. applies whether or not sliprings or integrated non-contact devices are fitted at the time of export.*

9.C. MATERIALS

None.

CATEGORY II; ITEM 9

9.D. SOFTWARE

- 9.D.1. "Software" specially designed or modified for the "use" of equipment specified in 9.A. or 9.B.
- 9.D.2. Integration "software" for the equipment specified in 9.A.1.
- 9.D.3. Integration "software" specially designed for the equipment specified in 9.A.6.
- 9.D.4. Integration "software", designed or modified for the 'integrated navigation systems' specified in 9.A.7.

Note:

A common form of integration "software" employs Kalman filtering.

9.E. TECHNOLOGY

- 9.E.1. "Technology", in accordance with the General Technology Note, for the "development", "production" or "use" of equipment or "software" specified in 9.A., 9.B. or 9.D.

Note:

Equipment or "software" specified in 9.A. or 9.D. may be exported as part of a manned aircraft, satellite, land vehicle, marine/submarine vessel or geophysical survey equipment or in quantities appropriate for replacement parts for such applications.

CATEGORY II; ITEM 10

ITEM 10 FLIGHT CONTROL

10.A. EQUIPMENT, ASSEMBLIES AND COMPONENTS

10.A.1. Hydraulic, mechanical, electro-optical, or electromechanical flight control systems (including fly-by-wire systems) designed or modified for the systems specified in 1.A.

10.A.2. Attitude control equipment designed or modified for the systems specified in 1.A.

10.A.3. Flight control servo valves designed or modified for the systems in 10.A.1. or 10.A.2., and designed or modified to operate in a vibration environment greater than 10 g rms between 20 Hz and 2 kHz.

Note:

Systems, equipment or valves specified in 10.A. may be exported as part of a manned aircraft or satellite or in quantities appropriate for replacement parts for manned aircraft.

10.B. TEST AND PRODUCTION EQUIPMENT

10.B.1. Test, calibration, and alignment equipment specially designed for equipment specified in 10.A.

10.C. MATERIALS

None.

CATEGORY II; ITEM 10

10.D. SOFTWARE

10.D.1. "Software" specially designed or modified for the "use" of equipment specified in 10.A. or 10.B.

Note:

"Software" specified in 10.D.1. may be exported as part of a manned aircraft or satellite or in quantities appropriate for replacement parts for manned aircraft.

10.E. TECHNOLOGY

10.E.1. Design "technology" for integration of air vehicle fuselage, propulsion system and lifting control surfaces, designed or modified for the systems specified in 1.A. or 19.A.2., to optimise aerodynamic performance throughout the flight regime of an unmanned aerial vehicle.

10.E.2. Design "technology" for integration of the flight control, guidance, and propulsion data into a flight management system, designed or modified for the systems specified in 1.A. or 19.A.1., for optimisation of rocket system trajectory.

10.E.3. "Technology", in accordance with the General Technology Note, for the "development", "production" or "use" of equipment or "software" specified in 10.A., 10.B. or 10.D.

CATEGORY II; ITEM 11

ITEM 11 AVIONICS

11.A. EQUIPMENT, ASSEMBLIES AND COMPONENTS

11.A.1. Radar and laser radar systems, including altimeters, designed or modified for use in the systems specified in 1.A.

Technical Note:

Laser radar systems embody specialised transmission, scanning, receiving and signal processing techniques for utilisation of lasers for echo ranging, direction finding and discrimination of targets by location, radial speed and body reflection characteristics.

11.A.2. Passive sensors for determining bearings to specific electromagnetic sources (direction finding equipment) or terrain characteristics, designed or modified for use in the systems specified in 1.A.

11.A.3. Receiving equipment for Global Navigation Satellite Systems (GNSS; e.g. GPS, GLONASS or Galileo), having any of the following characteristics, and specially designed components therefor:

- a. Designed or modified for use in systems specified in 1.A.; or
- b. Designed or modified for airborne applications and having any of the following:
 1. Capable of providing navigation information at speeds in excess of 600 m/s;
 2. Employing decryption, designed or modified for military or governmental services, to gain access to GNSS secure signal/data; or
 3. Being specially designed to employ anti-jam features (e.g. null steering antenna or electronically steerable antenna) to function in an environment of active or passive countermeasures.

Note:

11.A.3.b.2. and 11.A.3.b.3. do not control equipment designed for commercial, civil or 'Safety of Life' (e.g. data integrity, flight safety) GNSS services.

CATEGORY II; ITEM 11

11.A.4. Electronic assemblies and components, designed or modified for use in the systems specified in 1.A. or 19.A. and specially designed for military use and operation at temperatures in excess of 125°C.

Notes:

1. *Equipment specified in 11.A. includes the following:*
 - a. *Terrain contour mapping equipment;*
 - b. *Scene mapping and correlation (both digital and analogue) equipment;*
 - c. *Doppler navigation radar equipment;*
 - d. *Passive interferometer equipment;*
 - e. *Imaging sensor equipment (both active and passive).*
2. *Equipment specified in 11.A. may be exported as part of a manned aircraft or satellite or in quantities appropriate for replacement parts for manned aircraft.*

11.B. TEST AND PRODUCTION EQUIPMENT

None.

11.C. MATERIALS

None.

11.D. SOFTWARE

11.D.1. "Software" specially designed or modified for the "use" of equipment specified in 11.A.1., 11.A.2. or 11.A.4.

11.D.2. "Software" specially designed for the "use" of equipment specified in 11.A.3.

11.E. TECHNOLOGY

11.E.1. Design "technology" for protection of avionics and electrical subsystems against Electromagnetic Pulse (EMP) and Electromagnetic Interference (EMI) hazards from external sources, as follows:

- a. Design "technology" for shielding systems;

CATEGORY II; ITEM 11

b. Design "technology" for the configuration of hardened electrical circuits and subsystems;

c. Design "technology" for determination of hardening criteria for the above.

11.E.2. "Technology", in accordance with the General Technology Note, for the "development", "production" or "use" of equipment or "software" specified in 11.A. or 11.D.

CATEGORY II; ITEM 12

ITEM 12 LAUNCH SUPPORT

12.A. EQUIPMENT, ASSEMBLIES AND COMPONENTS

12.A.1. Apparatus and devices, designed or modified for the handling, control, activation and launching of the systems specified in 1.A., 19.A.1., or 19.A.2.

12.A.2. Vehicles designed or modified for the transport, handling, control, activation and launching of the systems specified in 1.A.

12.A.3. Gravity meters (gravimeters), gravity gradiometers, and specially designed components therefor, designed or modified for airborne or marine use, and having a static or operational accuracy of $7 \times 10^{-6} \text{ m/s}^2$ (0.7 milligal) or better, with a time to steady-state registration of two minutes or less, usable for systems specified in 1.A.

12.A.4. Telemetry and telecontrol equipment, including ground equipment, designed or modified for systems specified in 1.A., 19.A.1. or 19.A.2.

Notes:

1. 12.A.4. does not control equipment designed or modified for manned aircraft or satellites.
2. 12.A.4. does not control ground based equipment designed or modified for terrestrial or marine applications.
3. 12.A.4. does not control equipment designed for commercial, civil or 'Safety of Life' (e.g. data integrity, flight safety) GNSS services.

12.A.5. Precision tracking systems, usable for systems specified in 1.A., 19.A.1. or 19.A.2. as follows:

- a. Tracking systems which use a code translator installed on the rocket or unmanned aerial vehicle in conjunction with either surface or airborne references or navigation satellite systems to provide real-time measurements of inflight position and velocity;

CATEGORY II; ITEM 12

- b. Range instrumentation radars including associated optical/infrared trackers with all of the following capabilities:
 - 1. Angular resolution better than 1.5 mrad;
 - 2. Range of 30 km or greater with a range resolution better than 10 m rms;
and
 - 3. Velocity resolution better than 3 m/s.

12.A.6. Thermal batteries designed or modified for the systems specified in 1.A., 19.A.1. or 19.A.2.

Note:

Item 12.A.6. does not control thermal batteries specially designed for rocket systems or unmanned aerial vehicles that are not capable of a "range" equal to or greater than 300 km.

Technical Note:

Thermal batteries are single use batteries that contain a solid non-conducting inorganic salt as the electrolyte. These batteries incorporate a pyrolytic material that, when ignited, melts the electrolyte and activates the battery.

12.B. TEST AND PRODUCTION EQUIPMENT

None.

12.C. MATERIALS

None.

12.D. SOFTWARE

12.D.1. "Software" specially designed or modified for the "use" of equipment specified in 12.A.1.

12.D.2. "Software" which processes post-flight, recorded data, enabling determination of vehicle position throughout its flight path, specially designed or modified for systems specified in 1.A., 19.A.1. or 19.A.2.

CATEGORY II; ITEM 12

12.D.3. "Software" specially designed or modified for the "use" of equipment specified in 12.A.4. or 12.A.5., usable for systems specified in 1.A., 19.A.1. or 19.A.2.

12.E. TECHNOLOGY

12.E.1. "Technology", in accordance with the General Technology Note, for the "development", "production" or "use" of equipment or "software" specified in 12.A. or 12.D.

CATEGORY II; ITEM 13

ITEM 13 COMPUTERS

13.A. EQUIPMENT, ASSEMBLIES AND COMPONENTS

13.A.1. Analogue computers, digital computers or digital differential analysers, designed or modified for use in the systems specified in 1.A., having any of the following characteristics:

a. Rated for continuous operation at temperatures from below -45°C to above $+55^{\circ}\text{C}$; or

b. Designed as ruggedised or "radiation hardened".

13.B. TEST AND PRODUCTION EQUIPMENT

None.

13.C. MATERIALS

None.

13.D. SOFTWARE

None.

13.E. TECHNOLOGY

13.E.1. "Technology", in accordance with the General Technology Note, for the "development", "production" or "use" of equipment specified in 13.A.

Note:

Item 13. equipment may be exported as part of a manned aircraft or satellite or in quantities appropriate for replacement parts for manned aircraft.

CATEGORY II; ITEM 14

ITEM 14 ANALOGUE TO DIGITAL CONVERTERS

14.A. EQUIPMENT, ASSEMBLIES AND COMPONENTS

14.A.1. Analogue-to-digital converters, usable in the systems specified in 1.A., having any of the following characteristics:

- a. Designed to meet military specifications for ruggedised equipment; or
- b. Designed or modified for military use and being any of the following types:
 1. Analogue-to-digital converter "microcircuits", which are "radiation-hardened" or have all of the following characteristics:
 - a. Having a quantisation corresponding to 8 bits or more when coded in the binary system;
 - b. Rated for operation in the temperature range from below -54°C to above $+125^{\circ}\text{C}$; and
 - c. Hermetically sealed; or
 2. Electrical input type analogue-to-digital converter printed circuit boards or modules, having all of the following characteristics:
 - a. Having a quantisation corresponding to 8 bits or more when coded in the binary system;
 - b. Rated for operation in the temperature range from below -45°C to above $+55^{\circ}\text{C}$; and
 - c. Incorporating "microcircuits" specified in 14.A.1.b.1.

14.B. TEST AND PRODUCTION EQUIPMENT

None.

14.C. MATERIALS

None.

14.D. SOFTWARE

None.

CATEGORY II; ITEM 14

14.E. TECHNOLOGY

14.E.1. "Technology", in accordance with the General Technology Note, for the "development", "production" or "use" of equipment specified in 14.A.

CATEGORY II; ITEM 15

ITEM 15 TEST FACILITIES AND EQUIPMENT

15.A. EQUIPMENT, ASSEMBLIES AND COMPONENTS

None.

15.B. TEST AND PRODUCTION EQUIPMENT

15.B.1. Vibration test equipment, usable for the systems specified in 1.A., 19.A.1. or 19.A.2. or the subsystems specified in 2.A. or 20.A., and components therefor, as follows:

- a. Vibration test systems employing feedback or closed loop techniques and incorporating a digital controller, capable of vibrating a system at an acceleration equal to or greater than 10 g rms between 20 Hz and 2 kHz while imparting forces equal to or greater than 50 kN, measured 'bare table';
- b. Digital controllers, combined with specially designed vibration test "software", with a 'real-time control bandwidth' greater than 5 kHz and designed for use with vibration test systems specified in 15.B.1.a.;

Technical Note:

'Real-time control bandwidth' is defined as the maximum rate at which a controller can execute complete cycles of sampling, processing data and transmitting control signals.

- c. Vibration thrusters (shaker units), with or without associated amplifiers, capable of imparting a force equal to or greater than 50 kN, measured 'bare table', and usable in vibration test systems specified in 15.B.1.a.;
- d. Test piece support structures and electronic units designed to combine multiple shaker units into a complete shaker system capable of providing an effective combined force equal to or greater than 50 kN, measured 'bare table', and usable in vibration test systems specified in 15.B.1.a.

CATEGORY II; ITEM 15

Technical Note:

Vibration test systems incorporating a digital controller are those systems, the functions of which are, partly or entirely, automatically controlled by stored and digitally coded electrical signals.

- 15.B.2. Wind-tunnels for speeds of Mach 0.9 or more, usable for the systems specified in 1.A. or 19.A. or the subsystems specified in 2.A. or 20.A.
- 15.B.3. Test benches/stands, usable for the systems specified in 1.A., 19.A.1. or 19.A.2. or the subsystems specified in 2.A. or 20.A., which have the capacity to handle solid or liquid propellant rockets, motors or engines having a thrust greater than 68 kN, or which are capable of simultaneously measuring the three axial thrust components.
- 15.B.4. Environmental chambers as follows, usable for the systems specified in 1.A. or 19.A. or the subsystems specified in 2.A. or 20.A.:
- a. Environmental chambers capable of simulating all the following flight conditions:
 1. Having any of the following:
 - a. Altitude equal to or greater than 15 km; or
 - b. Temperature range from below -50°C to above 125°C ; and
 2. Incorporating, or designed or modified to incorporate, a shaker unit or other vibration test equipment to produce vibration environments equal to or greater than 10 g rms, measured 'bare table', between 20 Hz and 2 kHz imparting forces equal to or greater than 5 kN;

Technical Notes:

1. *Item 15.B.4.a.2. describes systems that are capable of generating a vibration environment with a single wave (e.g. a sine wave) and systems capable of generating a broad band random vibration (i.e. power spectrum).*
2. *In Item 15.B.4.a.2., designed or modified means the environmental chamber provides appropriate interfaces (e.g. sealing devices) to*

CATEGORY II; ITEM 15

incorporate a shaker unit or other vibration test equipment as specified in this Item.

- b. Environmental chambers capable of simulating all of the following flight conditions:
 - 1. Acoustic environments at an overall sound pressure level of 140 dB or greater (referenced to $2 \times 10^{-5} \text{ N/m}^2$) or with a total rated acoustic power output of 4 kW or greater; and
 - 2. Any of the following:
 - a. Altitude equal to or greater than 15 km; or
 - b. Temperature range from below -50°C to above 125°C .

15.B.5. Accelerators capable of delivering electromagnetic radiation produced by bremsstrahlung from accelerated electrons of 2 MeV or greater, and equipment containing those accelerators, usable for the systems specified in 1.A., 19.A.1. or 19.A.2. or the subsystems specified in 2.A. or 20.A.

Note:

15.B.5. does not control equipment specially designed for medical purposes.

Technical Note:

In Item 15.B. 'bare table' means a flat table, or surface, with no fixture or fittings.

15.C. MATERIALS

None.

15.D. SOFTWARE

15.D.1. "Software" specially designed or modified for the "use" of equipment specified in 15.B. usable for testing systems specified in 1.A., 19.A.1. or 19.A.2. or subsystems specified in 2.A. or 20.A.

CATEGORY II; ITEM 15

15.E. TECHNOLOGY

- 15.E.1. "Technology", in accordance with the General Technology Note, for the "development", "production" or "use" of equipment or "software" specified in 15.B. or 15.D.**

CATEGORY II; ITEM 16

ITEM 16 MODELLING-SIMULATION AND DESIGN INTEGRATION

16.A. EQUIPMENT, ASSEMBLIES AND COMPONENTS

16.A.1. Specially designed hybrid (combined analogue/digital) computers for modelling, simulation or design integration of systems specified in 1.A. or the subsystems specified in 2.A.

Note:

This control only applies when the equipment is supplied with "software" specified in 16.D.1.

16.B. TEST AND PRODUCTION EQUIPMENT

None.

16.C. MATERIALS

None.

16.D. SOFTWARE

16.D.1. "Software" specially designed for modelling, simulation, or design integration of the systems specified in 1.A. or the subsystems specified in 2.A or 20.A.

Technical Note:

The modelling includes in particular the aerodynamic and thermodynamic analysis of the systems.

16.E. TECHNOLOGY

16.E.1. "Technology", in accordance with the General Technology Note, for the "development", "production" or "use" of equipment or "software" specified in 16.A. or 16.D.

CATEGORY II; ITEM 17

ITEM 17 STEALTH

17.A. EQUIPMENT, ASSEMBLIES AND COMPONENTS

17.A.1. Devices for reduced observables such as radar reflectivity, ultraviolet/infrared signatures and acoustic signatures (i.e. stealth technology), for applications usable for the systems specified in 1.A. or 19.A. or the subsystems specified in 2.A. or 20.A.

17.B. TEST AND PRODUCTION EQUIPMENT

17.B.1. Systems, specially designed for radar cross section measurement, usable for the systems specified in 1.A., 19.A.1. or 19.A.2. or the subsystems specified in 2.A.

17.C. MATERIALS

17.C.1. Materials for reduced observables such as radar reflectivity, ultraviolet/infrared signatures and acoustic signatures (i.e. stealth technology), for applications usable for the systems specified in 1.A. or 19.A. or the subsystems specified in 2.A.

Notes:

1. 17.C.1. includes structural materials and coatings (including paints), specially designed for reduced or tailored reflectivity or emissivity in the microwave, infrared or ultraviolet spectra.

2. 17.C.1. does not control coatings (including paints) when specially used for thermal control of satellites.

17.D. SOFTWARE

17.D.1. "Software" specially designed for reduced observables such as radar reflectivity, ultraviolet/infrared signatures and acoustic signatures (i.e. stealth technology), for applications usable for the systems specified in 1.A. or 19.A. or the subsystems specified in 2.A.

CATEGORY II; ITEM 17

Note:

17.D.1. includes "software" specially designed for analysis of signature reduction.

17.E. TECHNOLOGY

17.E.1. "Technology", in accordance with the General Technology Note, for the "development", "production" or "use" of equipment, materials or "software" specified in 17.A., 17.B., 17.C. or 17.D.

Note:

17.E.1. includes databases specially designed for analysis of signature reduction.

CATEGORY II; ITEM 18

ITEM 18 NUCLEAR EFFECTS PROTECTION

18.A. EQUIPMENT, ASSEMBLIES AND COMPONENTS

18.A.1. "Radiation Hardened" "microcircuits" usable in protecting rocket systems and unmanned aerial vehicles against nuclear effects (e.g. Electromagnetic Pulse (EMP), X-rays, combined blast and thermal effects), and usable for the systems specified in 1.A.

18.A.2. 'Detectors' specially designed or modified to protect rocket systems and unmanned aerial vehicles against nuclear effects (e.g. Electromagnetic Pulse (EMP), X-rays, combined blast and thermal effects), and usable for the systems specified in 1.A.

Technical Note:

A 'detector' is defined as a mechanical, electrical, optical or chemical device that automatically identifies and records, or registers a stimulus such as an environmental change in pressure or temperature, an electrical or electromagnetic signal or radiation from a radioactive material. This includes devices that sense by one time operation or failure.

18.A.3. Radomes designed to withstand a combined thermal shock greater than $4.184 \times 10^6 \text{ J/m}^2$ accompanied by a peak over pressure of greater than 50 kPa, usable in protecting rocket systems and unmanned aerial vehicles against nuclear effects (e.g. Electromagnetic Pulse (EMP), X-rays, combined blast and thermal effects), and usable for the systems specified in 1.A.

18.B. TEST AND PRODUCTION EQUIPMENT

None.

18.C. MATERIALS

None.

18.D. SOFTWARE

None.

CATEGORY II; ITEM 18

18.E. TECHNOLOGY

18.E.1. "Technology", in accordance with the General Technology Note, for the "development", "production" or "use" of equipment specified in 18.A.

CATEGORY II; ITEM 19

ITEM 19 OTHER COMPLETE DELIVERY SYSTEMS

19.A. EQUIPMENT, ASSEMBLIES AND COMPONENTS

19.A.1. Complete rocket systems (including ballistic missile systems, space launch vehicles, and sounding rockets), not specified in 1.A.1., capable of a "range" equal to or greater than 300 km.

19.A.2. Complete unmanned aerial vehicle systems (including cruise missile systems, target drones and reconnaissance drones), not specified in 1.A.2., capable of a "range" equal to or greater than 300 km.

19.A.3. Complete unmanned aerial vehicle systems, not specified in 1.A.2. or 19.A.2., having all of the following:

a. Having any of the following:

1. An autonomous flight control and navigation capability; or
2. Capability of controlled flight out of the direct vision range involving a human operator; and

b. Having any of the following:

1. Incorporating an aerosol dispensing system/mechanism with a capacity greater than 20 litres; or
2. Designed or modified to incorporate an aerosol dispensing system/mechanism with a capacity greater than 20 litres.

Note:

Item 19.A.3. does not control model aircraft, specially designed for recreational or competition purposes.

Technical Notes:

1. An aerosol consists of particulate or liquids other than fuel components, by-products or additives, as part of the "payload" to be dispersed in the atmosphere. Examples of aerosols include pesticides for crop dusting and dry chemicals for cloud seeding.

CATEGORY II; ITEM 19

2. An aerosol dispensing system/mechanism contains all those devices (mechanical, electrical, hydraulic, etc.), which are necessary for storage and dispersion of an aerosol into the atmosphere. This includes the possibility of aerosol injection into the combustion exhaust vapour and into the propeller slip stream.

19.B. TEST AND PRODUCTION EQUIPMENT

None.

19.C. MATERIALS

None.

19.D. SOFTWARE

19.D.1. "Software" which coordinates the function of more than one subsystem, specially designed or modified for "use" in the systems specified in 19.A.1. or 19.A.2.

19.E. TECHNOLOGY

19.E.1. "Technology", in accordance with the General Technology Note, for the "development", "production" or "use" of equipment specified in 19.A. 1. or 19.A.2.

CATEGORY II; ITEM 20

ITEM 20 OTHER COMPLETE SUBSYSTEMS

20.A. EQUIPMENT, ASSEMBLIES AND COMPONENTS

20.A.1. Complete subsystems as follows:

- a. Individual rocket stages, not specified in 2.A.1., usable in systems specified in 19.A.;
- b. Solid propellant rocket motors or liquid propellant rocket engines, not specified in 2.A.1., usable in systems specified in 19.A., having a total impulse capacity equal to or greater than 8.41×10^5 Ns, but less than 1.1×10^6 Ns.

20.B. TEST AND PRODUCTION EQUIPMENT

20.B.1. "Production facilities" specially designed for the subsystems specified in 20.A.

20.B.2. "Production equipment" specially designed for the subsystems specified in 20.A.

20.C. MATERIALS

None.

20.D. SOFTWARE

20.D.1. "Software" specially designed or modified for the systems specified in 20.B.1.

20.D.2. "Software", not specified in 2.D.2., specially designed or modified for the "use" of rocket motors or engines specified in 20.A.1.b.

20.E. TECHNOLOGY

20.E.1. "Technology", in accordance with the General Technology Note, for the "development", "production" or "use" of equipment or "software" specified in 20.A., 20.B. or 20.D.

UNITS, CONSTANTS, ACRONYMS AND ABBREVIATIONS

UNITS, CONSTANTS, ACRONYMS AND ABBREVIATIONS

USED IN THIS ANNEX

ABEC	Annular Bearing Engineers Committee
ABMA	American Bearing Manufacturers Association
ANSI	American National Standards Institute
Angstrom	1×10^{-10} metre
ASTM	American Society for Testing and Materials
bar	unit of pressure
°C	degree Celsius
cc	cubic centimetre
CAS	Chemical Abstracts Service
CEP	Circle of Equal Probability
dB	decibel
g	gram; also, acceleration due to gravity
GHz	gigahertz
GNSS	Global Navigation Satellite System e.g. 'Galileo'
	'GLONASS' - Global'naya Navigatsionnaya Sputnikovaya Sistema
	'GPS' - Global Positioning System
h	hour
Hz	hertz
HTPB	Hydroxy-Terminated Polybutadiene
ICAO	International Civil Aviation Organisation
IEEE	Institute of Electrical and Electronic Engineers
IR	Infrared
ISO	International Organization for Standardization
J	joule
JIS	Japanese Industrial Standard
K	Kelvin
kg	kilogram
kHz	kilohertz
km	kilometre
kN	kilonewton
kPa	kilopascal
kW	kilowatt
m	metre
MeV	million electron volt or mega electron volt
MHz	megahertz
milligal	10^{-5} m/s^2 (also called mGal, mgal or milligalileo)
mm	millimetre
mm Hg	mm of mercury
MPa	megapascal
mrad	milliradian
ms	millisecond
µm	micrometre

UNITS, CONSTANTS, ACRONYMS AND ABBREVIATIONS

N	newton
Pa	pascal
ppm	parts per million
rads (Si)	radiation absorbed dose
RF	radio frequency
rms	root mean square
rpm	revolutions per minute
RV	Re-entry Vehicles
s	second
Tg	glass transition temperature
Tyler	Tyler mesh size, or Tyler standard sieve series
UAV	Unmanned Aerial Vehicle
UV	Ultra violet

TABLE OF CONVERSIONS

<u>TABLE OF CONVERSIONS USED IN THIS ANNEX</u>		
Unit (from)	Unit (to)	Conversion
bar	pascal (Pa)	1 bar = 100 kPa
g (gravity)	m/s ²	1 g = 9.806 65 m/s ²
mrاد (millirad)	degrees (angle)	1 mrاد ≈ 0.0573°
rads	ergs/gram of Si	1 rad (Si) = 100 ergs/gram of silicon (= 0.01 gray [Gy])
Tyler 250 mesh	mm	for a Tyler 250 mesh, mesh opening 0.063 mm

ADDENDUM – STATEMENT OF UNDERSTANDING

Statement of Understanding

In those cases where the term "national equivalents" are specifically allowed as alternatives to specified International Standards, the technical methods and parameters embodied in the national equivalent would ensure that the requirements of the standard set by the specified International Standards are met.

SECOND SCHEDULE

(Paragraph 3)

ANNEX TO RESOLUTION 1737 (2006)

A. Entities involved in the nuclear programme

1. Atomic Energy Organisation of Iran
2. Mesbah Energy Company (provider for A40 research reactor — Arak)
3. Kala-Electric (aka Kalaye Electric) (provider for PFEP — Natanz)
4. Pars Trash Company (involved in centrifuge programme, identified in IAEA reports)
5. Farayand Technique (involved in centrifuge programme, identified in IAEA reports)
6. Defence Industries Organisation (overarching MODAFL-controlled entity, some of whose subordinates have been involved in the centrifuge programme making components, and in the missile programme)
7. 7th of Tir (subordinate of DIO, widely recognized as being directly involved in the nuclear programme)

B. Entities involved in the ballistic missile programme

1. Shahid Hemmat Industrial Group (SHIG) (subordinate entity of AIO)
2. Shahid Bagheri Industrial Group (SBIG) (subordinate entity of AIO)
3. Fajr Industrial Group (formerly Instrumentation Factory Plant, subordinate entity of AIO)

C. Persons involved in the nuclear programme

1. Mohammad Qannadi, AEOI Vice President for Research & Development
2. Behman Asgarpour, Operational Manager (Arak)
3. Dawood Agha-Jani, Head of the PFEP (Natanz)
4. Ehsan Monajemi, Construction Project Manager, Natanz
5. Jafar Mohammadi, Technical Adviser to the AEOI (in charge of managing the production of valves for centrifuges)
6. Ali Hajinia Leilabadi, Director General of Mesbah Energy Company
7. Lt Gen Mohammad Mehdi Nejad Nouri, Rector of Malek Ashtar University of Defence Technology (chemistry dept, affiliated to MODALF, has conducted experiments on beryllium)

D. Persons involved in the ballistic missile programme

1. Gen Hosein Salimi, Commander of the Air Force, IRGC (Pasdaran)
2. Ahmad Vahid Dastjerdi, Head of the AIO

3. Reza-Gholi Esmaeli, Head of Trade & International Affairs Dept, AIO
4. Bahmanyar Morteza Bahmanyar, Head of Finance & Budget Dept, AIO

E. Person(s) involved in both the nuclear and ballistic missile programmes

1. Maj Gen Yahya Rahim Safavi, Commander, IRGC (Pasdaran)

ANNEX I TO RESOLUTION 1747 (2007)

A. Entities involved in nuclear or ballistic missile activities

1. Ammunition and Metallurgy Industries Group (AMIG) (aka Ammunition Industries Group) (AMIG controls 7th of Tir, which is designated under resolution 1737 (2006) for its role in Iran's centrifuge programme. AMIG is in turn owned and controlled by the Defence Industries Organisation (DIO), which is designated under resolution 1737 (2006))
2. Esfahan Nuclear Fuel Research and Production Centre (NFRPC) and Esfahan Nuclear Technology Centre (ENTC) (Parts of the Atomic Energy Organisation of Iran's (AEOI) Nuclear Fuel Production and Procurement Company, which is involved in enrichment-related activities. AEOI is designated under resolution 1737 (2006))
3. Kavoshyar Company (Subsidiary company of AEOI, which has sought glass fibres, vacuum chamber furnaces and laboratory equipment for Iran's nuclear programme)
4. Parchin Chemical Industries (Branch of DIO, which produces ammunition, explosives, as well as solid propellants for rockets and missiles)
5. Karaj Nuclear Research Centre (Part of AEOI's research division)
6. Novin Energy Company (aka Pars Novin) (Operates within AEOI and has transferred funds on behalf of AEOI to entities associated with Iran's nuclear programme)
7. Cruise Missile Industry Group (aka Naval Defence Missile Industry Group) (Production and development of cruise missiles. Responsible for naval missiles including cruise missiles)
8. Bank Sepah and Bank Sepah International (Bank Sepah provides support for the Aerospace Industries Organisation (AIO) and subordinates, including Shahid Hemmat Industrial Group (SHIG) and Shahid Bagheri Industrial Group (SBIG), both of which were designated under resolution 1737 (2006))
9. Sanam Industrial Group (subordinate to AIO, which has purchased equipment on AIO's behalf for the missile programme)
10. Ya Mahdi Industries Group (subordinate to AIO, which is involved in international purchases of missile equipment)

B. Iranian Revolutionary Guard Corps entities

1. Qods Aeronautics Industries (Produces unmanned aerial vehicles (UAVs), parachutes, para-gliders, para-motors, etc. Iranian Revolutionary Guard Corps (IRGC) has boasted of using these products as part of its asymmetric warfare doctrine)
2. Pars Aviation Services Company (Maintains various aircraft including MI-171, used by IRGC Air Force)
3. Sho'a' Aviation (Produces micro-lights which IRGC has claimed it is using as part of its asymmetric warfare doctrine)

C. Persons involved in nuclear or ballistic missile activities

1. Fereidoun Abbasi-Davani (Senior Ministry of Defence and Armed Forces Logistics (MODAFL) scientist with links to the Institute of Applied Physics, working closely with Mohsen Fakhrizadeh-Mahabadi, designated below)
2. Mohsen Fakhrizadeh-Mahabadi (Senior MODAFL scientist and former head of the Physics Research Centre (PHRC). The IAEA have asked to interview him about the activities of the PHRC over the period he was head but Iran has refused)
3. Seyed Jaber Safdari (Manager of the Natanz Enrichment Facilities)
4. Amir Rahimi (Head of Esfahan Nuclear Fuel Research and Production Center, which is part of the AEOI's Nuclear Fuel Production and Procurement Company, which is involved in enrichment-related activities)
5. Mohsen Hojati (Head of Fajr Industrial Group, which is designated under resolution 1737 (2006) for its role in the ballistic missile programme)
6. Mehrdada Akhlaghi Ketabachi (Head of SBIG, which is designated under resolution 1737 (2006) for its role in the ballistic missile programme)
7. Naser Maleki (Head of SHIG, which is designated under resolution 1737 (2006) for its role in Iran's ballistic missile programme. Naser Maleki is also a MODAFL official overseeing work on the Shahab-3 ballistic missile programme. The Shahab-3 is Iran's long range ballistic missile currently in service)
8. Ahmad Derakhshandeh (Chairman and Managing Director of Bank Sepah, which provides support for the AIO and subordinates, including SHIG and SBIG, both of which were designated under resolution 1737 (2006))

D. Iranian Revolutionary Guard Corps key persons

1. Brigadier General Morteza Rezaie (Deputy Commander of IRGC)
2. Vice Admiral Ali Akbar Ahmadian (Chief of IRGC Joint Staff)
3. Brigadier General Mohammad Reza Zahedi (Commander of IRGC Ground Forces)

4. Rear Admiral Morteza Safari (Commander of IRGC Navy)
5. Brigadier General Mohammad Hejazi (Commander of Bassij resistance force)
6. Brigadier General Qasem Soleimani (Commander of Qods force)
7. General Zolqadr (IRGC officer, Deputy Interior Minister for Security Affairs)

ANNEX I TO RESOLUTION 1803 (2008)

1. Amir Moayyed Alai (involved in managing the assembly and engineering of centrifuges)
2. Mohammad Fedai Ashiani (involved in the production of ammonium uranyl carbonate and management of the Natanz enrichment complex)
3. Abbas Rezaee Ashtiani (a senior official at the AEOI Office of Exploration and Mining Affairs)
4. Haleh Bakhtiar (involved in the production of magnesium at a concentration of 99.9%)
5. Morteza Behzad (involved in making centrifuge components)
6. Dr. Mohammad Eslami (Head of Defence Industries Training and Research Institute)
7. Seyyed Hussein Hosseini (AEOI official involved in the heavy water research reactor project at Arak)
8. M. Javad Karimi Sabet (Head of Novin Energy Company, which is designated under resolution 1747 (2007))
9. Hamid-Reza Mohajerani (involved in production management at the Uranium Conversion Facility (UCF) at Esfahan)
10. Brigadier-General Mohammad Reza Naqdi (former Deputy Chief of Armed Forces General Staff for Logistics and Industrial Research/Head of State Anti-Smuggling Headquarters, engaged in efforts to get round the sanctions imposed by resolutions 1737 (2006) and 1747 (2007))
11. Houshang Nobari (involved in the management of the Natanz enrichment complex)
12. Abbas Rashidi (involved in enrichment work at Natanz)
13. Ghasem Soleymani (Director of Uranium Mining Operations at the Saghand Uranium Mine)

ANNEX III TO RESOLUTION 1803 (2008)

1. Abzar Boresh Kaveh Co. (BK Co.) (involved in the production of centrifuge components)
2. Barzagani Tejarat Tavanmad Saccal companies (subsidiary of Saccal System companies) (this company tried to purchase sensitive goods for an entity listed in resolution 1737 (2006))
3. Electro Sanam Company (E. S. Co./E. X. Co.) (AIO front-company, involved in the ballistic missile programme)

4. Ettehad Technical Group (AIO front-company, involved in the ballistic missile programme)
5. Industrial Factories of Precision (IFP) Machinery (aka Instrumentation Factories Plant) (used by AIO for some acquisition attempts)
6. Jabber Ibn Hayan (AEOI laboratory involved in fuel-cycle activities)
7. Joza Industrial Co. (AIO front-company, involved in the ballistic missile programme)
8. Khorasan Metallurgy Industries (subsidiary of the Ammunition Industries Group (AMIG) which depends on DIO. Involved in the production of centrifuges components)
9. Niru Battery Manufacturing Company (subsidiary of the DIO. Its role is to manufacture power units for the Iranian military including missile systems)
10. Pishgam (Pioneer) Energy Industries (has participated in construction of the Uranium Conversion Facility at Esfahan)
11. Safety Equipment Procurement (SEP) (AIO front-company, involved in the ballistic missile programme)
12. TAMAS Company (involved in enrichment-related activities. TAMAS is the overarching body, under which four subsidiaries have been established, including one for uranium extraction to concentration and another in charge of uranium processing, enrichment and waste)

ANNEX I TO RESOLUTION 1929 (2010)

A. Entities involved in nuclear or ballistic missile activities

1. **Amin Industrial Complex:** Amin Industrial Complex sought temperature controllers which may be used in nuclear research and operational/production facilities. Amin Industrial Complex is owned or controlled by, or acts on behalf of, the Defense Industries Organization (DIO), which was designated in resolution 1737 (2006). Location: P.O. Box 91735-549, Mashad, Iran; Amin Industrial Estate, Khalage Rd., Seyedi District, Mashad, Iran; Kaveh Complex, Khalaj Rd., Seyedi St., Mashad, Iran A.K.A.: Amin Industrial Compound and Amin Industrial Company
2. **Armament Industries Group:** Armament Industries Group (AIG) manufactures and services a variety of small arms and light weapons, including large- and medium-calibre guns and related technology. AIG conducts the majority of its procurement activity through Hadid Industries Complex. Location: Sepah Islam Road, Karaj Special Road Km 10, Iran; Pasdaran Ave., P.O. Box 19585/777, Tehran, Iran
3. **Defense Technology and Science Research Center:** Defense Technology and Science Research Center (DTSRC) is owned or controlled by, or acts on behalf of, Iran's Ministry of Defense and Armed Forces Logistics (MODAFL), which oversees Iran's defence R&D, production,

- maintenance, exports, and procurement. Location: Pasdaran Ave, PO Box 19585/777, Tehran, Iran
4. Doostan International Company: Doostan International Company (DICO) supplies elements to Iran's ballistic missile program
 5. Farasakht Industries: Farasakht Industries is owned or controlled by, or act on behalf of, the Iran Aircraft Manufacturing Company, which in turn is owned or controlled by MODAFL. Location: P.O. Box 83145-311, Kilometer 28, Esfahan-Tehran Freeway, Shahin Shahr, Esfahan, Iran
 6. First East Export Bank, P.L.C.: First East Export Bank, PLC is owned or controlled by, or acts on behalf of, Bank Mellat. Over the last seven years, Bank Mellat has facilitated hundreds of millions of dollars in transactions for Iranian nuclear, missile, and defense entities. Location: Unit Level 10 (B1), Main Office Tower, Financial Park Labuan, Jalan Merdeka, 87000 WP Labuan, Malaysia; Business Registration Number LL06889 (Malaysia)
 7. Kaveh Cutting Tools Company: Kaveh Cutting Tools Company is owned or controlled by, or acts on behalf of, the DIO. Location: 3rd Km of Khalaj Road, Seyyedi Street, Mashad 91638, Iran; Km 4 of Khalaj Road, End of Seyyedi Street, Mashad, Iran; P.O. Box 91735-549, Mashad, Iran; Khalaj Rd., End of Seyyedi Alley, Mashad, Iran; Moqan St., Pasdaran St., Pasdaran Cross Rd., Tehran, Iran
 8. M. Babaie Industries: M. Babaie Industries is subordinate to Shahid AhmadKazemi Industries Group (formally the Air Defense Missile Industries Group) of Iran's Aerospace Industries Organization (AIO). AIO controls the missile organizations Shahid Hemmat Industrial Group (SHIG) and the Shahid Bakeri Industrial Group (SBIG), both of which were designated in resolution 1737 (2006). Location: P.O. Box 16535-76, Tehran, 16548, Iran
 9. Malek Ashtar University: A subordinate of the DTRSC within MODAFL. This includes research groups previously falling under the Physics Research Center (PHRC). IAEA inspectors have not been allowed to interview staff or see documents under the control of this organization to resolve the outstanding issue of the possible military dimension to Iran's nuclear program. Location: Corner of Imam Ali Highway and Babaei Highway, Tehran, Iran
 10. Ministry of Defense Logistics Export: Ministry of Defense Logistics Export (MODLEX) sells Iranian-produced arms to customers around the world in contravention of resolution 1747 (2007), which prohibits Iran from selling arms or related materiel. Location: PO Box 16315-189, Tehran, Iran; located on the west side of Dabestan Street, Abbas Abad District, Tehran, Iran
 11. Mizan Machinery Manufacturing: Mizan Machinery Manufacturing (3M) is owned or controlled by, or acts on behalf of, SHIG. Location: P.O. Box 16595-365, Tehran, Iran A.K.A.: 3MG
 12. Modern Industries Technique Company: Modern Industries Technique Company (MITEC) is responsible for design and construction of the IR-40 heavy water reactor in Arak. MITEC has

spearheaded procurement for the construction of the IR-40 heavy water reactor. Location: Arak, Iran A.K.A.: Rahkar Company, Rahkar Industries, Rahkar Sanaye Company, Rahkar Sanaye Novin

13. Nuclear Research Center for Agriculture and Medicine: The Nuclear Research Center for Agriculture and Medicine (NFRPC) is a large research component of the Atomic Energy Organization of Iran (AEOI), which was designated in resolution 1737 (2006). The NFRPC is AEOI's center for the development of nuclear fuel and is involved in enrichment-related activities. Location: P.O. Box 31585-4395, Karaj, Iran A.K.A.: Center for Agricultural Research and Nuclear Medicine; Karaji Agricultural and Medical Research Center
14. Pejman Industrial Services Corporation: Pejman Industrial Services Corporation is owned or controlled by, or acts on behalf of, SBIG. Location: P.O. Box 16785-195, Tehran, Iran
15. Sabalan Company: Sabalan is a cover name for SHIG. Location: Damavand Tehran Highway, Tehran, Iran
16. Sahand Aluminum Parts Industrial Company (SAPICO): SAPICO is a cover name for SHIG. Location: Damavand Tehran Highway, Tehran, Iran
17. Shahid Karrazi Industries: Shahid Karrazi Industries is owned or controlled by, or act on behalf of, SBIG. Location: Tehran, Iran
18. Shahid Satarri Industries: Shahid Sattari Industries is owned or controlled by, or acts on behalf of, SBIG. Location: Southeast Tehran, Iran A.K.A.: Shahid Sattari Group Equipment Industries
19. Shahid Sayyade Shirazi Industries: Shahid Sayyade Shirazi Industries (SSSI) is owned or controlled by, or acts on behalf of, the DIO. Location: Next To Nirou Battery Mfg. Co, Shahid Babaii Expressway, Nobonyad Square, Tehran, Iran; Pasdaran St., P.O. Box 16765, Tehran 1835, Iran; Babaei Highway — Next to Niru M.F.G, Tehran, Iran
20. Special Industries Group: Special Industries Group (SIG) is a subordinate of DIO. Location: Pasdaran Avenue, PO Box 19585/777, Tehran, Iran
21. Tiz Pars: Tiz Pars is a cover name for SHIG. Between April and July 2007, Tiz Pars attempted to procure a five axis laser welding and cutting machine, which could make a material contribution to Iran's missile program, on behalf of SHIG. Location: Damavand Tehran Highway, Tehran, Iran
22. Yazd Metallurgy Industries: Yazd Metallurgy Industries (YMI) is a subordinate of DIO. Location: Pasdaran Avenue, Next To Telecommunication Industry, Tehran 16588, Iran; Postal Box 89195/878, Yazd, Iran; P.O. Box 89195-678, Yazd, Iran; Km 5 of Taft Road, Yazd, Iran A.K.A.: Yazd Ammunition Manufacturing and Metallurgy Industries, Directorate of Yazd Ammunition and Metallurgy Industries

B. Person(s) involved in nuclear or ballistic missile activities

1. Javad Rahiqi: Head of the Atomic Energy Organization of Iran (AEOI) Esfahan Nuclear Technology Center (additional information: DOB: 24 April 1954; POB: Marshad)

ANNEX II TO RESOLUTION 1929 (2010)

A. Entities owned, controlled, or acting on behalf of the Islamic Revolutionary Guard Corps

1. Fater (or Faater) Institute: Khatam al-Anbiya (KAA) subsidiary. Fater has worked with foreign suppliers, likely on behalf of other KAA companies on IRGC projects in Iran
2. Gharagahe Sazandegi Ghaem: Gharagahe Sazandegi Ghaem is owned or controlled by KAA
3. Ghorb Karbala: Ghorb Karbala is owned or controlled by KAA
4. Ghorb Nooh: Ghorb Nooh is owned or controlled by KAA
5. Hara Company: Owned or controlled by Ghorb Nooh
6. Imensazan Consultant Engineers Institute: Owned or controlled by, or acts on behalf of, KAA.
7. Khatam al-Anbiya Construction Headquarters: Khatam al-Anbiya Construction Headquarters (KAA) is an IRGC-owned company involved in large scale civil and military construction projects and other engineering activities. It undertakes a significant amount of work on Passive Defense Organization projects. In particular, KAA subsidiaries were heavily involved in the construction of the uranium enrichment site at Qom/Fordow
8. Makin: Makin is owned or controlled by or acting on behalf of KAA, and is a subsidiary of KAA
9. Omran Sahel: Owned or controlled by Ghorb Nooh
10. Oriental Oil Kish: Oriental Oil Kish is owned or controlled by or acting on behalf of KAA
11. Rah Sahel: Rah Sahel is owned or controlled by or acting on behalf of KAA
12. Rahab Engineering Institute: Rahab is owned or controlled by or acting on behalf of KAA, and is a subsidiary of KAA
13. Sahel Consultant Engineers: Owned or controlled by Ghorb Nooh
14. Sepanir: Sepanir is owned or controlled by or acting on behalf of KAA
15. Sepasad Engineering Company: Sepasad Engineering Company is owned or controlled by or acting on behalf of KAA

ANNEX III TO RESOLUTION 1929 (2010)

B. Entities owned, controlled, or acting on behalf of the Islamic Republic of Iran Shipping Lines (IRISL)

1. Irano Hind Shipping Company. Location: 18 Mehrshad Street, Sadaghat Street, Opposite of Park Mellat, Valie-Asr Ave., Tehran, Iran; 265, Next to Mehrshad, Sedaghat St., Opposite of Mellat Park, Vali Asr Ave., Tehran 1A001, Iran
2. IRISL Benelux NV. Location: Noorderlaan 139, B-2030, Antwerp, Belgium; V.A.T. Number BE480224531 (Belgium)
3. South Shipping Line Iran (SSL). Location: Apt. No. 7, 3rd Floor, No. 2, 4th Alley, Gandi Ave., Tehran, Iran; Qaem Magham Farahani St., Tehran, Iran”.

Made this 3rd day of December, 2010.



GOVERNOR-GENERAL